

**IEEE Standard for Information Technology—
Telecommunications and information exchange between systems
Local and metropolitan area networks—
Specific requirements**

Part 22.1: Standard to Enhance Harmful Interference Protection for Low-Power Licensed Devices Operating in TV Broadcast Bands

IEEE Computer Society

Sponsored by the
LAN/MAN Standards Committee

IEEE
3 Park Avenue
New York, NY 10016-5997
USA

IEEE Std 802.22.1™-2010

1 November 2010

**IEEE Standard for
Information Technology—
Telecommunications and information exchange
between systems—
Local and metropolitan area networks—
Specific requirements**

**Part 22.1: Standard to Enhance
Harmful Interference Protection for
Low-Power Licensed Devices
Operating in TV Broadcast Bands**

Sponsor

**LAN/MAN Standards Committee
of the
IEEE Computer Society**

Approved 30 September 2010

IEEE-SA Standards Board

Abstract: This standard defines the protocol and data formats for communication devices forming a beaconing network that are used to protect low-power, licensed devices operating in television broadcast bands from harmful interference generated by license-exempt devices, such as Wireless Regional Area Networks (WRAN), intended to operate in the same bands. The devices being protected are devices licensed as secondary under Title 47, Part 74, Subpart H in the USA and equivalent devices in other regulatory domains.

Keywords: ad hoc network, beacons, TV white space, Wireless Regional Area Networks, WRAN

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2010 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 1 November 2010. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-0-7381-6497-7 STD97037
Print: ISBN 978-0-7381-6498-4 STDPD97037

IEEE prohibits discrimination, harassment and bullying. For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

Use of an IEEE Standard is wholly voluntary. The IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEEE Standard document.

The IEEE does not warrant or represent the accuracy or content of the material contained herein, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEEE Standards documents are supplied **“AS IS.”**

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation, or every ten years for stabilization. When a document is more than five years old and has not been reaffirmed, or more than ten years old and has not been stabilized, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is the IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEEE Standards document, should rely upon the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration. A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal interpretation of the IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position, explanation, or interpretation of the IEEE. Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Recommendations to change the status of a stabilized standard should include a rationale as to why a revision or withdrawal is required.

Comments and recommendations on standards, and requests for interpretations should be addressed to:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Authorization to photocopy portions of any individual standard for internal or personal use is granted by the Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Introduction

This introduction is not part of IEEE Std 802.22.1-2010, IEEE Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements—Part 22.1: Standard to Enhance Protection for Low-Power, Licensed Devices Operating in Television Broadcast Bands.

This standard defines the protocol and data formats for communication devices offering enhanced protection for low-power, licensed devices, such as those used in the production and transmission of broadcast programs (i.e., devices licensed as secondary under Title 47, Part 74, Subpart H in the USA and equivalent devices in other regulatory domains), operating in television broadcast bands. Protection is provided through the use of a beacon, which contains information relevant to the licensed device, including its physical location and estimated duration of TV channel occupancy. The standard uses the ALOHA medium access mechanism, and all transmissions are broadcast.

The physical layer uses direct sequence spread spectrum (DSSS) with differential quadrature phase-shift keying (DQPSK). A synchronization word and countdown mechanism (i.e., time until the next beacon transmission) is transmitted continuously on the I channel, while beacons and inter-device communications are transmitted on the Q channel. Frequency, modulation rate, and transmit power vary from region to region and shall adhere to local regulations.

Notice to users

Laws and regulations

Users of these documents should consult all applicable laws and regulations. Compliance with the provisions of this standard does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

This document is copyrighted by the IEEE. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making this document available for use and adoption by public authorities and private users, the IEEE does not waive any rights in copyright to this document.

Updating of IEEE documents

Users of IEEE standards should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE Standards Association website at <http://ieeexplore.ieee.org/xpl/standards.jsp>, or contact the IEEE at the address listed previously.

For more information about the IEEE Standards Association or the IEEE standards development process, visit the IEEE-SA website at <http://standards.ieee.org>.

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/updates/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Downloads

Portions of this standard can be downloaded from the Internet. Materials include PICS tables, data tables, and code. URLs are listed in the text in the appropriate sections.

Interpretations

Current interpretations can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/interp/index.html>.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this standard was submitted to the IEEE-SA for approval, the IEEE P802.22 Working Group had the following voting members:

Apurva N. Mody, *Chair*
Gerald Chouinard, *Vice Chair*

Greg Buchwald, *P802.22.1 Chair*
Monique Bourgeois Brown, *P802.22.1 Editor-in-Chief*

Chee Wei Ang	Baowei Ji	Edgar Reihl
Kwok Shum Au	Jerome J. Kalke	Jon Rosdahl
John Benko	Ramon Khalona	William Rose
Winston Caldwell	Chang-Joo Kim	Shigenobu Sasaki
Ed Callaway	Kihong Kim	Cheng Shan
Dave Cavalcanti	Gwangzeen Ko	Steve Shellhammer
Soo-Young Chang	Stephen Kuffner	Kirk Skeba
Chris Clanton	Jeong Suk Lee	Eli Sofer
Johnny Dixon	Zhongding Lei	Myung Sun Song
Charles Einolf	Kyutae Lim	Srikathyayani Srikanteswara
Wen Gao	Jiezhen Lin	Carl R. Stevenson
Ingo Gaspard	David Mazzaresse	Victor Tawil
Monisha Ghosh	Peter Murray	James Tomcik
Joanna Guenin	Paul Nikolich	Jungsun Um
Tom Gurley	Moh Nouroozian	George Vlantis
Anh Tuan Hoang	Juha Pihlaja	Kelly Williams
Wendong Hu	Jeff Poston	Yu-chun Wu
Sung Hyun Hwang	Ranga Reddy	Changlong Xu
Tae-In Hyon	Ivan Reede	Yonghong Zeng
		Jianwei Zhang

Major contributions were received from the following individuals:

Greg Buchwald	Mingwei Jie	K. Sivanesan
Ed Callaway	Jerome J. Kalke	Yang Tang
Soo-Young Chang	Mark Kenkel	Victor Tawil
Gerald Chouinard	Stephen Kuffner	Ke Wang
Chris Clanton	Linjun Lv	Kexue Wang
Charles Einolf	David Mazzaresse	Yu-chun Wu
Paul Gorday	Tom Messerges	Zhou Wu
Garret Heath	Zhixue Shi	Jianwei Zhang
Baowei Ji	Dave Silk	Xuesheng Zhu

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Thomas Alexander	Randall Groves	Apurva N. Mody
Butch Anton	Joanna Guenin	Ronald Murias
Reza Arefi	Thomas Gurley	Peter Murray
Kwok Shum Au	Hiroshi Harada	Michael S. Newman
Alexander Awuviri	William Hayes	Charles Ngethe
Taehan Bae	Robert F. Heile	Paul Nikolich
Youngkyo Baek	Oliver Hoffmann	John Notor
Stephen Berger	Seock Deock Hong	Satoshi Obara
Gregory Best	Victor Hou	Jisung Oh
Harry Bims	David Hunter	Okundu Omeni
Gennaro Boggia	Chan-Soo Hwang	Chris Osterloh
Achim Brandt	Tae-In Hyon	Satoshi Oyama
Nancy Bravin	Tetsushi Ikegami	Jeongho Park
Monique Bourgeois Brown	Atsushi Ito	Jungshin Park
Timothy Brown	Raj Jain	William Pechey
William Byrd	Jaehyuk Jang	Venkatesha Prasad
Sean Cai	Hongkyu Jeong	Michael Probasco
Peter J. Calderon	Suryong Jeong	Henry Ptasinski
Edgar Callaway	Baowei Ji	Ivan Reede
James Carlo	Bobby Jose	Benjamin Rolfe
Juan Carreon	Woochul Jung	William Rose
Youngbin Chang	Tal Kaitz	Jaeyoung Ryu
Clint Chaplin	Hyunjeong Kang	Randall Safier
Yung-Mu Chen	Noh-Gyoung Kang	John Santhoff
Kichun Cho	Efthymios Karabetsos	Shigenobu Sasaki
Hokyuu Choi	Piotr Karocki	Bartien Sayogo
Seung-Hoon Choi	Shuzo Kato	Cheng Shan
Gerald Chouinard	Stuart J. Kerry	Stephen Shellhammer
Keith Chow	Eunkyung Kim	Jaejeong Shim
jinyong chung	Gil Kim	Changyong Shin
Jules Cohen	Sangbum Kim	Wonjae Shin
Charles Cook	Yongbum Kim	Gil Shultz
Todor Cooklev	Youngdoo Kim	Jaeseung Son
Jose Costa	Youngsoo Kim	Jung Je Son
Manoj Das	Patrick Kinney	Kapil Sood
Russell Dietz	Dongkeon Kong	Amjad Soomro
Thomas Dineen	Bruce Kraemer	Kenneth Stanwood
Mi-Sun Do	Joseph Kwak	Thomas Starai
Carlo Donati	Edwin Kwon	Adrian Stephens
Paul Eastman	Jeremy Landt	Carl Stevenson
Peter Ecclesine	Insun Lee	Rene Struik
Richard Eckard	Jae Min Lee	Walter Struppler
Charles Einolf	Jeongho Lee	Jun Ichi Takada
Marc Emmelmann	Mi Hyun Lee	Masahiro Takagi
Bernard Eydt	Myung Lee	Michael Johas Teener
Shulan Feng	Seong-hee Lee	David Tepen
Michael Fischer	Sungjin Lee	Adam Toner
C. Fitzgerald	Tae Hoon Lee	Wen Tong
David Fort	Joseph Levy	Masahiro Umehira
Andre Fournier	Jan-Ray Liao	Dmitri Varsanofiev
Robert Frazier	Arthur Light	Prabodh Varshney
Avraham Freedman	Chiwoo Lim	George Vlantis
Devon Gayle	Hyoung-Kyu Lim	Stanley Wang
Theodore Georgantas	Daniel Lubar	Robert Weller
James Gilb	William Lumpkins	Harry Worstell
Jaganathan Gnanavelu	Mark Maloney	Xuyong Wu
Mariana Goldhamer	David Mazzaresse	Oren Yuen
	Steven Methley	Juan Zuniga

When the IEEE-SA Standards Board approved this standard on 30 September 2010, it had the following membership:

Robert M. Grow, *Chair*
Richard H. Hulett, *Vice Chair*
Steve M. Mills, *Past Chair*
Judith Gorman, *Secretary*

Karen Bartleson
Victor Berman
Ted Burse
Clint Chaplin
Andy Drozd
Alexander Gelman
Jim Hughes

Young Kyun Kim
Joseph L. Koepfinger*
John Kulick
David J. Law
Hung Ling
Oleg Logvinov
Ted Olsen

Ronald C. Petersen
Thomas Prevost
Jon Walter Rosdahl
Sam Sciacca
Mike Seavey
Curtis Siller
Don Wright

*Member Emeritus

Also included are the following nonvoting IEEE-SA Standards Board liaisons:

Satish Aggarwal, NRC Representative
Richard DeBlasio, DOE Representative
Michael Janezic, NIST Representative

Catherine Berger
IEEE Project Editor

Michael Kipness
IEEE Standards Program Manager, Technical Program Development

Contents

1. Overview	1
1.1 General	1
1.2 Scope	2
1.3 Purpose	2
2. Normative references	3
3. Definitions	5
4. Acronyms and abbreviations	7
5. Functional overview	9
5.1 Introduction	9
5.2 Architecture	9
5.3 Superframe structure	9
5.3.1 Synchronization burst structure	11
5.3.2 Beacon frame structure	12
5.4 Data transfer model	12
5.5 Security	14
5.5.1 Public-key approach	15
5.5.2 Security considerations	15
5.5.3 Beaconing device life cycle	16
6. PHY specification	17
6.1 General requirements and definitions	17
6.1.1 TV channel/licensed auxiliary service (LAS) channel information	17
6.1.2 Modulation rates and beacon offset location for ATSC DTV regions	17
6.1.3 RF power measurement information	18
6.1.4 Receiver sensitivity definitions	18
6.2 PHY service specifications	18
6.2.1 PHY data service	19
6.2.2 PHY management service	20
6.2.3 PHY enumerations description	27
6.3 Synchronization burst	27
6.4 PPDU format	28
6.5 Inter-device communication interval (ICI)	28
6.5.1 Receive (Rx) period	29
6.5.2 Acknowledgement/no acknowledgement period (ANP)	31
6.6 PHY constants and PIB attributes	32
6.6.1 PHY constants	32
6.6.2 PHY PIB attributes	32
6.7 PHY specifications	33
6.7.1 Modulation and spreading	33
6.7.2 Forward error correction (FEC)	35
6.8 Radio specifications	37
6.8.1 Transmit center frequency tolerance	37
6.8.2 Transmit power	37
6.8.3 Transmit PSD mask	37
6.8.4 Modulation accuracy	38
6.8.5 Spurious harmonically-related emission suppression	39

6.8.6	Receiver sensitivity.....	39
6.8.7	Adjacent LAS channel rejection.....	39
6.8.8	Receiver maximum input level of compliant beacon signal (blocking).....	40
6.8.9	Link quality indicator (LQI).....	40
7.	MAC sublayer specification.....	43
7.1	MAC sublayer service specification.....	43
7.1.1	MAC management service.....	43
7.1.2	Enumeration description.....	51
7.2	MAC beacon frame.....	52
7.2.1	MSF 1.....	52
7.2.2	MSF 2.....	58
7.2.3	MSF 3.....	61
7.3	MAC constants and MIB attributes.....	62
7.3.1	MAC constants.....	62
7.3.2	MIB attributes.....	62
7.4	MAC functional description.....	65
7.4.1	Transmission protocol.....	65
7.4.2	Retry procedure for an SPD.....	65
7.4.3	Frame reception and rejection.....	66
7.4.4	Device initialization procedure.....	67
7.4.5	Inter-device communications.....	68
7.4.6	Beaconing.....	71
7.4.7	Ceasing transmissions.....	75
7.4.8	Setting the internal operating states of the transceiver.....	77
7.5	Security suite specifications.....	79
7.5.1	Notation and representation.....	79
7.5.2	Representation of time.....	79
7.5.3	Elliptic-curve building blocks.....	80
7.5.4	Signature scheme.....	81
7.5.5	Certificate scheme.....	83
7.6	Message sequence charts (MSC) illustrating MAC-PHY interaction.....	85
Annex A	(informative) Example block decoding method.....	93
A.1	Introduction.....	93
A.2	Method details.....	93
A.3	Example.....	94
Annex B	(informative) Recommended deployment in the United States.....	97
B.1	Introduction.....	97
B.2	Physical positioning of the beacon relative to other Part 74 wireless systems.....	97
B.3	Additional beacon antenna deployment considerations.....	101
B.4	Recommended wireless system frequencies of operation.....	102
Annex C	(informative) Receiver sensitivity and adjacent channel protection justification.....	103
C.1	Introduction.....	103
C.2	Analysis.....	104
C.2.1	Link 1 Rx signal.....	104
C.2.2	Microphone interfering signal.....	105

Annex D (informative) Next higher layer (NHL) operation.....	107
D.1 Introduction.....	107
D.2 Next higher layer (NHL).....	107
D.3 Beaconing device types	108
D.4 Generic PD behavior.....	108
D.4.1 Searching for existing PDs	108
D.4.2 Deciding to become a PPD or an SPD after an initial search	109
D.4.3 Beacon frame construction and transmission	110
D.4.4 Beacon transmission failure-related enumeration values	111
D.5 PPD behaviors.....	112
D.5.1 Insertion of Rx period and ANP	112
D.5.2 Data aggregation	112
D.5.3 NPD selection	114
D.5.4 SPD lost indication	115
D.5.5 NPD lost indication.....	115
D.5.6 Planned termination of PPD transmission	115
D.5.7 Behavior following termination of SPD transmissions without warning	115
D.5.8 Behavior following planned termination of SPD transmissions.....	116
D.5.9 Behavior following termination of NPD transmissions without warning	116
D.5.10 Behavior following planned termination of NPD transmissions	116
D.5.11 PPD-specific MIB attributes	116
D.6 SPD behaviors.....	116
D.6.1 PPD beacon reception	117
D.6.2 Inter-device communication	117
D.6.3 Inter-device communication—retry failure handling	117
D.6.4 Inter-device communication—selection of the same RTS codeword	118
D.6.5 PPD protection of an SPD	118
D.6.6 Transmission of more than one beacon frame	119
D.6.7 Behavior on SPD receiving a PPD lost indication.....	119
D.6.8 Behavior on SPD receiving an NPD lost indication	119
D.6.9 Behavior if both PPD and NPD are lost	120
D.6.10 Behavior when selected as the NPD	121
D.6.11 Planned termination of SPD transmission	121
D.6.12 Behavior following termination of PPD transmissions without warning	121
D.6.13 Behavior following planned termination of PPD transmissions.....	122
D.6.14 Behavior following termination of NPD transmissions without warning	122
D.6.15 Behavior following planned termination of NPD transmissions	122
D.6.16 SPD-specific MIB attributes	122
D.7 NPD behaviors.....	122
D.7.1 Behavior on reception of the PPD NPD Indication subfield	123
D.7.2 Behavior on NPD receiving a PPD lost indication	123
D.7.3 Planned termination of NPD transmissions	123
D.7.4 Behavior following termination of PPD transmissions without warning	123
D.7.5 Behavior following planned termination of PPD transmissions.....	124
D.7.6 NPD-specific MIB attributes	124

Annex E (informative) Acquisition of time and location information	125
E.1 Introduction.....	125
E.2 Time	125
E.3 Location information	126
Annex F (informative) Concept of service primitives	129
Annex G (informative) Bibliography	131

IEEE Standard for Information Technology— Telecommunications and information exchange between systems— Local and metropolitan area networks— Specific requirements

Part 22.1: Standard to Enhance Harmful Interference Protection for Low-Power Licensed Devices Operating in the TV Broadcast Bands

IMPORTANT NOTICE: This standard is not intended to ensure safety, security, health, or environmental protection in all circumstances. Implementers of the standard are responsible for determining appropriate safety, security, environmental, and health practices or regulatory requirements.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

1. Overview

1.1 General

National regulators are advancing regulations that allow license-exempt devices to operate on a non-interfering basis within the portions of the TV spectrum that are not used for broadcasts or required to remain unused in order to protect broadcast stations from interference. The Federal Communications Commission (FCC) in the United States of America has proposed to allow license-exempt devices to operate on a non-interfering basis within the portions of the TV spectrum that are not used for broadcasts or required to remain unused in order to protect broadcast stations from interference. It is expected that other regulatory bodies will take similar actions. Although the TV channels in these portions are not used for TV broadcasts, low-power, licensed devices, such as wireless microphones operated by broadcasters, do use these channels, and are entitled to protection by regulation to avoid disrupting incumbent services.