

ASABE S578 JAN2007 (R2016)
Yield Monitor Performance Test Standard



**American Society of
Agricultural and Biological Engineers**

**S
T
A
N
D
A
R
D**

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as "ASAE", regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as "ASABE".

Standards designated as "ANSI" are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, fax 269-429-3852, hq@asabe.org

Yield Monitor Performance Test Standard

Developed by the ASABE Precision Agriculture Committee. Adopted by ASABE January 2007; reaffirmed January 2012; reaffirmed October 2016.

Keywords: Calibration, Flow sensor, Material flow rate, Steady state flow, Step flow, Transient flow, Yield

1 Purpose and Scope

1.1 This Standard is intended to provide the basic requirements for a uniform procedure to measure and report yield monitor accuracy. The goal is to provide a series of repeatable tests that may be used as a basis to evaluate and compare yield monitors under a wide range of operating conditions.

1.2 This Standard covers grain and bulk crop yield monitors. Because crop conditions are variable and uncontrollable, the procedure provides for laboratory testing with controlled material flow rates. The Standard includes evaluation of all sensors required for the yield monitor including moisture sensors. The Standard applies to all technologies associated with evaluating yield, mass flow, force, and volume measurements during crop harvest.

1.3 This Standard defines tests that include all components contained in the commercial yield monitor except the positioning device. Harvester inputs required for determining yield that cannot be duplicated on the test fixture are simulated to permit testing of all yield calculations.

2 Terminology

2.1 yield monitor: A system of sensors and associated electronics mounted on a harvester and used to quantify the yield for the crop being harvested on an instantaneous and averaging basis.

2.2 yield sensor (flow sensor): The sensor(s) that measure the mass or volume flow or mass accumulation of the crop in a short time interval.

2.3 test monitor: The yield monitor to be evaluated.

2.4 test run: The events necessary to record a single set of measurements.

2.5 test: All the events and data of several test runs and the test stand qualification information.

2.6 test stand: A stationary system including precision flow or load measurement system, material conveyance system and test monitor. See Figure 1.