

Contents	Page
1 Introduction.....	1
2 Scope and Purpose.....	1
2.1 Scope	1
2.2 Purpose	1
3 Definitions.....	1
4 Product characteristics	3
4.1 Volume of liquefied gases	3
4.2 Gas release	3
4.3 Gas spillage.....	3
5 General safety aspects.....	3
5.1 Personal protection.....	3
5.2 Emergency response information/TREMcards.....	3
5.3 Operating instructions.....	3
6 Preparation for shipment	3
6.1 Periodic tests	4
6.2 Placarding.....	4
6.3 Marking/data plates	4
6.4 Emergency contacts	4
6.5 Leak test.....	4
6.6 Working pressure	4
6.7 Insulation shields.....	4
6.8 Visual checks.....	4
7 Stowage onboard ship.....	5
8 Transport of empty containers or containers with residual product.....	5
9 What to do in the case of release of product.....	5
9.1 Release of gas.....	5
9.2 Release of vapor from portable tanks containing refrigerated liquefied gases.....	5
9.3 Release of refrigerated liquid	6
10 Security	6
11 References	6

Appendices

Appendix A—Example of a checklist	8
Appendix B—Example of determination of the actual holding time of a vacuum insulated tank container.....	9
Appendix C—Examples of portable tanks and multiple element gas containers	12

Appendix Table

Table B-1—Thermodynamic properties of saturated nitrous oxide.....	11
--	----

Appendix Figures

Figure C-1—Portable tank for refrigerated liquefied gas (20 ft cryogenic vacuum insulated tank container)	12
Figure C-2—Portable tank for refrigerated liquefied gas (40 ft cryogenic vacuum insulated tank container for helium with a nitrogen shield)	12
Figure C-3—Portable tank for refrigerated liquefied gas (20 ft thermally insulated tank container for carbon dioxide)	13
Figure C-4—Portable tank for liquefied gas (20 ft noninsulated tank container with sunshield)	13
Figure C-5—Multiple element gas container (MEGC) (20 ft for compressed and liquefied compressed gas)....	14
Figure C-6—Multiple element gas container (MEGC) (40 ft for compressed and liquefied compressed gas)...	14

This page is intentionally blank.

1 Introduction

This publication provides guidance for the safe water transport of portable tanks and multiple element gas containers (MEGCs) containing industrial, medical and specialty gas and liquefied gas products.

This publication addresses product characteristics, general safety aspects, preparation for shipment, stowage onboard ship, transport of containers and emergency response.

Normally during sea transport a skilled operator does not accompany these containers and this publication has been written for the guidance of parties involved in their preparation and subsequent transportation by sea. Compliance with these guidelines will, under normal conditions, help ensure safe transport by sea.

2 Scope and Purpose

2.1 Scope

This publication applies to the transport by sea of portable tanks and MEGCs that are used in the industrial, medical and specialty gases industry for the worldwide transport of gases and liquefied gases in bulk.

2.2 Purpose

To provide guidelines for the safe transport of insulated and noninsulated portable tanks and MEGCs by sea, to reduce the potential for unintentional releases of the contents for the duration of a defined journey and to recommend actions in case of an accidental release.

3 Definitions

3.1 Compressed gas

A gas which when packaged under pressure for transport is entirely gaseous at $-46\text{ }^{\circ}\text{F}$ ($-50\text{ }^{\circ}\text{C}$); this category includes all gases with a critical temperature less than or equal to $-46\text{ }^{\circ}\text{F}$ ($-50\text{ }^{\circ}\text{C}$).

3.2 Container

A container is designed for multimodal use and is fitted with devices permitting its ready stowage and handling particularly when being trans-loaded from one means of transport to another. A container is any portable tank or MEGC that meets the definition of a "container" within the terms of the International Convention for Safe Containers (CSC).

3.3 Liquefied gas

A gas which when packaged under pressure for transport is partially liquid at temperatures above $-58\text{ }^{\circ}\text{F}$ ($-50\text{ }^{\circ}\text{C}$). A distinction is made between:

- high pressure liquefied gas, which is a gas with a critical temperature between $-58\text{ }^{\circ}\text{F}$ and $149\text{ }^{\circ}\text{F}$ ($-50\text{ }^{\circ}\text{C}$ and $65\text{ }^{\circ}\text{C}$); and
- low pressure liquefied gas, which is a gas with a critical temperature above $149\text{ }^{\circ}\text{F}$ ($65\text{ }^{\circ}\text{C}$);

3.4 Refrigerated liquefied gas

A gas that when packaged for transport is made partially liquid because of its low temperature.

3.5 Portable tank

A multimodal tank having a capacity of more than 450 L fitted with service equipment and structural equipment necessary for the transport of refrigerated and nonrefrigerated liquefied gases. The portable tank shall be capable of being filled and discharged without the removal of its structural equipment. It shall possess stabilizing members external to the shell, and shall be capable of being lifted when full. Road tank vehicles, rail tank-wagons, nonmetallic tanks and intermediate bulk containers (IBCs) are not considered to fall within the definition for portable tanks.