

ASABE S579.1 JUL2012 (R2016)
Yield Monitor Field Test Engineering Procedure



**American Society of
Agricultural and Biological Engineers**

**S
T
A
N
D
A
R
D**

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as "ASAE", regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as "ASABE".

Standards designated as "ANSI" are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, fax 269-429-3852, hq@asabe.org

Yield Monitor Field Test Engineering Procedure

Developed by the ASABE Precision Agriculture Committee; approved by the ASABE Power and Machinery Division; adopted as an ASABE standard May 2009; revised July 2012; reaffirmed October 2016.

Keywords: Mass flow delay, Response time, Terminology, Yield

1 Purpose and scope

- 1.1 This procedure provides the basic requirements for evaluating field performance accuracy of a yield monitor installed on a harvester.
- 1.2 The procedure defines methods to determine time delay of material flow through the harvester.
- 1.3 This procedure outlines the method to select and prepare a field for testing to simulate changing yield conditions to evaluate yield measurement accuracy for varying flow rates.
- 1.4 This procedure was developed for grain, fiber, and bulk crop yield monitors, but could be adapted for other crops.

2 Terminology

2.1 Yield Monitor: A system of sensors and electronics mounted on a harvester and used to quantify the yield for the crop being harvested on an instantaneous and/or averaging basis. This includes all sensors necessary to accurately calculate yield for a given location within a field.

For example, if a moisture corrected yield is desired, the yield monitor will include a moisture sensor.

- 2.2 **Test monitor:** The yield monitor to be evaluated.
- 2.3 **Flow Sensor:** The sensor(s) that directly measures the mass or volume flow of the crop in a short time period.
- 2.4 **Test:** The events necessary to record data from multiple test plots.
- 2.5 **Test plot:** An area of sufficient size and length to conduct one repetition of test passes and associated reference passes.
- 2.6 **Test pass:** One harvest trip across the test plot consisting of multiple test blocks.
- 2.7 **Test block:** An area defined as one harvest width by the block length as defined in section 2.15 where the harvester operates in a steady state condition.
- 2.8 **Reference Pass:** One harvest swath through the test plot at normal flow rate with a full harvest width. The reference pass is used to document variability within the test plot.
- 2.9 **Sample Reference System:** A precision weighing system used to determine actual weight of each test pass. The reference system must be calibrated and traceable. Calibration must be current within 12 months prior to this procedure. The reference system includes a moisture test to correct weight to dry basis for crops that require it.