

ACI 347R-14

Guide to Formwork for Concrete

Reported by ACI Committee 347



American Concrete Institute
Always advancing



Guide to Formwork for Concrete

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Guide to Formwork for Concrete

Reported by ACI Committee 347

Kenneth L. Berndt, Chair

Rodney D. Adams
Mary Bordner-Tanck
George Charitou
Eamonn F. Connolly
James N. Cornell II
Jack L. David
Aubrey L. Dunham
Jeffrey C. Erson
Noel J. Gardner

Brian J. Golanowski
Timothy P. Hayes
Gardner P. Horst
Jeffery C. Jack
David W. Johnston
Roger S. Johnston
Robert G. Kent
Kevin R. Koogle
Jim E. Kretz

H. S. Lew
Robert G. McCracken
Eric S. Peterson
Steffen Pippig
Matthew J. Poisel
Douglas J. Schoonover
Aviad Shapira
John M. Simpson
Rolf A. Spahr

Pericles C. Stivaros
Daniel B. Toon
Ralph H. Tulis

Consulting Members
Samuel A. Greenberg
R. Kirk Gregory

Objectives of safety, quality, and economy are given priority in these guidelines for formwork. A section on contract documents explains the kind and amount of specification guidance the engineer/architect should provide for the contractor. The remainder of the guide advises the formwork engineer/contractor on the best ways to meet the specification requirements safely and economically. Separate chapters deal with design, construction, and materials for formwork. Considerations specific to architectural concrete are also outlined in a separate chapter. Other sections are devoted to formwork for bridges, shells, mass concrete, and underground work. The concluding chapter on formwork for special methods of construction includes slipforming, preplaced-aggregate concrete, tremie concrete, precast concrete, and prestressed concrete.

Keywords: anchors; architectural concrete; coatings; construction; construction loads; contract documents; falsework; form ties; forms; formwork; foundations; quality control; reshoring; shoring; slipform construction; specifications; tolerances.

CONTENTS

CHAPTER 1—INTRODUCTION AND SCOPE, p. 2

- 1.1—Introduction, p. 2
- 1.2—Scope, p. 2

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

CHAPTER 2—NOTATION AND DEFINITIONS, p. 2

- 2.1—Notation, p. 2
- 2.2—Definitions, p. 2

CHAPTER 3—GENERAL CONSIDERATIONS, p. 3

- 3.1—Achieving economy in formwork, p. 3
- 3.2—Contract documents, p. 4

CHAPTER 4—DESIGN, p. 5

- 4.1—General, p. 5
- 4.2—Loads, p. 6
- 4.3—Member capacities, p. 9
- 4.4—Safety factors for accessories, p. 9
- 4.5—Shores, p. 10
- 4.6—Bracing and lacing, p. 10
- 4.7—Foundations for formwork, p. 10
- 4.8—Settlement, p. 10

CHAPTER 5—CONSTRUCTION, p. 10

- 5.1—Safety precautions, p. 10
- 5.2—Construction practices and workmanship, p. 12
- 5.3—Tolerances, p. 13
- 5.4—Irregularities in formed surfaces, p. 14
- 5.5—Shoring and centering, p. 14
- 5.6—Inspection and adjustment of formwork, p. 14
- 5.7—Removal of forms and supports, p. 15
- 5.8—Shoring and reshoring of multistory structures, p. 17

ACI 347R-14 supersedes ACI 347-04 and was adopted and published July 2014.
Copyright © 2014, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

CHAPTER 6—MATERIALS, p. 18

- 6.1—General, p. 18
- 6.2—Properties of materials, p. 19
- 6.3—Accessories, p. 19
- 6.4—Form coatings and release agents, p. 21

CHAPTER 7—ARCHITECTURAL CONCRETE, p. 21

- 7.1—Introduction, p. 21
- 7.2—Role of architect, p. 21
- 7.3—Materials and accessories, p. 23
- 7.4—Design, p. 23
- 7.5—Construction, p. 24
- 7.6—Form removal, p. 25

CHAPTER 8—SPECIAL STRUCTURES, p. 25

- 8.1—Discussion, p. 25
- 8.2—Bridges and viaducts, including high piers, p. 25
- 8.3—Structures designed for composite action, p. 25
- 8.4—Folded plates, thin shells, and long-span roof structures, p. 26
- 8.5—Mass concrete structures, p. 27
- 8.6—Underground structures, p. 28

CHAPTER 9—SPECIAL METHODS OF CONSTRUCTION, p. 29

- 9.1—Preplaced-aggregate concrete, p. 29
- 9.2—Slipforms, p. 29
- 9.3—Permanent forms, p. 31
- 9.4—Forms for prestressed concrete construction, p. 32
- 9.5—Forms for site precasting, p. 32
- 9.6—Use of precast concrete for forms, p. 33
- 9.7—Forms for concrete placed under water, p. 33

CHAPTER 10—REFERENCES, p. 34

- Authored references, p. 35

CHAPTER 1—INTRODUCTION AND SCOPE**1.1—Introduction**

Many individuals, firms, and companies are usually involved in the design of the facility to be built and in the design and construction of the formwork. The facility team typically involves structural engineers and architects who determine the requirements for the concrete structure to be built. For simplicity, the facility design team will usually be referred to as the engineer/architect, although they may be referred to separately in some situations. The formwork team may include the general contractor, formwork specialty subcontractors, formwork engineers, form manufacturers, and form suppliers. The participating companies and firms also have form designers and skilled workers executing many detailed tasks. For simplicity, the formwork team will usually be referred to as the formwork engineer/contractor, although they may be referred to separately in some situations.

This guide is based on the premise that layout, design, and construction of formwork should be the responsibility of the formwork engineer/contractor. This is believed to be

fundamental to the achievement of safety and economy of formwork and of the required formed surface quality of the concrete.

The paired values stated in inch-pound and SI units are usually not exact equivalents. Therefore, each system is to be used independently of the other.

1.2—Scope

This guide covers:

- a) A listing of information to be included in the contract documents
- b) Design criteria for horizontal and vertical loads on formwork
- c) Design considerations, including safety factors for determining the capacities of formwork accessories
- d) Preparation of formwork drawings
- e) Construction and use of formwork, including safety considerations
- f) Materials for formwork
- g) Formwork for special structures
- h) Formwork for special methods of construction

CHAPTER 2—NOTATION AND DEFINITIONS**2.1—Notation**

- C_{CP} = concrete lateral pressure, lb/ft² (kPa)
- C_c = chemistry coefficient
- C_w = unit weight coefficient
- c_1 = slipform vibration factor, lb/ft² (kPa)
- g = gravitational constant, 0.00981 kN/kg
- h = depth of fluid or plastic concrete from top of placement to point of consideration in form, ft (m)
- R = rate of placement, ft/h (m/h)
- T = temperature of concrete at time of placement, °F (°C)
- w = unit weight of concrete, lb/ft³
- ρ = density of concrete, kg/m³

2.2—Definitions

The 2014 ACI Concrete Terminology (<http://www.concrete.org/Tools/ConcreteTerminology.aspx>) provides a comprehensive list of definitions. The definitions provided herein complement that source.

backshores—shores left in place or shores placed snugly under a concrete slab or structural member after the original formwork and shores have been removed from a small area, without allowing the entire slab or member to deflect or support its self-weight and construction loads.

brace—structural member used to provide lateral support for another member, generally for the purpose of ensuring stability or resisting lateral loads.

centering—falsework used in the construction of arches, shells, space structures, or any continuous structure where the entire falsework is lowered (struck or decentered) as a unit.

climbing form—form that is raised vertically for succeeding lifts of concrete in a given structure.