

American National Standard

*for Outdoor Power Equipment –
Portable, Handheld,
Internal Combustion Engine–Powered
Cut-Off Machines –
Safety and Environmental Requirements*



ANSI/OPEI

B175.4-2013

Revision and redesignation of
ANSI B175.4-2006

American National Standard
for Outdoor Power Equipment –

Portable, Handheld,
Internal Combustion Engine–Powered
Cut-Off Machines –
Safety and Environmental Requirements

Sponsor

Outdoor Power Equipment Institute

Approved August 12, 2013

Published November 22, 2013

American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires review by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made towards their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published by

**American National Standards Institute, Inc.
25 West 43rd Street, New York, NY 10036**

Copyright © 2013 by the Outdoor Power Equipment Institute
All rights reserved.

No part of this publication may be reproduced in any form, stored in an electronic retrieval system, or transmitted in any form or by any means (electronic, photocopying, recording, or otherwise) without prior written permission of the Outdoor Power Equipment Institute, Inc.

Printed in the United States of America

Contents

| | Page |
|---|------|
| Foreword | iii |
| 1 Scope and purpose | 1 |
| 2 Normative references | 1 |
| 3 Definitions | 3 |
| 4 Safety requirements | 7 |
| 5 Sound levels | 18 |
| 6 Vibration | 18 |
| 7 Operator manual(s) | 18 |
| 8 Marking/Symbols | 21 |
| Annexes | |
| A Procedures for the evaluation of environment and fuel compatibility of fuel lines and tanks | 23 |
| B Method of sound pressure measurement at the ear of the operator | 25 |
| C Sound measurement for bystanders (optional) | 29 |
| D Method of vibration measurement | 34 |
| E Determination of the strength of cut-off wheel guards | 38 |
| F Retention test for cut-off wheels | 40 |
| G Examples of symbols | 41 |
| Tables | |
| 1 Handle clearance dimensions | 8 |
| 2 Minimum flange dimensions for composite wheels | 16 |
| 3 Minimum flange dimensions for diamond (steel core) wheels | 17 |
| B.1 Table for reporting measurement results out of the sound pressure measurements at the operator's ear position | 27 |
| C.1 Reporting sound data | 33 |
| Figures | |
| 1 Typical cut-off machine | 3 |
| 2 Cutting equipment - Depth of cut | 4 |
| 3 Typical cutting position | 5 |
| 4 Clearance and distance between front and rear handles for rear handle machines | 8 |
| 5 Handle grip area | 8 |
| 6 Perimeter of handle cross section | 9 |
| 7 Clearances behind released throttle trigger | 9 |
| 8 Finger clearances at released throttle trigger | 9 |

| | Page |
|---|------|
| 9 Hand and finger clearances for front and rear handles for top handle machines | 9 |
| 10 Hold machine by both handles during vibration isolators full failure test | 10 |
| 11 Probe for fuel line testing..... | 12 |
| 12 Far side of front handle above the machine | 14 |
| 13 Far side of front handle at sides of the machine | 14 |
| 14 Cylinder or muffler area | 14 |
| 15 Test cone..... | 14 |
| 16 Typical flange dimensions | 17 |
| B.1 Test fixture set-up for sound pressure measurement..... | 27 |
| B.2 Typical loading device for sound measurements | 28 |
| C.1 Measuring locations | 31 |
| D.1 Vibration total value | 34 |
| D.2 Accelerometer positions | 35 |
| E.1 Test set-up for strength tests with cut-off wheel guards | 38 |

Foreword (This foreword is not part of American National Standard ANSI/OPEI B175.4-2013.)

This standard revises ANSI B175.4-2006, *American National Standard for Outdoor Power Equipment - Portable, Handheld, Internal-Combustion-Engine-Driven Cut-Off Machines - Safety Requirements*.

The B175.4 Standards Development Committee developed this standard. The Committee is comprised of several organizations and individuals that evaluate or manufacture these products and accessories.

This standard covers maximum wheel diameters up to 16 inches.

A summary of the principal changes included in this standard is as follows:

- New important technical specifications and test procedures were added, such as fuel tank and fuel line integrity and machine drop testing.
- Reactive forces definitions were revised for clarity.
- During the development of this standard, an attempt to harmonize it globally with relevant ISO, CEN, and ANSI standards was considered and implemented where appropriate. In this regard, some of the clauses of this standard are identified as optional as they may only apply to certain market requirements.
- Concerning the maximum speed for cut-off machines, the definitions of ANSI B7.1-2010, *American National Standard, Safety Requirements for the Use, Care, and Protection of Abrasive Wheels*, apply, i.e., to define a maximum spindle speed, which correlates to the maximum speed of the cut-off wheel. Usually this maximum wheel speed is calculated from the maximum peripheral speed of the existing wheels, i.e., 100 m/s. Under these circumstances, section 8 of ANSI B7.1-2010 for Special Speeds is applicable.
- Requirements for heat protection were revised.
- A new Annex A was inserted for the Procedures for the Evaluation of Environmental and Fuel Compatibility of Fuel Lines and Tanks information and the remaining Annexes re-numbered.

There are seven annexes in this standard. Annexes A - F are normative and are considered part of the standard. Annex G is informative and is not considered part of the standard.

Suggestions for improvements to this standard are welcome. They should be sent to the Outdoor Power Equipment Institute, 341 South Patrick Street, Alexandria, VA 22314.

The following entities, recognized as having an interest in the standardization of safety requirements for cut-off machines, were contacted prior to the approval of this revised standard. Inclusion in the list does not necessarily imply that the organization concurred with the submittal of the proposal to ANSI:

Association of Equipment Manufacturers
Piedmont Technical Associates, Inc.
Concrete Sawing and Drilling Association
Construction Solutions Services LLC
Dolmar GmbH North American Division
ECHO, Inc. Husqvarna Outdoor Equipment
North American Equipment Dealers Association
STIHL, Inc.
U. S. Consumer Product Safety Commission
U. S. Forest Service – San Dimas
Underwriters Laboratories, Inc.

American National Standard
for Outdoor Power Equipment –

Portable, Handheld, Internal Combustion Engine–Powered Cut-Off Machines – Safety and Environmental Requirements

1 Scope and purpose

This standard applies to portable, handheld internal combustion engine-powered machines, which use a rotating cut-off (abrasive) wheel that is center-mounted on and driven by a spindle shaft, and designed for cutting construction materials such as asphalt, concrete, stone, and metal.

The requirements in this standard apply to machines using up to 406-mm (16-in) cut-off wheels. If the machine is designed for larger than 406-mm (16-in) cut-off wheels, the requirements of this standard shall be considered. The requirements listed may apply to machines designed for larger cut-off wheels.

Cut-off wheel design and safety specifications are not included in this standard.

The effective implementation date of this standard shall be two (2) years after the publication date and shall apply to all products built after that date. Manufacturers may also comply with the requirements of this standard any time after the publication date.

“ANSI/OPEI B175.4-2013” and “ANSI B175.4-2013” may be used interchangeably wherever referenced or required in this standard.

1.1. Purpose

This standard establishes safety and environmental requirements to reduce the risk of injury associated with the use of portable, hand-held internal combustion engine-powered machines using a rotating cut-off (abrasive) wheel.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

ANSI B7.1-2010, *Safety requirements for the use, care, and protection of abrasive wheels*