



American National Standard for

# Rotodynamic Vertical Pumps

of Radial, Mixed, and Axial Flow  
Types for Nomenclature and  
Definitions

ANSI/HI 2.1-2.2-2014



6 Campus Drive  
First Floor North  
Parsippany, New Jersey  
07054-4406  
[www.Pumps.org](http://www.Pumps.org)

American National Standard for

# Rotodynamic Vertical Pumps

of Radial, Mixed, and Axial Flow Types  
for Nomenclature and Definitions

Sponsor  
**Hydraulic Institute**  
[www.Pumps.org](http://www.Pumps.org)

Approved April 8, 2014  
**American National Standards Institute, Inc.**

# American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

**CAUTION NOTICE:** This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

**Hydraulic Institute**  
**6 Campus Drive, First Floor North**  
**Parsippany, NJ 07054-4406**

**[www.Pumps.org](http://www.Pumps.org)**

Copyright © 2014 Hydraulic Institute  
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-1-935762-14-0



Recycled  
paper

# Contents

Page

Foreword	v
2 Rotodynamic vertical pumps	1
2.1 Types and nomenclature	1
2.1.1 Scope	1
2.1.2 Definition of rotodynamic vertical pumps	1
2.1.3 Types of vertical pumps	1
2.1.4 Classification by configuration	11
2.1.5 Classification by impeller design	16
2.1.6 General information	19
2.2 Definitions, terminology, and symbols	28
2.2.1 Rate of flow (capacity) ( $Q$ or $q$ ) [ $Q$ ]	30
2.2.2 Speed ( $n$ )	31
2.2.3 Head ( $h$ ) [ $H$ ]	31
2.2.4 Condition points	34
2.2.5 Suction conditions	35
2.2.6 Power	36
2.2.7 Pump pressures	37
2.2.8 Impeller balancing	37
2.2.9 Rotodynamic vertical pump icons – vertically suspended	37
Appendix A Hollow-shaft driver	43
Appendix B Index	45
Figures	
2.1.3 — Vertical pump types – vertically suspended rotor – single and multistage	2
2.1.3.1 — Vertical, multistage, submersible pump (VS0)	3
2.1.3.2 — Deep-well pumps (VS1)	4
2.1.3.3a — Vertical single or multistage, short setting, open line shaft (VS1)	5
2.1.3.3b — Mixed flow vertical — open line shaft (VS1)	6
2.1.3.3c — Vertical double suction, short setting, open line shaft (VS2)	7
2.1.3.3d — Vertical, axial flow impeller (propeller) type (enclosed line shaft) below-floor discharge configuration (VS3)	8
2.1.3.4a — Line-shaft design sump pump (VS4)	9
2.1.3.4b — Cantilever shaft design sump pump (VS5)	10
2.1.3.5a — Vertical, single, or multistage diffuser (double casing) barrel or can pump (VS6)	12
2.1.3.5b — Vertical double suction, single or multistage barrel or can pump (VS7)	13
2.1.3.5c — Vertical, multistage volute (double casing) barrel or can pump (VS7a)	14
2.1.3.6 — Vertical in-line casing diffuser pump (VS8)	15

2.1.4.4 — Typical vertical pump impeller types with rings (casing and/or impeller) . . . . .	17
2.1.5.5a — General vertical pump characteristic curves . . . . .	20
2.1.5.5b — General vertical pump impeller configuration and specific speeds . . . . .	20
2.1.6.6.1 — Pump length . . . . .	27
2.2.3.4 — Datum elevation for various pump designs at eye of first-stage impeller . . . . .	33
2.2.4.6 — Typical performance curve for rotodynamic pumps of lower specific speed design . . . . .	34
2.2.9.1.1.1 — Submersible turbine (VS0) . . . . .	38
2.2.9.1.2.1 — Discharge through column – diffuser – wet pit (VS1) . . . . .	38
2.2.9.1.2.2 — Discharge through column – volute – wet pit (VS2) . . . . .	39
2.2.9.1.2.3 — Discharge through column – axial flow – wet pit (VS3) . . . . .	39
2.2.9.1.3.1 — Separate discharge – line shaft – vertical sump (VS4) . . . . .	40
2.2.9.1.3.2 — Separate discharge – cantilever (VS5) . . . . .	40
2.2.9.2.1 — Vertically suspended – double casing – double suction – diffuser (VS6) . . . . .	41
2.2.9.2.2a — Vertically suspended – double casing - volute - diffuser (VS7) . . . . .	41
2.2.9.2.2b — Vertical volute multistage double casing pump (VS7a) . . . . .	41
2.2.9.3.1 — Vertically suspended – in-line casing – multistage diffuser (VS8) . . . . .	42
A.1 — Vertical hollow-shaft driver coupling dimensions . . . . .	44
Tables	
2.1.6.5 — Alphabetical part name listing . . . . .	21
2.2a — Principal symbols . . . . .	28
2.2b — Subscripts . . . . .	30