

ACI/TMS 122R-14

Guide to Thermal Properties of Concrete and Masonry Systems

Reported by ACI/TMS Committee 122



American Concrete Institute
Always advancing





This document is the intellectual property of ACI and the cosponsor, and both have copyright. All rights reserved. This material may not be reproduced or copied, in whole or in part, in any printed, mechanical, electronic, film, or other distribution and storage media, without written consent. ACI is the lead sponsor of this joint committee and its operating procedures were followed. ACI's information is below; the cosponsor's information is on the inside back cover of this document.

Guide to Thermal Properties of Concrete and Masonry Systems

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Guide to Thermal Properties of Concrete and Masonry Systems

Reported by ACI/TMS Committee 122

Stephen S. Szoke, Chair

Maribeth S. Bradfield
Theodore W. Bremner
Dennis W. Graber

Thomas A. Holm
John P. Ries
Jeffrey F. Speck

Martha G. VanGeem

Consulting Member
W. Calvin McCall

This guide reports data on the thermal properties of concrete and masonry constituents, masonry units, and systems of materials and products that form building components. This guide includes consideration of thermal inertia of concrete and masonry, passive solar design, and procedures to limit condensation within assemblages.

Keywords: aggregate; cement paste; concrete masonry unit; moisture; precast/prestressed concrete; specific heat; sustainability; thermal conductivity; thermal diffusivity; thermal resistance.

CONTENTS

CHAPTER 1—INTRODUCTION, p. 2

- 1.1—Introduction, p. 2
- 1.2—Energy conservation with concrete and masonry, p. 2
- 1.3—Building enclosure requirements, p. 2

CHAPTER 2—NOTATION AND DEFINITIONS, p. 2

- 2.1—Notation, p. 2
- 2.2—Definitions, p. 3

CHAPTER 3—THERMAL CONDUCTIVITY OF CONCRETE, AGGREGATE, AND CEMENT PASTE, p. 4

- 3.1—Introduction, p. 4
- 3.2—Thermal conductivity of concrete, p. 4
- 3.3—Influence of moisture, p. 4
- 3.4—Thermal conductivity of aggregates and cement paste, p. 5
- 3.5—Thermal conductivity of concrete used in concrete masonry units, p. 5
- 3.6—Thermal conductivity of two-phase systems, p. 7
- 3.7—Sample thermal conductivity calculations using cubic model, p. 7
- 3.8—Practical thermal conductivity, p. 8

CHAPTER 4—CALCULATION METHODS FOR STEADY-STATE THERMAL RESISTANCE OF WALL SYSTEMS, p. 9

- 4.1—Introduction, p. 9
- 4.2—Thermal resistance of concrete masonry walls, p. 10
- 4.3—Methods for calculating thermal resistance of concrete masonry units, p. 10
- 4.4—Thermal resistance of other concrete wall systems, p. 13

CHAPTER 5—THERMAL INERTIA, p. 16

- 5.1—Introduction, p. 16
- 5.2—Factors affecting thermal inertia effect, p. 16
- 5.3—Determining thermal inertia effects, p. 19
- 5.4—Equivalent R -values for concrete and masonry walls, p. 21

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI 122R-14 supersedes ACI 122R-02 and was adopted and published December 2014..

Copyright © 2014, American Concrete Institute

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

5.5—Interior thermal inertia, p. 21

CHAPTER 6—THERMAL PROPERTIES FOR PASSIVE SOLAR DESIGN, p. 22

6.1—Introduction, p. 22

6.2—Thermal properties, p. 23

6.3—Incorporating mass into passive solar designs, p. 23

6.4—Summary, p. 24

CHAPTER 7—CONDENSATION CONTROL, p. 24

7.1—Introduction, p. 24

7.2—Prevention of condensation on wall surfaces under steady-state analysis, p. 25

7.3—Prevention of condensation within wall constructions, p. 25

CHAPTER 8—REFERENCES, p. 26

Authored documents, p. 27

APPENDIX A—TEST RESULTS AND CALCULATED THERMAL CONDUCTANCE OF OVEN-DRIED CONCRETE MASONRY, p. 29

CHAPTER 1—INTRODUCTION

1.1—Introduction

To reduce the use of nonrecoverable energy sources, authorities have adopted energy-conservation building codes and standards that apply to the design and construction of buildings. The design of energy-conserving buildings requires an expanded understanding of the thermal properties of the building envelope and the materials that comprise the envelope system.

This guide provides thermal-property data and design techniques that are useful in designing concrete and masonry building envelopes and determining energy code compliance. The guide is intended for use by owners, architects, engineers, building inspectors, code-enforcement officials, and all those interested in the energy-efficient design of buildings containing concrete or masonry components.

1.2—Energy conservation with concrete and masonry

Due to its inherent functionality and the availability of raw materials used in production, concrete and masonry are the world's most widely used building materials. Many civilizations have built structures with concrete and masonry walls that provide uniform and comfortable indoor temperatures despite all types of climatic conditions. Cathedrals composed of massive masonry walls produce an indoor climate with little temperature variation during the entire year despite the absence of a heating system. Even primitive housing in the desert areas of North America used thick masonry walls that resulted in acceptable interior temperatures despite high outside daytime temperatures.

Housing systems have been developed featuring efficient load-bearing concrete or masonry wall systems that provide resistance to weather, temperature changes, fire,

and noise. Many of these wall systems are made with light-weight concrete to enhance both static and dynamic thermal resistance.

Numerous organizations have studied and reported on the steady-state and dynamic energy-conserving contributions that concrete and concrete masonry walls can make to thermal efficiency in buildings (Peavy et al. 1973; Petersen and Barnett 1980; Petersen et al. 1981; U.S. Department of Energy 1989; ASHRAE 2009; ANSI/ASHRAE/IES 90.1; Childs et al. 1983; National Concrete Masonry Association 2010; Portland Cement Association 1981, 1982). This increased energy efficiency may permit reductions in the required size and operating costs of mechanical systems. This reduction in energy usage is not recognized by steady-state calculations (R -values and U -values). Improved calculation methods are required to account for the dynamic, real-world performance of concrete and concrete masonry building elements.

1.3—Building enclosure requirements

In addition to structural requirements, a building envelope should be designed to control the flow of air, heat, sunlight, radiant energy, liquid water, and water vapor. It should also provide the many other attributes generally associated with enclosure materials, including fire protection, noise control, impact damage resistance, durability, aesthetic quality, and economy. Analysis of building enclosure materials should extend beyond heat-flow analysis to also account for their multifunctional purposes. The non-heat-flow subjects are beyond the scope of this guide, but this exclusion should not be taken as an indication that they are not crucial to the total overall performance of a building enclosure.

CHAPTER 2—NOTATION AND DEFINITIONS

2.1—Notation

a	=	fractional area
a_{gr}	=	fractional grouted area of wall
a_i	=	fractional area of insulation
a_{np}	=	fractional area of heat flow path for path number p of thermal layer number n
a_s	=	fractional area of steel
a_{ungr}	=	fractional ungrouted area of wall
a_w	=	fractional area of web of masonry unit determined using the dimensions of web in the same planes as the height and length of the masonry unit
C	=	thermal conductance, Btu/(h·ft ² ·°F) (W/(m ² ·K))
c_p	=	specific heat, Btu/(lb·°F) (J/kg·K)
fs	=	face shell thickness of concrete masonry unit, in. (mm)
h_c	=	heat capacity, Btu(ft ³ ·°F) (J/(m ³ ·K))
I	=	thermal inertia, Btu/(h ^{1/2} ·ft ² ·°F) (J/(m ² ·K·s ^{1/2}))
k_c	=	thermal conductivity of concrete, Btu·in./(h·ft ² ·°F) (W/(m·K))
k_f	=	thermal conductivity of material placed in the cores of masonry units, Btu·in./(h·ft ² ·°F) (W/(m·K))
k_p	=	thermal conductivity of cement paste, Btu·in./(h·ft ² ·°F) (W/(m·K))