



IPC-CC-830B
with Amendment 1
Qualification and
Performance of Electrical
Insulating Compound for
Printed Wiring Assemblies

October 2008
Supersedes IPC-CC-830B
August 2002

A standard developed by IPC

Association Connecting Electronics Industries



The Principles of Standardization

In May 1995 the IPC's Technical Activities Executive Committee (TAEC) adopted Principles of Standardization as a guiding principle of IPC's standardization efforts.

Standards Should:

- Show relationship to Design for Manufacturability (DFM) and Design for the Environment (DFE)
- Minimize time to market
- Contain simple (simplified) language
- Just include spec information
- Focus on end product performance
- Include a feedback system on use and problems for future improvement

Standards Should Not:

- Inhibit innovation
- Increase time-to-market
- Keep people out
- Increase cycle time
- Tell you how to make something
- Contain anything that cannot be defended with data

Notice

IPC Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of IPC from manufacturing or selling products not conforming to such Standards and Publication, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than IPC members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by IPC without regard to whether their adoption may involve patents on articles, materials, or processes. By such action, IPC does not assume any liability to any patent owner, nor do they assume any obligation whatever to parties adopting the Recommended Standard or Publication. Users are also wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

IPC Position Statement on Specification Revision Change

It is the position of IPC's Technical Activities Executive Committee that the use and implementation of IPC publications is voluntary and is part of a relationship entered into by customer and supplier. When an IPC publication is updated and a new revision is published, it is the opinion of the TAEC that the use of the new revision as part of an existing relationship is not automatic unless required by the contract. The TAEC recommends the use of the latest revision. Adopted October 6, 1998

Why is there a charge for this document?

Your purchase of this document contributes to the ongoing development of new and updated industry standards and publications. Standards allow manufacturers, customers, and suppliers to understand one another better. Standards allow manufacturers greater efficiencies when they can set up their processes to meet industry standards, allowing them to offer their customers lower costs.

IPC spends hundreds of thousands of dollars annually to support IPC's volunteers in the standards and publications development process. There are many rounds of drafts sent out for review and the committees spend hundreds of hours in review and development. IPC's staff attends and participates in committee activities, typesets and circulates document drafts, and follows all necessary procedures to qualify for ANSI approval.

IPC's membership dues have been kept low to allow as many companies as possible to participate. Therefore, the standards and publications revenue is necessary to complement dues revenue. The price schedule offers a 50% discount to IPC members. If your company buys IPC standards and publications, why not take advantage of this and the many other benefits of IPC membership as well? For more information on membership in IPC, please visit www.ipc.org or call 847/597-2872.

Thank you for your continued support.



IPC-CC-830B with Amendment 1

Qualification and Performance of Electrical Insulating Compound for Printed Wiring Assemblies

Developed by the Conformal Coating Task Group (5-33a) of the Cleaning and Coating Committee (5-30)

Supersedes:

IPC-CC-830B - August 2002
IPC-CC-830A with
Amendment 1 - July 1999
IPC-CC-830A - October 1998
IPC-CC-830 - January 1984

Users of this publication are encouraged to participate in the development of future revisions.

Contact:

IPC
3000 Lakeside Drive, Suite 309S
Bannockburn, Illinois
60015-1249
Tel 847 615.7100
Fax 847 615.7105

Acknowledgment

Any document involving a complex technology draws material from a vast number of sources. While the principal members of the Conformal Coating Task Group (5-33a) of the Cleaning and Coating Committee (5-30) are shown below, it is not possible to include all of those who assisted in the evolution of this standard. To each of them, the members of the IPC extend their gratitude.

Cleaning and Coating Committee	Conformal Coating Task Group	Technical Liaisons of the IPC Board of Directors
Chair Douglas O. Pauls Rockwell Collins	Chair John P. Waryold HumiSeal Division of Chase Corporation	Peter Bigelow IMI Inc.
Vice Chair Debora L. Obitz Trace Laboratories - East	Vice Chair Debora L. Obitz Trace Laboratories - East	Sammy Yi Flextronics International
<hr/>		
Conformal Coating Task Group		
David Adams, Rockwell Collins	Christopher Hunt, National Physical Laboratory	Lynn Norman, Continental Automotive Systems US, Inc.
Greg Alexander, Ascentech, LLC	Joseph Kane, BAE Systems Platform Solutions	Victor Powell, L-3 Communications Aviation Recorders
Gustavo Arredondo, Para Tech Coating Inc.	Jason Keeping, Celestica International Inc.	Barry Ritchie, Dow Corning Corporation
Paul Berry, Dow Corning Corporation	William Kenyon, Global Centre Consulting	John Rohlfing, Delphi Electronics and Safety
Gerald Leslie Bogert, Bechtel Plant Machinery, Inc.	Phil Kinner, HumiSeal Division of Chase Corporation	Henry Sanftleben, Delphi Electronics and Safety
Calette Chamness, U.S. Army Aviation & Missile Command	Sven Kramer, Lackwerke Peters GmbH & Co KG	Jeffrey Sargeant, HumiSeal
David Corbett, Defense Supply Center Columbus	Richard Kraszewski, Plexus Corp.	Lowell Sherman, Defense Supply Center Columbus
Rudiger Dietrich, Lackwerke Peters GmbH & Co KG	Vijay Kumar, Lockheed Martin Missile & Fire Control	Gordon Sullivan, Huntsman Advanced Technology Center
Mahendra Gandhi, Northrop Grumman Space Technology	Kenneht Manning, Raytheon Company	Manfred Suppa, Lackwerke Peters GmbH & Co KG
Hue Green, Lockheed Martin Space Systems Company	Renee Michalkiewicz, Trace Laboratories - East	Crystal Vanderpan, Underwriters Laboratories Inc.
Michael Green, Lockheed Martin Space Systems Company	Roger Miedico, Raytheon Company	David Vaughan, Taiyo America Inc.
Amy Hagnauer, Raytheon Company	Graham Naisbitt, Gen3 Systems Limited	Fonda Wu, Raytheon Company
Steve Henly, Acota Limited	David Nelson, Raytheon Company	Lamar Young, Specialty Coating Systems Inc.

Table of Contents

1	SCOPE	1	3.7.1	Moisture and Insulation Resistance	4
1.1	Scope	1	3.7.2	Thermal Shock	4
1.2	Purpose	1	3.7.3	Temperature and Humidity Aging (Hydrolytic Stability)	4
1.3	Classification	1	3.8	Special Requirements	5
1.3.1	Types	1	4	QUALITY ASSURANCE PROVISION	5
1.3.2	Classes	1	4.1	Responsibility for Inspection	5
1.4	Interpretation	1	4.2	Categories of Inspection and Frequency	5
2	APPLICABLE DOCUMENTS	1	4.2.1	Qualification Inspection	5
2.1	IPC	1	4.2.2	Qualification Retention Inspection	5
2.2	Government	2	4.2.3	Quality Conformance Inspection	5
2.3	American Society for Testing of Materials	2	4.3	Product Change	5
2.4	Underwriters Laboratories	2	4.4	Test Equipment and Inspection Facilities	5
2.5	ANSI	2	4.4.1	Standard Laboratory Conditions	5
2.6	ISO	2	4.4.2	Permissible Temperature Variation in Environmental Chambers	6
3	REQUIREMENTS	2	4.4.3	Reference Conditions	6
3.1	General Requirements	2	4.5	Inspection Routine	6
3.1.1	Terms and Definitions	2	4.6	Inspection Sampling	6
3.1.2	Conflict	2	4.6.1	Test Vehicles	6
3.2	Inspection and Testing Requirements	2	4.6.2	Sample Size	6
3.2.1	Qualification Inspection and Testing	2	4.6.3	Preparation Prior to Coating	6
3.2.2	Qualification Retention Inspection and Testing	2	4.6.4	Coating	7
3.2.3	Quality Conformance Inspection Testing	3	4.7	Failures	7
3.2.4	Additional Testing	3	4.8	Inspection Reporting	7
3.3	Materials Requirements	3	4.8.1	Qualification Reporting	7
3.3.1	Materials	3	4.8.2	Qualification Retention Reporting	7
3.3.2	Shelf Life	3	4.8.3	Quality Conformance Reporting	7
3.3.3	Cure	3	5	PREPARATION FOR DELIVERY	7
3.4	Chemical Requirements	3	5.1	Containers	7
3.4.1	Fourier Transform Infrared Spectroscopy Test (FTIR)	3	5.2	Packaging	8
3.5	Physical Requirements	4	5.3	Marking	8
3.5.1	Viscosity	4	6	NOTES	8
3.5.2	Appearance	4	6.1	Order Data	8
3.5.3	Fluorescence	4	6.2	Formulation Change	8
3.5.4	Fungus Resistance	4	6.3	Conditioning	8
3.5.5	Flexibility	4	6.4	Cleanliness	8
3.5.6	Flammability	4	6.5	Adhesion	8
3.6	Electrical Requirements	4	6.6	Solvent Compatibility	8
3.6.1	Dielectric Withstanding Voltage (DWV)	4	6.7	Identification of Solvent Sensitive Conformal Coatings	8
3.7	Environmental Requirements	4			

Appendix A	Example of Qualification Inspection Report	9
Appendix B	Example of Qualification Retention Inspection Report	10
Appendix C	Example of Quality Conformance Inspection Report	11

Figures

Figure 4-1	IPC-B-25A	7
Figure 4-2	Test Coupon with “Y” Shape Pattern	7

Tables

Table 3-1	Requirements for Qualification, Qualification Retention and Quality Conformance of Conformal Coating Products	3
Table 4-1	Test Vehicles and Sample Sizes	6
Table 4-2	Thickness Requirements on Test Vehicle	7

Qualification and Performance of Electrical Insulating Compound for Printed Wiring Assemblies

1 SCOPE

1.1 Scope This standard establishes qualification and conformance requirements for electrical insulating compounds (conformal coatings). It has been designed and constructed with the intent of obtaining maximum confidence in the materials with minimum test redundancy. This standard covers:

- The qualification and qualification retention of the conformal coating material (Table 3-1, Column A and B).
- The quality conformance of conformal coating material properties (Table 3-1, Column C).

For the purpose of this standard, the term conformal coating is used herein when referring to a type of protective coating for use on printed wiring assemblies. The conformal coating is intended to provide protection from moisture and contamination and provide electrical insulation; not as a sole source of mechanical support.

For the purpose of this standard, inspections are performed on standardized test vehicles instead of real production assemblies. A standardized test vehicle refers to the test vehicle specified per test method indicated, coated with the conformal coating under inspection.

1.2 Purpose With standardized testing on standardized test vehicles under test conditions specified in test methods listed herein, this standard enables a manufacturer to qualify his conformal coating product and express the qualification it possesses. This standard also enables the manufacturer to attest the conformance of the quality of production to the qualification of each product.

1.3 Classification

1.3.1 Types Conformal coatings **shall** be categorized into types by the cured chemistry of the coating. The type for multifunctional materials **shall** be based on the chemistry type which is the highest percentage by weight.

Conformal coatings **shall** be of the following types:

Type AR — Acrylic
 Type ER — Epoxy
 Type SR — Silicone
 Type UR — Polyurethane
 Type XY — Paraxylylene

1.3.2 Classes Although previous versions of IPC-CC-830 made reference to Class A and Class B coating classifications, these classifications have been removed. To be qualified to this specification, a coating must be hydrolytically stable (formerly Class B). Non-hydrolytically stable coatings (formerly Class A) no longer meet the requirements of this specification and usage will only be As Agreed Between User and Supplier (AABUS). Coatings that meet the requirements of Class B coatings in previous document revisions meet the requirements of this revision.

Note: Earlier versions of this specification, as well as other IPC documents, made reference to “Class 1,” “Class 2,” and “Class 3” inspection and testing requirements for these classes that were not directly correlated to the previous Class A and B requirements.

1.4 Interpretation “**Shall**,” the imperative form of the verb, is used throughout this standard whenever a requirement is intended to express a provision that is mandatory. Deviation from a “**shall**” requirement may be considered if sufficient data is supplied to justify the exception.

The words “should” and “may” are used whenever it is necessary to express nonmandatory provisions. “Will” is used to express a declaration of purpose.

To assist the reader, the word “**shall**” is presented in bold characters.

2 APPLICABLE DOCUMENTS

The following documents of the issue currently in effect form a part of this standard to the extent specified herein.

2.1 IPC¹

IPC-B-25A Multipurpose Test Board

IPC-T-50 Terms and Definitions for Interconnecting and Packaging Electronic Circuits

IPC-TM-650 Test Methods Manual²

2.4.5.1 Flexibility

2.5.7.1 Dielectric Withstanding Voltage - Polymeric Conformal Coating

2.6.1.1 Fungus Resistance - Conformal Coating

2.6.3.4 Moisture and Insulation Resistance - Conformal Coating

1. www.ipc.org

2. Current and revised IPC Test Methods are available through IPC-TM-650 subscription and on the IPC Web site (www.ipc.org/html/testmethods.htm).