

**Report on Steel Reinforcement—  
Material Properties and  
U.S. Availability**

Reported by ACI Committee 439



**American Concrete Institute®**



First Printing  
October 2009

American Concrete Institute®  
*Advancing concrete knowledge*

## **Report on Steel Reinforcement— Material Properties and U.S. Availability**

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI. Proper use of this document includes periodically checking for errata at [www.concrete.org/committees/errata.asp](http://www.concrete.org/committees/errata.asp) for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

**Order information:** ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised *ACI Manual of Concrete Practice* (MCP).

**American Concrete Institute**  
**38800 Country Club Drive**  
**Farmington Hills, MI 48331**  
**U.S.A.**

**Phone: 248-848-3700**  
**Fax: 248-848-3701**

**[www.concrete.org](http://www.concrete.org)**

ISBN 978-0-87031-348-6

# Report on Steel Reinforcement— Material Properties and U.S. Availability

Reported by ACI Committee 439

Mark D. Marvin  
Chair

William C. Gallenz  
Secretary

Joseph A. Bohinsky

Paul S. Fredrickson

Peter Meza

Mario A. Rodriguez

Domingo J. Carreira\*

Todd R. Hawkinson

Theodore A. Mize\*

Philip E. Ross

Augusta Carroll

Steven H. Holdsworth

Conrad Paulson

Clifford A. Sabo

Louis J. Colarusso

Allen J. Hulshizer

Ryan W. Pelter

Robert G. Smith

David H. DeValve

Harry B. Lancelot, III

Richard A. Ramsey

Dyke W. Starnes

Gustav G. Erlemann†

Kenneth A. Luttrell

Roy H. Reiterman

Kenneth W. Williamson

Salem S. Faza

LeRoy A. Lutz\*

Robert C. Richardson

William H. Zehrt, Jr.

Anthony L. Felder\*

A. Murray Lount†

\*Subcommittee members who produced this report.

†Deceased.

*The material properties of the various types of steel reinforcement produced for use in the United States are described. Types of steel reinforcement defined in this report include deformed reinforcing bars, plain and deformed wire, welded wire reinforcement, bar mats, and prestressing reinforcement. The requirements, restrictions, and testing information of the pertinent ASTM specifications are reviewed. The availability of the various types and sizes of reinforcement in the U. S. is discussed.*

**Keywords:** bend tests; bending (reinforcing steels); deformed reinforcement; deformed reinforcing bars; ductility; material properties; prestressing steels; reinforced concrete; reinforcing steels; specifications; spiral reinforcement; tensile strength; welded reinforcement grids; welded wire fabric; welded wire reinforcement; yield strength.

ACI Committee Reports, Guides, Manuals, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

## CONTENTS

### Chapter 1—Introduction and scope, p. 439.4R-2

1.1—Introduction

1.2—Scope

### Chapter 2—Notation and definitions, p. 439.4R-2

2.1—Notation

2.2—Definitions

### Chapter 3—Reinforcing bars, p. 439.4R-2

3.1—Introduction

3.2—Material properties

3.3—Availability

3.4—Welding

3.5—Material testing

3.6—Spirals and mats

3.7—Corrosion protection products

ACI 439.4R-09 supersedes ACI 439.4R-89 and was adopted and published October 2009.

Copyright © 2009, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

**Chapter 4—Plain and deformed wire, p. 439.4R-10**

- 4.1—Introduction
- 4.2—Material properties
- 4.3—Wire size designation
- 4.4—Availability
- 4.5—Corrosion protection products

**Chapter 5—Welded wire reinforcement, p. 439.4R-11**

- 5.1—Introduction
- 5.2—Material properties
- 5.3—Higher-strength welded wire reinforcement
- 5.4—Welded wire reinforcement styles
- 5.5—Availability
- 5.6—Minimum quantity requirements
- 5.7—Corrosion protection products

**Chapter 6—Prestressing reinforcement, p. 439.4R-13**

- 6.1—Introduction
- 6.2—Material properties
- 6.3—Availability
- 6.4—Corrosion protection products
- 6.5—Other prestressing reinforcement

**Chapter 7—Developments in reinforcing steel, p. 439.4R-17**

- 7.1—High relative rib area reinforcing bars
- 7.2—Low-carbon, chromium steel reinforcing bars

**Chapter 8—References, p. 439.4R-18**

- 8.1—Referenced standards and reports
- 8.2—Cited references

**CHAPTER 1—INTRODUCTION AND SCOPE****1.1—Introduction**

The material properties of the various types of steel reinforcement produced for use in the U.S. are described. Types of steel reinforcement defined in this report include deformed reinforcing bars, plain and deformed wire, welded wire reinforcement, bar mats, and prestressing reinforcement. The requirements, restrictions, and testing information of pertinent ASTM specifications are reviewed. The availability of the various types and sizes of reinforcement in the U.S. is discussed.

**1.2—Scope**

Requirements for reinforcement are stated in Section 3.5.1 of ACI 318-08 as: “Reinforcement shall be deformed reinforcement, except that plain reinforcement shall be permitted for spirals or prestressing steel...” Deformed reinforcement is defined in Section 2.2 of ACI 318-08 as: “Deformed reinforcing bars, bar mats, deformed wire, welded wire reinforcement conforming to Section 3.5.3.” This report excludes discussion of structural steel, steel pipe, steel tubing, steel fibers, expanded metal, and fiber-reinforced polymers (FRP) and other nonmetallic reinforcement.

This report describes these types of steel reinforcement in terms of availability and material properties, expressed in inch-pound units and metric units. The special requirements

of ACI 349 and 359 are also discussed. American Association of State Highway and Transportation Officials (AASHTO) requirements (2002, 2004) are not discussed in this report because they generally follow ACI 318.

**CHAPTER 2—NOTATION AND DEFINITIONS****2.1—Notation**

There is no notation used in this document.

**2.2—Definitions**

**compacted strand**—prestressing strand that is drawn through a circular die deforming the wires to produce a strand with a smaller circular shape.

**indented strand**—prestressing strand in which the outer wires have small indentations to permit more rapid transfer of strand force to the concrete.

See ACI CT, ‘Concrete Terminology,’ for definitions at the ACI Web site, [http://www.concrete.org/Technical/CCT/FlashHelp/ACI\\_Terminology.htm](http://www.concrete.org/Technical/CCT/FlashHelp/ACI_Terminology.htm).

**CHAPTER 3—REINFORCING BARS****3.1—Introduction**

Reinforcing bars are the most popular type of nonprestressed reinforcing steel used in concrete construction. Approximately 10 million tons of reinforcing bars are used in the U.S. every year. Nearly all reinforced concrete construction, including precast and prestressed structures, requires some reinforcing bars.

Most of the reinforcing bars used in construction are deformed bars; that is, the bars have deformations to enhance the bond of the steel to the surrounding concrete. Limits on the deformation dimensions, such as the minimum deformation height and maximum deformation spacing, are prescribed in ASTM specifications. Plain reinforcing bars, which do not have deformations, are only permitted by ACI 318 for spiral reinforcement as used in reinforced concrete columns.

**3.2—Material properties**

The mechanical property requirements, chemical composition restrictions, and other requirements of the ASTM specifications for reinforcing bars are summarized in Tables 3.1 through 3.3. Reinforcing bars are primarily a hot-rolled product. The bars are manufactured by a steel mill using electric-arc furnaces to melt scrap steel to produce billets. These billets are then heated and passed through a series of rolls to make reinforcing bars. The deformations are formed on the bars during the final pass through the rolls.

Most of the properties of reinforcing bars of interest to the Architect/Engineer are defined by ASTM specifications. The significance of certain properties as defined by ASTM, however, is not readily apparent, and some special properties related to structural design are not defined by ASTM. Therefore, a brief review of the significance of various mechanical properties on structural design is appropriate. Plots of idealized stress-strain curves for ASTM A615 and ASTM A706 reinforcing bars are shown for two strain ranges in Fig. 3.1.

Of prime importance in structural design is the yield strength of nonprestressed reinforcement. ACI 318 requires determination of yield strengths over 60 ksi (420 MPa) at a