



ANSI/HI 3.1-3.5-2015

American National Standard for

Rotary Pumps

for Nomenclature, Definitions,
Application and Operation



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

American National Standard for

Rotary Pumps

for Nomenclature, Definitions,
Application, and Operation

Sponsor

Hydraulic Institute

www.Pumps.org

Approved September 25, 2015

American National Standards Institute, Inc

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406

www.Pumps.org

Copyright © 2015 Hydraulic Institute

All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-1-935762-42-3

Contents

| | |
|----------|----------------------------------|
| Foreword |vii |
| 3.1 | Types and nomenclature..... 1 |
| 3.1.1 | Scope..... 7 |
| 3.1.2 | Sliding vane (rigid)..... 7 |
| 3.1.3 | Axial piston pumps..... 7 |
| 3.1.4 | Flexible member..... 8 |
| 3.1.5 | Lobe..... 9 |
| 3.1.6 | Gear..... 9 |
| 3.1.7 | Circumferential piston..... 11 |
| 3.1.8 | Screw..... 11 |
| 3.2 | Definitions..... 15 |
| 3.2.1 | Fluids and liquids..... 16 |
| 3.2.2 | Pumping chamber..... 16 |
| 3.2.3 | Inlet or suction port..... 16 |
| 3.2.4 | Outlet or discharge port..... 16 |
| 3.2.5 | Body..... 16 |
| 3.2.6 | End plate..... 16 |
| 3.2.7 | Stator..... 16 |
| 3.2.8 | Rotor..... 16 |
| 3.2.9 | Bearing..... 16 |
| 3.2.10 | Timing gear..... 17 |
| 3.2.11 | Rotating assembly..... 17 |
| 3.2.12 | Relief valve..... 17 |
| 3.2.13 | Stuffing box..... 17 |
| 3.2.14 | Gland..... 17 |
| 3.2.15 | Packing..... 17 |
| 3.2.16 | Lantern ring..... 18 |
| 3.2.17 | Seal chamber..... 18 |
| 3.2.18 | Mechanical seal..... 18 |
| 3.2.19 | Radial seal..... 18 |
| 3.2.20 | Direction of rotation..... 18 |
| 3.2.21 | Jacketed pump..... 18 |
| 3.2.22 | Rate of flow (Q)..... 18 |
| 3.2.23 | Displacement (D)..... 18 |
| 3.2.24 | Speed (n)..... 19 |

| | | |
|--------|--|----|
| 3.2.25 | Pump volumetric efficiency (η_v) | 19 |
| 3.2.26 | Slip (S)..... | 19 |
| 3.2.27 | Pressure (p)..... | 19 |
| 3.2.28 | Pump pressures..... | 20 |
| 3.2.29 | Differential pressure (Δp) | 21 |
| 3.2.30 | Maximum differential pressure (Δp_{max}) | 21 |
| 3.2.31 | Net positive inlet pressure available ($NPIPA$)..... | 21 |
| 3.2.32 | Net positive inlet pressure required ($NPIPR$)..... | 22 |
| 3.2.33 | Power (P)..... | 22 |
| 3.2.34 | Pump input power (P_p)..... | 22 |
| 3.2.35 | Pump output power (P_w)..... | 22 |
| 3.2.36 | Pump torque..... | 23 |
| 3.2.37 | Pump efficiency (η_p) | 23 |
| 3.2.38 | Multiphase..... | 23 |
| 3.2.39 | Letter (dimensional) designations..... | 23 |
| 3.3 | Design and application..... | 33 |
| 3.3.1 | Temperature (t)..... | 33 |
| 3.3.2 | Liquid identification and properties..... | 34 |
| 3.3.3 | Fluid type..... | 34 |
| 3.3.4 | Entrained or dissolved gases in liquids..... | 34 |
| 3.3.5 | Viscosity..... | 37 |
| 3.3.6 | Viscous response types..... | 38 |
| 3.3.7 | Effect of viscosity on pump and system performance..... | 40 |
| 3.3.8 | Specific gravity (s)..... | 41 |
| 3.3.9 | Vapor pressure..... | 41 |
| 3.3.10 | Effect of vapor pressure on pump performance..... | 42 |
| 3.3.11 | Other fluid properties..... | 42 |
| 3.3.12 | Drive specifications..... | 42 |
| 3.3.13 | Efficiency and energy conservation..... | 42 |
| 3.3.14 | Duty cycle..... | 44 |
| 3.3.15 | Other user requirements..... | 44 |
| 3.3.16 | Slurry applications..... | 44 |
| 3.3.17 | Rotary pump noise levels..... | 48 |
| 3.3.18 | Rotary multiphase pumps in oil and gas application..... | 50 |
| 3.3.19 | Data sheet..... | 50 |
| 3.4 | Installation, operation, and maintenance..... | 54 |
| 3.4.1 | Shipment inspection..... | 54 |
| 3.4.2 | Storage..... | 54 |

| | | |
|------------|-------------------------------------|----|
| 3.4.3 | Installation..... | 54 |
| 3.4.4 | Operation..... | 63 |
| 3.4.5 | Maintenance..... | 65 |
| 3.4.6 | Malfunctions: cause and remedy..... | 66 |
| 3.5 | Reference and source material..... | 70 |
| 3.5.1 | ASTM..... | 70 |
| 3.5.2 | Hydraulic Institute..... | 70 |
| 3.5.3 | 3-A Sanitary Standards..... | 70 |
| 3.5.4 | API..... | 70 |
| 3.5.5 | Igor J. Karassik, et al..... | 70 |
| 3.5.6 | Cameron Hydraulic Data..... | 71 |
| Appendix A | Index..... | 72 |

Figures

| | | |
|------------|--|----|
| 3.1a | — Types of rotary pumps..... | 1 |
| 3.1b | — Rotary pump consolidated range chart (metric units)..... | 5 |
| 3.1c | — Rotary pump consolidated range chart (US customary units)..... | 6 |
| 3.1.2 | — Sliding vane pump..... | 14 |
| 3.1.3 | — Axial piston pump..... | 14 |
| 3.1.4.1 | — Flexible vane pump..... | 14 |
| 3.1.4.2 | — Flexible tube pump (peristaltic)..... | 14 |
| 3.1.5a | — Single-lobe pump..... | 14 |
| 3.1.5b | — Three-lobe pump..... | 14 |
| 3.1.6.1 | — External gear pump..... | 14 |
| 3.1.6.2a | — Internal gear pump (with crescent)..... | 14 |
| 3.1.6.2b | — Internal gear pump (without crescent)..... | 14 |
| 3.1.7 | — Circumferential piston pump..... | 14 |
| 3.1.8.1 | — Single-screw pump (progressing cavity)..... | 14 |
| 3.1.8.2.1 | — Two-screw pump (timed)..... | 14 |
| 3.1.8.2.2a | — Three-screw single end pump (untimed)..... | 14 |
| 3.1.8.2.2b | — Three-screw double end pump (untimed)..... | 14 |
| 3.2.39a | — Internal gear pump (foot mounting)..... | 24 |
| 3.2.39b | — Internal gear pump (flange mounting)..... | 24 |
| 3.2.39c | — Internal gear pump (frame mounting)..... | 25 |

| | |
|--|----|
| 3.2.39d — Internal gear pump (close coupled)..... | 25 |
| 3.2.39e — External gear pump (flanged ports)..... | 26 |
| 3.2.39f — External gear pump (threaded ports)..... | 26 |
| 3.2.39g — External gear pump on baseplate..... | 27 |
| 3.2.39h — Timed screw pump on baseplate..... | 28 |
| 3.2.39i — Untimed screw pump..... | 29 |
| 3.2.39j — Lobe pump..... | 30 |
| 3.2.39k — Vane pump..... | 31 |
| 3.2.39l — Stuffing box or seal chamber..... | 32 |
| 3.3.4a — Effect of entrained gas only on liquid rate of flow of rotary pumps (metric units)..... | 35 |
| 3.3.4b — Effect of entrained gas only on liquid rate of flow of rotary pumps (US customary units)..... | 35 |
| 3.3.4c — Effect of dissolved gas only in saturated solution on liquid rate of flow of rotary pumps (metric units)..... | 36 |
| 3.3.4d — Effect of dissolved gas only in saturated solution on liquid rate of flow of rotary pumps (US customary units)..... | 36 |
| 3.3.13 — Specified conditions: constant speed, constant pressure..... | 43 |
| 3.3.16.1.4 — Materials hardness..... | 45 |
| 3.3.16.1.6 — Typical slurry system conversion curve..... | 46 |
| 3.3.16.2 — Differential pressure versus pump input power..... | 46 |
| 3.4.3.3 — Typical foundation bolts..... | 56 |
| 3.4.3.6 — Leveling and grouting..... | 57 |
| 3.4.3.8 — Types of misalignment..... | 58 |
| 3.4.3.10 — V-belt sheave and synchronous sprocket alignment..... | 60 |
| 3.4.3.11 — Pipe-to-pump alignment..... | 61 |

Tables

| | |
|---|----|
| 3.1a — Capability table - metric..... | 3 |
| 3.1b — Capability table - US customary units..... | 4 |
| 3.2a — Symbols and terminology..... | 15 |
| 3.2b — Subscripts..... | 15 |
| 3.3.5.4.1 — - Viscosity of common fluids..... | 37 |
| 3.4.6 — Malfunctions: cause and remedy..... | 67 |