



American National Standard for

Rotary Pump Tests

ANSI/HI 3.6-2016



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This page intentionally blank.

American National Standard for
Rotary Pump Tests

Sponsor
Hydraulic Institute
www.Pumps.org

Approved August 17, 2016
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406

www.Pumps.org

Copyright © 2016 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-1-935762-49-2



Recycled
paper

Contents

Page

Foreword	v
3.6 Rotary pump tests	1
3.6.1 Scope	1
3.6.2 Type of performance test	1
3.6.3 Terminology	1
3.6.4 Performance test	8
3.6.5 Hydrostatic test (optional)	16
3.6.6 Net positive inlet pressure required test (optional)	18
3.6.7 Rate of flow measurement	20
3.6.8 Measurement of pressure	22
3.6.9 Power measurements	24
3.6.10 Methods for rotary speed measurement	25
3.6.11 Temperature measurement	25
3.6.12 Suitable interval between calibrations for performance test instruments	25
Appendix A Index	27
Figures	
3.6.4.7.1 — Recommended test setup	10
3.6.4.9.5 — Speed correction values for pump input power for $x = 1.5$	15
3.6.4.10a — Pump performance at constant speed	15
3.6.4.10b — Pump performance at constant pressure	15
3.6.4.11.2 — Information data sheet	17
3.6.8a — Pressure tap opening with corrosion-related plug	22
3.6.8b — Welded-on pressure tap opening	22
3.6.8c — Loop manifold connecting pressure taps	22
3.6.8.1 — Use of calibrated Bourdon gauge	23
Tables	
3.6.3a — Symbols and terminology	3
3.6.3b — Subscripts	4
3.6.4.7.3 — Test tabulation	11
3.6.12 — Recommended instrument calibration interval	26

This page intentionally blank.

Foreword (Not part of Standard)

Purpose and aims of the Hydraulic Institute

The purpose and aims of the Hydraulic Institute are to promote the advancement of the pump manufacturing industry and further the interests of the public and to this end, among other things:

- a) Develop and publish standards.
- b) Address pump systems.
- c) Expand knowledge and resources.
- d) Educate the marketplace.
- e) Advocate for the industry.

Purpose of Standards and Guidelines

- a) Hydraulic Institute Standards and Guidelines are adopted in the public interest and are designed to help eliminate misunderstandings between the manufacturer, the purchaser, and/or the user and to assist the purchaser in selecting and obtaining the proper product for a particular need.
- b) Use of Hydraulic Institute Standards and Guidelines is completely voluntary. Existence of Hydraulic Institute Standards does not in any respect preclude a member from manufacturing or selling products not conforming to the standards.

Definition of a Standard of the Hydraulic Institute

Quoting from Article XV, Standards, of the By-Laws of the Institute, Section B:

“An Institute Standard defines the product, material, process or procedure with reference to one or more of the following: nomenclature, composition, construction, dimensions, tolerances, safety, operating characteristics, performance, quality, rating, testing and service for which designed.”

Definition of a Hydraulic Institute Guideline

A Hydraulic Institute Guideline is not normative. The guideline is tutorial in nature, to help the reader better understand the subject matter.

Comments from users

Comments from users of this standard will be appreciated, to help the Hydraulic Institute prepare even more useful future editions. Questions arising from the content of this standard may be directed to the Technical Director of the Hydraulic Institute. If appropriate, the inquiry will then be directed to the appropriate technical committee for provision of a suitable answer.

Revisions

American National Standards of the Hydraulic Institute are subject to constant review, and revisions are undertaken whenever it is found necessary because of new developments and progress in the art. If no revisions are made for five years, the standards are reaffirmed using the ANSI canvass procedure.

Disclaimer

This document was prepared by a committee of the Hydraulic Institute and approved by following ANSI essential requirements. Neither the Hydraulic Institute, Hydraulic Institute committees, nor any person acting on behalf of the Hydraulic Institute: 1) makes any warranty, expressed or implied, with respect to the use of any information, apparatus, method, or process disclosed in this document or guarantees that such may not infringe privately owned rights; 2) assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this guideline. The Hydraulic Institute is in no way responsible for

any consequences to an owner, operator, user, or anyone else resulting from reference to the content of this document, its application, or use.

This document does not contain a complete statement of all requirements, analyses, and procedures necessary to ensure safe or appropriate selection, installation, testing, inspection, and operation of any pump or associated products. Each application, service, and selection is unique with process requirements that shall be determined by the owner, operator, or its designated representative.

Units of measurement

Metric units of measurement are used, and corresponding US customary units appear in parentheses. Charts, graphs, and sample calculations are also shown in both metric and US customary units. Because values given in metric units are not exact equivalents to values given in US customary units, it is important that the selected units of measure to be applied be stated in reference to this standard. If no such statement is provided, metric units shall govern.

Consensus

Consensus for this American National Standard was achieved by use of the canvass method. The following organizations, recognized as having an interest in the standardization of pumps, were contacted prior to the approval of this revision of the standard. Inclusion in this list does not necessarily imply that the organization concurred with the submittal of the proposed standard to ANSI.

DuPont	Outotec
Flowsolve	Parametrix
Fluid Sealing Association	Patterson Pump Company
Hydraulic, Measurement, and Inspection Consulting, LLC	Peerless Pump/Grundfos
Kemet Inc.	Rotating Equipment Repair, Inc.
Las Vegas Valley Water District	Stantec
Leistriz Advanced Technologies Corp	Syncrude Canada
	Weir Floway, Inc.

Committee list

Although this standard was processed and approved for submittal to ANSI by the canvass method, a working committee met many times to facilitate its development. At the time it was developed, the committee had the following members:

Chair – Randy Bennett, Leistriz Advanced Technologies Corp.

Vice-chair – Nick Gryskiewicz, Boerger LLC

Committee members

David G. McKinstry
Bernhard Wessendorf

Company

Pumps Positive
Boerger LLC

3.6 Rotary pump tests

This standard recognizes various performance test levels designed to permit a reasonable selection of tests, tolerances, and accuracy requirements appropriate for the application and the customer’s needs.

Tests of rotary pumps that conform to the requirements of this standard shall be designated as tests conducted in accordance with the Hydraulic Institute Test Standards. Types of performance tests are defined in Section 3.6.2.

These standards apply to rotary pump tests only, unless stated otherwise. Recorded data and the final report may include information on drives and auxiliary equipment, and must be identified as such.

The type of test performed and the auxiliary equipment to be used (purchaser’s driver, gearbox, etc.) should be agreed on in writing by all interested parties before the test.

It is the intent of this standard to offer testing procedures to be used by all testing facilities. It is not the intent to limit or restrict tests to only those described herein. Variations in test procedures may exist without violating the intent of this standard. Exceptions may be taken to the provisions of this standard if properly agreed on by the parties involved without sacrificing the validity of the applicable parts of the standard.

Because pumps are used to handle different liquids or liquid/solid mixtures, it is necessary to limit this standard to the testing of pumps with readily available test liquids. For other than normal test liquids, some methods and procedures not outlined herein may be required.

The objective of the standard is to establish a uniform method for determining a pump’s ability to perform satisfactorily both mechanically and hydraulically. The quantitative values observed and recorded will depend on the type of test specified. The quantitative indices are the same for a particular type of test no matter what type of pump is specified.

3.6.1 Scope

This standard recognizes four types of performance tests for rotary pumps and provides procedures for conducting and reporting test data. The test levels have been designed to permit selection of tolerances and accuracy appropriate for the application and the customer’s needs. It does not include vibration or acoustical testing.

3.6.2 Type of performance test

The test types below apply to tests on liquids.

I	II	III	IV
Internal quality- assurance test	Speed Pressure Power	Speed Pressure Rate of Flow	Speed Pressure Rate of Flow Power

Type III and IV have two levels of acceptance for the quantitative values. The level of test is to be Level A unless otherwise specified by the user. Refer to Sections 3.6.4.4 and 3.6.4.5.

Optional tests: Hydrostatic test and net positive inlet pressure required test are separate tests and are described in Sections 3.6.5 and 3.6.6.

3.6.3 Terminology

The following terms, symbols, units, abbreviations, and definitions are used to designate test parameters or are used in connection with pump testing. For symbols and terminology, and subscripts, refer to Tables 3.6.3a and 3.6.3b, respectively.