

# FINAL VERSION

# VERSION FINALE

---

**Discharge lamps (excluding fluorescent lamps) – Safety specifications**

**Lampes à décharge (à l'exclusion des lampes à fluorescence) – Prescriptions de sécurité**



## CONTENTS

FOREWORD.....	6
1 Scope.....	8
2 Normative references .....	8
3 Terms and definitions .....	9
4 General safety requirements.....	11
4.1 General.....	11
4.2 Marking.....	11
4.2.1 Lamp marking.....	11
4.2.2 Additional information to be provided.....	12
4.3 Mechanical requirements .....	12
4.3.1 Requirements for caps.....	12
4.3.2 Construction and assembly.....	13
4.4 Electrical requirements .....	14
4.4.1 Parts which can become accidentally live .....	14
4.4.2 Insulation resistance.....	15
4.4.3 Electric strength .....	15
4.5 Thermal requirements .....	15
4.5.1 General .....	15
4.5.2 Resistance to heat.....	16
4.5.3 Resistance to abnormal heat and fire.....	16
4.6 Photobiological requirements .....	17
4.6.1 UV Hazard.....	17
4.6.2 Blue light hazard.....	18
4.6.3 IR hazard.....	18
5 Particular safety requirements .....	18
5.1 High-pressure sodium vapour lamps .....	18
5.2 Metal halide lamps.....	18
5.2.1 General .....	18
5.2.2 Marking .....	18
5.2.3 Containment.....	19
6 Information for luminaire design.....	19
7 Assessment.....	19
7.1 General.....	19
7.2 Assessment of whole production by means of manufacturer's records .....	19
7.3 Assessment of batches .....	19
7.3.1 Sampling for batch testing .....	19
7.3.2 Number of lamps in batch sample .....	20
7.3.3 Sequence of the tests .....	20
7.3.4 Rejection conditions for large batches (> 500 lamps).....	20
7.3.5 Rejection conditions for small batches ( $\leq$ 500 lamps).....	20
Annex A (normative) List of lamp caps and gauges.....	23
Annex B (normative) Pull and torsion test values .....	24
Annex C (normative) Torsion test holders .....	25
Annex D (normative) Information for thermal tests .....	27

Annex E (normative) Measurement of pulse height for lamps with internal starting device.....	28
E.1 Introduction.....	28
E.2 Test circuit.....	28
E.2.1 Test circuit and key .....	28
E.2.2 Ballast characteristics.....	28
E.2.3 Power factor capacitor .....	29
E.2.4 Pulse height measuring circuit.....	29
E.3 Tests .....	29
E.3.1 Lamps with an internal glow switch.....	29
E.3.2 Lamps with an internal thermal switch .....	29
Annex F (informative) Information for luminaire design .....	31
F.1 Guidelines for safe lamp operation.....	31
F.2 Maximum lamp cap temperature .....	31
F.3 Cap/holder – key configuration and information for class II luminaires .....	31
F.4 Protection against lamp shattering .....	32
F.5 Protection against UV radiation.....	32
F.6 Possible condition at end of lamp life .....	32
F.7 Water contact .....	33
Annex G (normative) Conditions of compliance for design tests .....	34
G.1 Insulation resistance (see 4.4.2) Electric strength (see 4.4.3) .....	34
G.2 Cap construction and assembly (see 4.3.2.2 b) and 4.3.2.3 b)) .....	34
G.3 Cap creepage distance (see 4.3.1.2) Resistance to heat (see 4.5.2.1 and 4.5.2.2) Resistance to abnormal heat and fire (see 4.5.3.1) Pulse height (see 5.1.) UV radiation (see 4.6.1.3) .....	34
Annex H (normative) Symbols.....	35
H.1 General.....	35
H.2 Symbol indicating that the lamp shall be operated only in a luminaire provided with a protective shield .....	35
H.3 Symbol indicating that the lamp emits a high level of UV radiation .....	35
H.4 Symbol indicating that the lamp shall not be operated when the outer bulb is broken .....	35
H.5 Self-shielded lamp symbol indicating that the lamp can be operated in a luminaire without a protective shield .....	36
H.6 Symbol indicating not to stare at a light source, for example, a lamp, a luminaire, a video projector etc. ....	36
Annex I (normative) Containment testing procedure for metal halide lamps with quartz arc tubes .....	37
I.1 General.....	37
I.1.1 Purpose.....	37
I.1.2 Test description .....	37
I.2 Experimental setup .....	37
I.2.1 Safety precautions.....	37
I.2.2 Electrical circuit.....	37
I.2.3 Enclosure requirements .....	39
I.3 Test procedures.....	39
I.3.1 Lamp selection and preparation.....	39
I.3.2 Determination of median rupture energy .....	39
I.3.3 Rupture test procedure .....	40

I.4	Self-shielded lamp design .....	40
I.4.1	Definition of damage to the outer bulb .....	40
I.4.2	Determination of self-shielded .....	40
Annex J (normative)	Containment testing procedure for metal halide lamps with ceramic arc tubes .....	41
J.1	General.....	41
J.1.1	Purpose.....	41
J.1.2	Test description .....	41
J.2	Experimental setup .....	41
J.2.1	Safety precautions.....	41
J.2.2	Electrical circuit.....	41
J.2.3	Enclosure requirements .....	42
J.3	Test procedures.....	42
J.3.1	Lamp selection and preparation .....	42
J.3.2	Determination of median rupture energy .....	42
J.3.3	Rupture test procedure .....	43
J.4	Self-shielded lamp design .....	43
J.4.1	Definition of damage to the outer bulb .....	43
J.4.2	Determination of containment rating .....	43
Annex K (informative)	Additional requirements for certification.....	45
K.1	General.....	45
K.2	Assessment of manufacturer’s records for particular tests .....	46
K.3	Sampling procedures for the whole production testing .....	46
Bibliography	.....	50
Figure 1	– Edison screw-capped lamp .....	15
Figure C.1	– Holder for torsion test on lamps with Edison screw caps .....	25
Figure C.2	– Holder for torsion test on lamps with bayonet caps .....	26
Figure D.1	– Ball pressure test apparatus .....	27
Figure E.1	– Test circuit.....	28
Figure I.1	– Basic electrical diagram for quartz metal halide lamp containment test .....	38
Figure J.1	– Electrical diagram for containment test.....	42
Table 1	– Classification of risk groups.....	17
Table 5	– Batch sample size and rejection number (for batches > 500 lamps) .....	21
Table 6	– Batch sample size and rejection number (for batches ≤ 500 lamps) .....	22
Table 7	– Voltage to be considered for creepage and clearance .....	13
Table A.1	– Data sheet references of IEC 60061 .....	23
Table B.1	– Pull test values .....	24
Table B.2	– Torsion test values.....	24
Table D.1	– Temperatures .....	27
Table E.1	– Test ballast resonance characteristics .....	29
Table E.2	– Power factor capacitor values for tests.....	29
Table F.1	– Maximum lamp cap temperatures.....	31
Table K.1	– Grouping of test records – Sampling and acceptable quality levels (AQL) .....	47

Table K.2 – Acceptance numbers AQL = 0,65 % ..... 48

Table K.3 – Acceptance numbers AQL = 2,5 % ..... 49

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**DISCHARGE LAMPS  
(EXCLUDING FLUORESCENT LAMPS) –  
SAFETY SPECIFICATIONS****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

**DISCLAIMER**

**This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.**

**This Consolidated version of IEC 62035 bears the edition number 2.1. It consists of the second edition (2014-04) [documents 34A/1600/CDV and 34A/1643/RVC] and its amendment 1 (2016-11) [documents 34A/1873/CDV and 34A/1909/RVC]. The technical content is identical to the base edition and its amendment.**

**This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.**

International Standard IEC 62035 has been prepared by subcommittee 34A: Lamps, of IEC technical committee 34: Lamps and related equipment.

This edition includes the following significant technical changes with respect to the previous edition. Photobiological safety requirements are taken care of on basis of the risk group concept of IEC 62471 and the technical report IEC TR 62778 on blue light hazard. This has consequences for terms, marking, structure of 4.6, and introduction of a new symbol “Caution, do not stare at light source”. Special attention is given to blue light hazard.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

## DISCHARGE LAMPS (EXCLUDING FLUORESCENT LAMPS) – SAFETY SPECIFICATIONS

### 1 Scope

This International Standard specifies the safety requirements for discharge lamps (excluding fluorescent lamps) for general lighting purposes.

This International Standard is applicable to low-pressure sodium vapour lamps and to high-intensity discharge (HID) lamps, i.e. high-pressure mercury vapour lamps (including blended lamps), high-pressure sodium vapour lamps and metal halide lamps. It applies to single- and double-capped lamps, having caps as listed in Annex A.

This standard only concerns safety criteria and does not take into account performance. The performance standards IEC 60188, IEC 60192, IEC 60662, IEC 61167 and IEC 61549 should be referred to for such characteristics.

It may be expected that lamps which comply with this standard will operate safely at supply voltages between 90 % and 110 % of rated supply voltage and when operated with a ballast complying with IEC 61347-2-9 and IEC 60923, with a starting device complying with IEC 61347-2-1 and IEC 60927, and in a luminaire complying with IEC 60598-1.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050, *International Electrotechnical Vocabulary* (available at <http://www.electropedia.org>)

IEC 60061-1, *Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 1: Lamp caps*

IEC 60061-2, *Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 2: Lampholders*

IEC 60061-3, *Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 3: Gauges*

IEC 60061-4, *Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 4: Guidelines and general information*

IEC 60155, *Glow-starters for fluorescent lamps*

IEC 60598-1:2014, *Luminaires – Part 1: General requirements and tests*

IEC 60662, *High-pressure sodium vapour lamps*