

Reporting of Fuel Properties When Testing Diesel Engines with Alternative Fuels Derived from Plant Oils and Animal Fats



S T A N D A R D

American Society of Agricultural and Biological Engineers

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as "ASAE", regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as "ASABE".

Standards designated as "ANSI" are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, fax 269-429-3852, hq@asabe.org

Reporting of Fuel Properties When Testing Diesel Engines with Alternative Fuels Derived from Plant Oils and Animal Fats

Developed by the ASAE Biomass Energy and Industrial Products Committee; approved by the ASAE Food and Process Engineering Institute Standards Committee; adopted by ASAE January 1996; reaffirmed December 2001, January 2007; revised December 2009; reaffirmed December 2014; revised May 2017; editorially revised December 2018.

Keywords: Alternative fuel, Diesel, Engines, Fuel testing

1 Purpose and Scope

1.1 This Engineering Practice establishes a minimum set of fuel properties that shall be included with the report of diesel engine performance on alternative fuels derived from plant oils, animal fats and other bio-based feedstocks including blends of these bio-based fuels with petroleum-derived diesel fuel. While this Engineering Practice focuses on methyl and ethyl esters (biodiesel), various other alternative fuels from many plant and animal sources may have applications as diesel engine fuels, including straight vegetable oil (not transesterified), algal biofuels, thermochemical biofuels, and various other advanced biofuels. These alternative fuels are collected and processed using a variety of methods, which can influence their physical and chemical properties. In addition, they are tested in diesel engines using a range of procedures. To facilitate comparison of test data, it is essential that some reference point or baseline be established. This Engineering Practice is designed to provide a consistent set of data for these alternative fuels when used as diesel fuel replacements, and it will help to identify deviations from normal expected fuel characteristics that have been established for petroleum-derived fuels.

1.2 This Engineering Practice specifies which fuel properties shall be reported and lists the procedure that shall be used to measure these properties. It does not establish a requirement for any fuel property. The minimum documentation of every engine test should include those items listed in clause 4, with a few exceptions as noted below. The total data set should be reported whenever possible, although it is recognized that some data are difficult to obtain on every batch of fuel. In some cases, specific fuel properties listed below may not be relevant for a specific category of fuel. Two examples are the fatty acid composition and glycerol composition of thermochemical biofuels that are not processed from a fat or oil and thus do not include these components. It should be clearly indicated whether the batch of fuel was specifically tested for the data being reported, and whether a listed property is not relevant for the particular class of fuel.

1.3 This Engineering Practice does not specify an engine test procedure; however, it is expected that a complete description of the test procedure will be provided with the test report.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ASTM D93 *Standard Test Method for Flash Point by Pensky-Martens Closed Cup Tester*

ASTM D97 *Standard Test Method for Pour Point of Petroleum Products*

ASTM D130 *Standard Test Method for Detection of Copper Corrosion from Petroleum Products by the Copper Strip Tarnish Test*

ASTM D240 *Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter*