

# FINAL VERSION

## VERSION FINALE

**Electromagnetic compatibility (EMC) –  
Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker  
in public low-voltage supply systems, for equipment with rated current  $\leq 16$  A  
per phase and not subject to conditional connection**

**Compatibilité électromagnétique (CEM) –  
Partie 3-3: Limites – Limitation des variations de tension, des fluctuations de  
tension et du papillotement dans les réseaux publics d'alimentation basse  
tension, pour les matériels ayant un courant assigné  $\leq 16$  A par phase et non  
soumis à un raccordement conditionnel**

## CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references .....	7
3 Terms and definitions .....	8
4 Assessment of voltage changes, voltage fluctuations and flicker .....	10
4.1 Assessment of a relative voltage change, $d(t)$ .....	10
4.2 Assessment of the short-term flicker value, $P_{st}$ .....	11
4.2.1 General .....	11
4.2.2 Flickermeter .....	11
4.2.3 Simulation method.....	11
4.2.4 Analytical method .....	11
4.2.5 Use of $P_{st} = 1$ curve .....	12
4.3 Assessment of long-term flicker value, $P_{lt}$ .....	12
5 Limits .....	12
6 Test conditions .....	13
6.1 General.....	13
6.2 Measurement uncertainty .....	14
6.3 Test supply voltage .....	14
6.4 Reference impedance.....	14
6.5 Observation period.....	15
6.6 General test conditions.....	15
Annex A (normative) Application of limits and type test conditions for specific equipment.....	19
Annex B (normative) Test conditions and procedures for measuring $d_{max}$ voltage changes caused by manual switching .....	27
Annex C (informative) Determination of steady state voltage and voltage change characteristics, as defined in IEC 61000-4-15:2010 .....	28
Annex D (informative) Input relative voltage fluctuation $\Delta V/V$ for $P_{st} = 1,0$ at output [IEC/TR 61000-3-7:2008] .....	33
Bibliography.....	34
Figure 1 – Reference network for single-phase and three-phase supplies derived from a three-phase, four-wire supply.....	16
Figure 2 – Curve for $P_{st} = 1$ for rectangular equidistant voltage changes .....	17
Figure 3 – Shape factors $F$ for double-step and ramp-voltage characteristics.....	17
Figure 4 – Shape factors $F$ for rectangular and triangular voltage characteristics .....	18
Figure 5 – Shape factor $F$ for motor-start voltage characteristics having various front times.....	18
Figure C.1 – Evaluation of $U_{hp}(t)$ .....	32
Table 1 – Assessment method .....	11
Table A.1 – Test conditions for hotplates .....	19
Table A.2 – Electrode parameters.....	24

Table A.3 – Frequency factor $R$ related to repetition rate " $r$ " .....	25
Table C.1 – Test specification for $d_C - d_{\max} - t_{d(t)} > 3,3\%$ (from Table 12 of IEC 61000-4-15: 2010).....	31
Table C.2 – Test specification for $d_C - d_{\max} - t_{d(t)} > 3,3\%$ (from Table 13 of IEC 61000-4-15: 2010).....	31
Table D.1 – Input relative voltage fluctuation $\Delta V/V$ for $P_{St} = 1,0$ at output .....	33

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### ELECTROMAGNETIC COMPATIBILITY (EMC) –

#### **Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current $\leq 16$ A per phase and not subject to conditional connection**

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

#### **DISCLAIMER**

**This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.**

**This Consolidated version of IEC 61000-3-3 bears the edition number 3.1. It consists of the third edition (2013-05) [documents 77A/809/FDIS and 77A/816/RVD] and its amendment 1 (2017-05) [documents 77A/952/FDIS and 77A/960/RVD]. The technical content is identical to the base edition and its amendment.**

**This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.**

International Standard IEC 61000-3-3 has been prepared by subcommittee 77A: EMC – Low frequency phenomena, of IEC technical committee 77: Electromagnetic compatibility.

This standard forms part 3-3 of IEC 61000 series of standards. It has the status of a product family standard.

This third edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) This edition takes account of the changes made in IEC 61000-4-15:2010.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61000 series, published under the general title *Electromagnetic compatibility (EMC)*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

## INTRODUCTION

IEC 61000 is published in separate parts according to the following structure:

### Part 1: General

General considerations (introduction, fundamental principles)

Definitions, terminology

### Part 2: Environment

Description of the environment

Classification of the environment

Compatibility levels

### Part 3: Limits

Emission limits

Immunity limits (in so far as they do not fall under the responsibility of product committees)

### Part 4: Testing and measurement techniques

Measurement techniques

Testing techniques

### Part 5: Installation and mitigation guidelines

Installation guidelines

Mitigation methods and devices

### Part 9: Miscellaneous

Each part is further subdivided into sections which are to be published either as International Standards or as Technical Reports.

These standards and reports will be published in chronological order and numbered accordingly.

## ELECTROMAGNETIC COMPATIBILITY (EMC) –

### Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current $\leq 16$ A per phase and not subject to conditional connection

#### 1 Scope

This part of IEC 61000 is concerned with the limitation of voltage fluctuations and flicker impressed on the public low-voltage system.

It specifies limits of voltage changes which may be produced by an equipment tested under specified conditions and gives guidance on methods of assessment.

This part of IEC 61000 is applicable to electrical and electronic equipment having an input current equal to or less than 16 A per phase, intended to be connected to public low-voltage distribution systems of between 220 V and 250 V line to neutral at 50 Hz, and not subject to conditional connection.

Equipment which does not comply with the limits of this part of IEC 61000 when tested with the reference impedance  $Z_{ref}$  of 6.4, and which therefore cannot be declared compliant with this part, may be retested or evaluated to show conformity with IEC 61000-3-11. Part 3-11 is applicable to equipment with rated input current  $\leq 75$  A per phase and subject to conditional connection.

The tests according to this part are type tests. Particular test conditions are given in Annex A and the test circuit is shown in Figure 1.

NOTE 1 The limits in this standard relate to the voltage changes experienced by consumers connected at the interface between the public supply low-voltage network and the equipment user's installation. Consequently, if the actual impedance of the supply at the supply terminals of equipment connected within the equipment user's installation exceeds the test impedance, it is possible that supply disturbance exceeding the limits could occur.

NOTE 2 The limits in this standard are based mainly on the subjective severity of flicker imposed on the light from 230 V 60 W coiled-coil filament lamps by fluctuations of the supply voltage. For systems with nominal voltage less than 220 V line to neutral and/or frequency of 60 Hz, the limits and reference circuit values are under consideration.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC/TR 60725, *Consideration of reference impedances and public supply impedances for use in determining disturbance characteristics of electrical equipment having a rated current  $\leq 75$  A per phase*

IEC 60974-1, *Arc welding equipment – Part 1: Welding power sources*

IEC 61000-3-2, *Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current  $\leq 16$  A per phase)*