

# Care, Handling, and Installation of Internally Plastic-Coated Oilfield Tubular Goods and Accessories

This NACE International standard represents a consensus of those individual members who have reviewed this document, its scope, and provisions. Its acceptance does not in any respect preclude anyone, whether he has adopted the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in conformance with this standard. Nothing contained in this NACE International standard is to be construed as granting any right, by implication or otherwise, to manufacture, sell, or use in connection with any method, apparatus, or product covered by Letters Patent, or as indemnifying or protecting anyone against liability for infringement of Letters Patent. This standard represents minimum requirements and should in no way be interpreted as a restriction on the use of better procedures or materials. Neither is this standard intended to apply in all cases relating to the subject. Unpredictable circumstances may negate the usefulness of this standard in specific instances. NACE International assumes no responsibility for the interpretation or use of this standard by other parties and accepts responsibility for only those official NACE International interpretations issued by NACE International in accordance with its governing procedures and policies which preclude the issuance of interpretations by individual volunteers.

Users of this NACE International standard are responsible for reviewing appropriate health, safety, environmental, and regulatory documents and for determining their applicability in relation to this standard prior to its use. This NACE International standard may not necessarily address all potential health and safety problems or environmental hazards associated with the use of materials, equipment, and/or operations detailed or referred to within this standard. Users of this NACE International standard are also responsible for establishing appropriate health, safety, and environmental protection practices, in consultation with appropriate regulatory authorities if necessary, to achieve compliance with any existing applicable regulatory requirements prior to the use of this standard.

**CAUTIONARY NOTICE:** NACE International standards are subject to periodic review, and may be revised or withdrawn at any time without prior notice. NACE International requires that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of initial publication. The user is cautioned to obtain the latest edition. Purchasers of NACE International standards may receive current information on all standards and other NACE International publications by contacting the NACE International *FirstService* Department, 15835 Park Ten Place, Houston, Texas 77084, telephone +1 281-228-6223.

## **ABSTRACT**

*This standard recommended practice covers the care, handling, transportation, and installation of internally plastic-coated (IPC) oilfield tubular goods and accessories (IPC material). It presents guidelines for the proper care, handling, and installation of IPC oilfield tubular goods and accessories. This standard is maintained by Task Group 486.*

## **KEYWORDS**

*Oilfield, composites, maintenance*

## Foreword

***In NACE standards, the terms “shall,” “must,” “should,” and “may” are used in accordance with the definitions of these terms in the NACE Publications Style Manual. The terms “shall” and “must” are used to state a requirement, and are considered mandatory. The term “should” is used to state something good and is recommended, but is not considered mandatory. The term “may” is used to state something considered optional.***

This standard practice covers the care, handling, transportation, and installation of internally plastic-coated (IPC) oilfield tubular goods and accessories (IPC material). Some internal plastic coatings are inherently brittle or may be incompatible with various chemicals used in oil and gas production operations and therefore are susceptible to damage from poor handling procedures, well operations, and chemical attack. Coating damage (e.g., cracks, chips, and disbondment) reduces coating effectiveness and results in premature coating failure. To minimize coating damage and prolong coating life, special handling and operating procedures must be used with IPC material during all phases of storage, transport, installation, and operation. Following the guidelines presented in this standard helps users, oil and gas producers, transportation companies, workover companies, and well-servicing companies and personnel to ensure the most cost-effective use of IPC material.

This standard was originally prepared in 1991 by NACE Task Group T-1G-4, a component of Unit Committee T-1G on Protective Coatings, Elastomers, and Other Nonmetallic Materials for Oilfield Use. It was reaffirmed in 1996 by T-1G, and revised in 2005 by Task Group (TG) 087, “Reaffirmation, Revision, or Withdrawal of STG 33 Standards and Technical Committee Reports.” It was revised in 2015 by TG 486, “Review of NACE Standard RP0291-2005.” TG 486 is administered by Specific Technology Group (STG) 33, “Oil and Gas Production—Nonmetallics and Wear Coatings (Metallic),” and sponsored by STG 03, “Protective Coatings and Linings—Immersion/Buried.” This standard is published by NACE International under the auspices of STG 33.

# Care, Handling, and Installation of Internally Plastic-Coated Oilfield Tubular Goods and Accessories

1.	General .....	4
2.	Definitions .....	4
3.	Preliminary Requirements.....	4
4.	Yard Storage .....	5
5.	Transportation .....	5
6.	Well/Job Site Storage.....	7
7.	IPC Tubular Goods Installation .....	7
8.	IPC Accessory Installation.....	8
9.	Operation .....	8
10.	Special Handling—Internally Coated Corrosion-Resistant Alloys (CRAs) .....	10
11.	Inspection/Quality Control.....	10
	References.....	11