

ACI 549.1R-18

Design Guide for Ferrocement

Reported by ACI Committee 549



American Concrete Institute
Always advancing



Design Guide for Ferrocement

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Design Guide for Ferrocement

Reported by ACI Committee 549

Antonio Nanni*, Chair

Corina-Maria Aldea, Secretary

Nemkumar Banthia
Dale P. Bentz
Christian Carloni
Paolo Casadei
Antonio De Luca
Michael E. Driver

Ashish Dubey
Usama A. Ebead
Mahmut Ekenel
Brad L. Erickson
Garth J. Fallis
Barzin Mobasher

Hani H. Nassif
James E. Patterson
Bekir Yilmaz Pekmezci
Alva Peled
Larry Rowland
Surendra P. Shah

Yixin Shao
Lesley H. Sneed
J. Gustavo Tumialan

Consulting Members

Gordon B. Batson
James I. Daniel

John Jones†
Antoine E. Naaman*

Paul Nedwell*
P. Paramasivam

Parviz Soroushian

*Members of subcommittee that prepared this report.

†Chair of subcommittee that prepared this report.

This guide provides technical information on physical and mechanical properties, design criteria, and testing of ferrocement. The objectives are to promote the most effective use of ferrocement in terrestrial structures, provide architects and engineers with the necessary tools to specify and use ferrocement, and provide owners or their representatives with a reference document to check the acceptability of a ferrocement alternative in a given application.

Keywords: composite materials; construction materials; ferrocement; fibers; reinforcing materials; structural design; welded wire fabric.

CONTENTS

CHAPTER 1—GENERAL, p. 2

- 1.1—Scope, p. 2
- 1.2—Approval for use in design and construction, p. 2

CHAPTER 2—NOTATION AND DEFINITIONS, p. 2

- 2.1—Notation, p. 2
- 2.2—Definitions, p. 3

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

CHAPTER 3—PHYSICAL AND MECHANICAL PROPERTIES, p. 3

- 3.1—Introduction, p. 3
- 3.2—Reinforcing parameters, p. 3
- 3.3—Ultimate strength under static load, p. 4
- 3.4—First-crack strength under static load, p. 8
- 3.5—Elasticity and load-deformation behavior, p. 9
- 3.6—Strength under fatigue loading, p. 10
- 3.7—Impact resistance, p. 11
- 3.8—Crack development and leakage, p. 11
- 3.9—Shrinkage and creep, p. 11
- 3.10—Durability, p. 12
- 3.11—Fire resistance, p. 13

CHAPTER 4—PERFORMANCE CRITERIA, p. 13

- 4.1—Introduction, p. 13
- 4.2—Design methods, p. 13
- 4.3—Allowable tensile stress, p. 14
- 4.4—Allowable compressive stress, p. 14
- 4.5—Volume fraction and specific surface of reinforcement, p. 14
- 4.6—Cover requirements, p. 14
- 4.7—Crack width limitations, p. 14
- 4.8—Stress range, p. 14

CHAPTER 5—DESIGN CRITERIA, p. 14

- 5.1—Design methods, p. 14

ACI 549.1R-18 supersedes ACI 549.1R-93 was adopted and published September 2018.

Copyright © 2018, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

- 5.2—Strength requirements, p. 15
- 5.3—Service load design, p. 17
- 5.4—Serviceability, p. 17
- 5.5—Particular design parameters, p. 17
- 5.6—Examples, p. 18
- 5.7—Design aids, p. 18

CHAPTER 6—TESTING, p. 18

- 6.1—Test methods, p. 18

CHAPTER 7—REFERENCES, p. 20

- Authored documents, p. 20

APPENDIX A—CALCULATION OF VOLUME FRACTION OF REINFORCEMENT, p. 23

APPENDIX B—FLEXURAL STRENGTH ANALYSIS OF FERROCEMENT SECTIONS, p. 23

APPENDIX C—SIMPLIFIED DESIGN AIDS, p. 27

CHAPTER 1—GENERAL

1.1—Scope

This guide is based on technical information assembled from current practice, developments, and advances in the field of ferrocement around the world. It represents a practical supplement to ACI 549R. This guide covers physical and mechanical properties, performance and design criteria, and testing.

The objectives of this guide, in conjunction with ACI 549R, are to promote the effective use of ferrocement in structures, provide architects and engineers with the necessary tools to specify and use ferrocement, and provide owners or their representatives with a reference document to check the acceptability of a ferrocement alternative in a given application. This guide is consistent with ACI 318, except for the special characteristics of ferrocement, such as reinforcement cover and limits on deflection.

Ferrocement is a form of reinforced concrete using closely spaced multiple layers of mesh, small-diameter rods completely infiltrated with mortar, or encapsulated in mortar, or both. The most common type of reinforcement is steel mesh. Other materials such as selected organic, natural, or synthetic fibers may be combined with metallic mesh. This guide addresses only the use of steel reinforcement in a hydraulic cement mortar matrix.

Applications of ferrocement are numerous, especially in structures or structural components where self-help or low levels of skills are required. Besides boats and marine structures, ferrocement is also used for housing units, water tanks, grain silos, flat or corrugated roofing sheets, and irrigation channels (ACI 549R).

1.2—Approval for use in design and construction

Use of ferrocement and the procedures covered in this guide may require approval by the authority or governmental agency having jurisdiction over the project.

CHAPTER 2—NOTATION AND DEFINITIONS

2.1—Notation

- A_c = cross-sectional area of ferrocement composite
- A_s = total effective cross-sectional area of reinforcement in the direction considered
- $A_s = \sum_{i=1}^N A_{si} = \sum_{i=1}^N A_{si}$
- A_{si} = effective cross-sectional area of reinforcement of mesh layer i in the direction considered
- b = width of ferrocement section
- c = distance from extreme compression fiber to neutral axis
- d'' = clear cover of mortar over first layer of mesh
- d_b = diameter or equivalent diameter of reinforcement used
- d_i = distance from extreme compression fiber to centroid of reinforcing layer i
- E_c = elastic modulus of mortar matrix
- E_{cr} = elastic modulus of cracked ferrocement in tension (slope of the stress-strain curve in the cracked elastic state)
- E_r = effective modulus of the reinforcing system
- E_s = elastic modulus of steel reinforcement
- f'_c = specified compressive strength of mortar
- f_{si} = stress in reinforcing layer i
- f_{su} = strength of mesh reinforcement or reinforcing bars
- f_y = yield strength of mesh reinforcement or reinforcing bars
- h = thickness of ferrocement section
- M_n = nominal moment strength
- N = number of layers of mesh; nominal resistance
- N_n = nominal tensile strength
- n_r = modular ratio of reinforcement
- S_r = specific surface of reinforcement
- S_{rl} = specific surface of reinforcement in the longitudinal direction
- S_{rt} = specific surface of reinforcement in the transverse direction
- s = mesh opening or size
- V_f = volume fraction of reinforcement
- V_{fi} = volume fraction of reinforcement for mesh layer i
- V_{fl} = volume fraction of reinforcement in the longitudinal direction
- V_{ft} = volume fraction of reinforcement in the transverse direction
- β_1 = factor defining depth of rectangular stress block
- η = global efficiency factor of embedded reinforcement in resisting tension or tensile bending loads
- η_l = value of η when the load or stress is applied along the longitudinal direction of the mesh system or rod reinforcement
- η_t = value of η when the load or stress is applied along the transverse direction of the mesh reinforcement system or rod reinforcement
- η_θ = value of η when the load or stress is applied along a direction forming an angle θ with the longitudinal direction