



Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane



AS 5337:2019

This Australian Standard® was prepared by EV-010, Acoustics Community Noise. It was approved on behalf of the Council of Standards Australia on 05 April 2019.

This Standard was published on 8 May 2019.

The following are represented on Committee EV-010:

- Association of Australasian Acoustical Consultants
- Australian Acoustical Society
- Austroads
- Bureau of Steel Manufacturers of Australia
- Department of Defence (Australian Government)
- Engineers Australia
- Master Builders Australia
- University of Sydney

This Standard was issued in draft form for comment as DR AS/NZS ISO 3746:2019.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76072 434 4



Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane

First published as AS 5337:2019.

COPYRIGHT

© ISO 2019 — All rights reserved
© Standards Australia Limited 2019

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee EV-010, Acoustics Community Noise.

After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian Standard rather than an Australian/New Zealand Standard.

The objective of this Standard is to specify methods for determining the sound power level or sound energy level of a noise source from sound pressure levels measured on a surface enveloping a noise source (machinery or equipment) in a test environment for which requirements are given. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source with frequency A-weighting applied is calculated using those measurements.

This Standard is identical with, and has been reproduced from, ISO 3746:2010, *Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane*.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text “this International Standard” should read “this Australian Standard”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an ‘informative’ appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	v
Introduction	vi
1 Scope	1
1.1 General.....	1
1.2 Types of noise and noise sources.....	1
1.3 Test environment.....	1
1.4 Measurement uncertainty.....	1
2 Normative references	1
3 Terms and definitions	2
4 Test environment	6
4.1 General.....	6
4.2 Criterion for background noise.....	6
4.3 Criterion for acoustic adequacy of test environment.....	7
5 Instrumentation	7
5.1 General.....	7
5.2 Calibration.....	7
6 Definition, location, installation and operation of noise source under test	7
6.1 General.....	7
6.2 Auxiliary equipment.....	8
6.3 Noise source location.....	8
6.4 Mounting of the noise source.....	8
6.4.1 General.....	8
6.4.2 Hand-held machinery and equipment.....	8
6.4.3 Base-mounted, wall-mounted and tabletop machinery and equipment.....	9
6.5 Operation of source during test.....	9
7 Reference box and measurement surface	9
7.1 Reference box.....	9
7.2 Measurement surface.....	10
7.2.1 General.....	10
7.2.2 Microphone orientation.....	10
7.2.3 Hemispherical measurement surface.....	12
7.2.4 Parallelepiped measurement surface.....	12
8 Determination of sound power levels and sound energy levels	13
8.1 Determination of environmental correction.....	13
8.2 Microphone positions on the measurement surface.....	13
8.2.1 Hemispherical measurement surface.....	13
8.2.2 Parallelepiped measurement surface.....	13
8.2.3 Reduction in the number of microphone positions.....	14
8.3 Determination of sound power levels.....	14
8.3.1 Measurement of sound pressure levels.....	14
8.3.2 Calculation of mean time-averaged sound pressure levels.....	14
8.3.3 Corrections for background noise.....	15
8.3.4 Calculation of surface time-averaged sound pressure level.....	16
8.3.5 Calculation of sound power levels.....	16
8.4 Determination of sound energy levels.....	16
8.4.1 Measurement of single event time-integrated sound pressure levels.....	16
8.4.2 Corrections for background noise.....	16
8.4.3 Calculation of surface single event time-integrated sound pressure levels.....	17
8.4.4 Calculation of sound energy levels.....	18

9	Measurement uncertainty	18
9.1	Methodology	18
9.2	Determination of σ_{omc}	19
9.3	Determination of σ_{R0}	19
9.3.1	General	19
9.3.2	Round robin test	20
9.3.3	Modelling approach for σ_{R0}	20
9.4	Typical upper bound values of σ_{R0}	21
9.5	Total standard deviation σ_{tot} and expanded measurement uncertainty U	21
10	Information to be recorded	21
10.1	General	21
10.2	Noise source under test	22
10.3	Test environment	22
10.4	Instrumentation	22
10.5	Acoustical data	22
11	Test report	23
Annex A	(normative) Determination of the environmental correction	24
Annex B	(normative) Microphone arrays on a hemispherical measurement surface	25
Annex C	(normative) Microphone arrays on a parallelepiped measurement surface	30
Annex D	(informative) Guidelines on the development of information on measurement uncertainty	38
Bibliography	47

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3746 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This third edition cancels and replaces the second edition (ISO 3746:1995), which has been technically revised. It also incorporates the Technical Corrigendum ISO 3746:1995/Cor.1:1995.

Introduction

This International Standard is one of the series ISO 3741[2] to ISO 3747[6], which specify methods for determining the sound power levels and sound energy levels of noise sources including machinery, equipment and their sub-assemblies. Guidelines to select one of those methods are provided in ISO 3740[4]. The selection depends on the environment of the available test facility and on the precision of the sound power level or sound energy level values required. It may be necessary to establish a test code for the individual noise source in order to select the appropriate sound measurement surface and microphone array from among those allowed in each of the ISO 3740[4] to ISO 3747[6] series, and to give requirements for test unit mounting, loading, and operating conditions under which the sound power levels or sound energy levels are to be obtained. The sound power emitted by a given source into the test environment is calculated from the mean square sound pressure that is measured over a hypothetical measurement surface enclosing the source, and the area of that surface. The sound energy for a single machine event is calculated from this sound power and the time over which it existed.

This International Standard specifies methods giving results of ISO 12001:1996, accuracy grade 3 (survey grade) when measurements are performed within industrial buildings or outdoors. Ideally, the test source should be mounted on a sound-reflecting plane located in a large open space. For sources normally installed on the floor of machine rooms, corrections are defined to account for undesired reflections from nearby objects, walls, and the ceiling, and for the residual background noises that occur there.

The methods specified in this International Standard permit the determination of the sound power level and the sound energy level with frequency A-weighting applied.

For applications where greater accuracy is required, reference can be made to ISO 3744, ISO 3745[5] or an appropriate part of ISO 9614[14]-[16]. If the relevant criteria for the measurement environment specified in this International Standard are not met, it might be possible to refer to another of the ISO 3741[2] to ISO 3747[6] series, or to an appropriate part of ISO 9614[14]-[16].

Australian Standard®

Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane

1 Scope

1.1 General

This International Standard specifies methods for determining the sound power level or sound energy level of a noise source from sound pressure levels measured on a surface enveloping a noise source (machinery or equipment) in a test environment for which requirements are given. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source with frequency A-weighting applied is calculated using those measurements.

NOTE Differently shaped measurement surfaces can yield differing estimates of the sound power level of a given noise source and an appropriately drafted test code (see ISO 12001) gives detailed information on the selection of the surface.

1.2 Types of noise and noise sources

The methods specified in this International Standard are suitable for all types of noise (steady, non-steady, fluctuating, isolated bursts of sound energy, etc.) defined in ISO 12001.

This International Standard is applicable to all types and sizes of noise source (e.g. stationary or slowly moving plant, installation, machine, component or sub-assembly), provided the conditions for the measurements can be met.

NOTE The conditions for measurements given in this International Standard can be impracticable for very tall or very long sources such as chimneys, ducts, conveyors, and multi-source industrial plants. A test code for the determination of noise emission of specific sources can provide alternative methods in such cases.

1.3 Test environment

The test environments that are applicable for measurements made in accordance with this International Standard can be located indoors or outdoors, with one or more sound-reflecting planes present on or near which the noise source under test is mounted.

1.4 Measurement uncertainty

Information is given on the uncertainty of the sound power levels and sound energy levels determined in accordance with this International Standard, for measurements made with frequency A-weighting applied. The uncertainty conforms with that of ISO 12001:1996, accuracy grade 3 (survey grade).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3744, *Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Engineering methods for an essentially free field over a reflecting plane*

ISO 5725 (all parts), *Accuracy (trueness and precision) of measurement methods and results*

ISO 12001:1996, *Acoustics — Noise emitted by machinery and equipment — Rules for the drafting and presentation of a noise test code*