



Electroacoustics — Octave-band and fractional-octave-band filters

Part 1: Specifications



AS IEC 61260.1:2019

This Australian Standard® was prepared by EV-010, Acoustics Community Noise. It was approved on behalf of the Council of Standards Australia on 27 February 2019.

This Standard was published on 2 May 2019.

The following are represented on Committee EV-010:

Association of Australian Acoustical Consultants
Australian Acoustical Society
AUSTROADS
Bureau of Steel Manufacturers of Australia
Department of Defence (Australian Government)
Engineers Australia
Master Builders Australia
University of Sydney

This Standard was issued in draft form for comment as DR AS IEC 61260.1:2018.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76072 426 9



Electroacoustics — Octave-band and fractional-octave-band filters

Part 1: Specifications

Originated in Australia as AS Z41—1969.
Originated in New Zealand as NZS 1499:1965.
AS Z41—1969 and NZS 1499:1965 jointly revised, amalgamated and redesignated AS/NZS 4476:1997.
This edition revised in part and redesignated as AS IEC 61260.1:2019.

COPYRIGHT

© IEC 2019 — All rights reserved
© Standards Australia Limited 2019

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee EV-010, Acoustics Community Noise, to supersede AS/NZS 4476:1997, *Acoustics—Octave-band and fractional-octave-band-filters*.

The objective of this Standard is to specify performance requirements for analogue, sampled-data, and digital implementations of band-pass filters. The extent of the pass-band region of a filter's relative attenuation characteristic is a constant percentage of the exact mid-band frequency for all filters of a given bandwidth. An instrument conforming to the requirements of this standard may contain any number of contiguous band-pass filters covering any desired frequency range.

Performance requirements are provided for two filter classes: class 1 and class 2. In general, specifications for class 1 and class 2 filters have the same design goals and differ mainly in the acceptance limits and the range of operational temperature.

Band-pass filters conforming to the performance requirements of this Standard may be part of various measurement systems or may be an integral component of a specific instrument such as a spectrum analyser.

This Standard is identical with, and has been reproduced from, IEC 61260-1:2014, *Electroacoustics — Octave-band and fractional-octave-band filters — Part 1: Specifications*.

As this document has been reproduced from an International Standard, a full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms and definitions	8
4 Reference environmental conditions.....	12
5 Performance requirements.....	12
5.1 General.....	12
5.2 Octave frequency ratio	13
5.3 Reference frequency	13
5.4 Exact mid-band frequencies	13
5.5 Nominal mid-band frequencies.....	13
5.6 Band-edge frequencies.....	14
5.7 Time-averaged signal levels	14
5.8 Filter attenuation	14
5.9 Reference attenuation	15
5.10 Relative attenuation	15
5.11 Normalized effective bandwidth	18
5.12 Effective bandwidth deviation	19
5.13 Linear operating range	19
5.14 Time-invariant operation.....	20
5.15 Anti-alias filters	20
5.16 Summation of output signals.....	21
5.17 Overload indicator	21
5.18 Filter decay time.....	21
5.19 Maximum input signal.....	21
5.20 Output terminals and terminating impedances.....	22
5.21 Power supply check	22
5.22 Sensitivity to various environments.....	22
5.22.1 General.....	22
5.22.2 Ambient air temperature and relative humidity.....	22
5.23 Electrostatic-discharge and electromagnetic-compatibility requirements	22
5.23.1 General.....	22
5.23.2 Electrostatic discharges.....	23
5.23.3 Immunity to power-frequency and radio-frequency fields	23
5.23.4 Emission limits	25
6 Instrument marking.....	25
7 Instruction manual	26
7.1 General.....	26
7.2 Operation.....	26
7.3 Testing.....	27
Annex A (informative) Relationship between tolerance interval, corresponding acceptance interval and the maximum-permitted uncertainty of measurement	28
Annex B (normative) Maximum-permitted expanded uncertainties of measurement	29
Annex C (informative) Examples of conformance assessment to specifications of this standard	30

C.1	General.....	30
C.2	Conformance criteria	30
C.3	Example test results	31
Annex D (informative) Base 2 filters		33
Annex E (normative) Nominal mid-band frequencies		34
E.1	Mid-band frequencies for octave-band and one-third-octave-band filters.....	34
E.2	Mid-band frequencies for one-half-octave-band filters	34
E.3	Mid-band frequencies for other bandwidths	34
Annex F (informative) Normalized frequencies at breakpoints of acceptance limits on minimum and maximum relative attenuation for one-third-octave-band filters.....		36
Annex G (informative) Filter response to exponentially swept sinusoidal signals.....		38
G.1	Exponential frequency sweep	38
G.2	Response of set of band-pass filters to a sweep.....	38
Annex H (informative) Measurement of filter decay time.....		41
H.1	General.....	41
H.2	Measurement of filter decay time	41
H.2.1	Instruments with the capability to measure reverberation time	41
H.2.2	Instruments without the capability to measure reverberation time	41
Bibliography		43
Figure 1 – Minimum and maximum limits on relative attenuation as a function of f/f_m for class 1 and class 2 octave-band filters		17
Figure A.1 – Relationship between tolerance interval, corresponding acceptance interval and the maximum-permitted uncertainty of measurement.....		28
Figure C.1 – Examples of conformance assessment		32
Figure G.1 – Relation between the logarithmic frequency scale and the linear time scale due to the exponential sweep		40
Table 1 – Acceptance limits on relative attenuation for octave-band filters		15
Table 2 – Limits for radiated disturbance of class B Information Technology Equipment (ITE) at a distance of 10 m.....		25
Table 3 – Limits for conducted disturbance to the voltage of a public supply of electric power		25
Table B.1 – Maximum-permitted expanded uncertainties of measurement		29
Table C.1 – Examples of conformance assessment		31
Table E.1 – Mid-band frequencies for octave-band and one-third-octave-band filters in the audio range		35
Table F.1 – Acceptance limits on relative attenuation for one-third-octave-band filters.....		37

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTROACOUSTICS – OCTAVE-BAND AND FRACTIONAL-OCTAVE-BAND FILTERS –

Part 1: Specifications

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61260-1 has been prepared by IEC technical committee 29: Electroacoustics.

This first edition of IEC 61260-1, future IEC 61260-2 and future IEC 61260-3, cancel and replace the first edition of IEC 61260 published in 1995, and Amendment 1:2001. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the IEC 61260:

- a) the single document in the first edition of IEC 61260:1995 is in IEC 61260 series separated into the three parts covering: specifications, pattern evaluation tests and periodic tests;
- b) the IEC 61260:1995 specified three performance categories: classes 0, 1 and 2. The IEC 61260 series specifies requirements for class 1 and 2;
- c) in the IEC 61260:1995, the design goals for the specification can be based on base-2 or base 10 design. In IEC 61260 series only base-10 is specified;

- d) the reference environmental conditions have been changed from 20 °C / 65 % RH to 23 °C / 50 % RH;
- e) IEC 61260:1995 specified tolerance limits without considering the uncertainty of measurement for verification of the specifications. IEC 61260 series specifies acceptance limits for the observed values and maximum-permitted uncertainty of measurements for laboratories testing conformance to specifications in the standard.

The text of this standard is based on the following documents:

FDIS	Report on voting
29/835/FDIS	29/839/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 61260 series, published under the general title *Electroacoustics – Octave-band and fractional-octave-band filters* can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

IEC 61260:1995 and its Amendment 1:2001 are now separated into the following three parts of IEC 61260 series:

- Part 1: Specifications
- Part 2: Pattern evaluation tests (under consideration)
- Part 3: Periodic tests (under consideration)

For assessments of conformance to performance specifications, IEC 61260-1 uses different criteria than were used for the IEC 61260:1995 edition.

IEC 61260:1995 did not provide any requirements or recommendations to account for the uncertainty of measurement in assessments of conformance to specifications. This absence of requirements or recommendations to account for uncertainty of measurement created ambiguity in determinations of conformance to specifications for situations where a measured deviation from a design goal was close to a limit of the allowed deviation. If conformance was determined based on whether a measured deviation did or did not exceed the limits, the end-user of the octave-band and fractional-octave-band filters incurred the risk that the true deviation from a design goal exceeded the limits.

To remove this ambiguity, IEC Technical Committee 29, at its meeting in 1996, adopted a policy to account for measurement uncertainty in assessments of conformance in International Standards that it prepares.

This first edition of IEC 61260-1 uses an amended criterion for assessing conformance to a specification. Conformance is demonstrated when (a) measured deviations from design goals do not exceed the applicable *acceptance limits* and (b) the uncertainty of measurement does not exceed the corresponding maximum-permitted uncertainty. Acceptance limits are analogous to the tolerance limits allowances for design and manufacturing implied in the IEC 61260:1995.

Actual and maximum-permitted uncertainties of measurement are determined for a coverage probability of 95 %. Unless more-specific information is available, the evaluation of the contribution of a specific filter or filter set to a total measurement uncertainty can be based on the acceptance limits and maximum-permitted uncertainties specified in this standard.

ELECTROACOUSTICS – OCTAVE-BAND AND FRACTIONAL-OCTAVE-BAND FILTERS –

Part 1: Specifications

1 Scope

1.1 This part of the IEC 61260 series specifies performance requirements for analogue, sampled-data, and digital implementations of band-pass filters. The extent of the pass-band region of a filter's relative attenuation characteristic is a constant percentage of the exact mid-band frequency for all filters of a given bandwidth. An instrument conforming to the requirements of this standard may contain any number of contiguous band-pass filters covering any desired frequency range.

1.2 Performance requirements are provided for two filter classes: class 1 and class 2. In general, specifications for class 1 and class 2 filters have the same design goals and differ mainly in the acceptance limits and the range of operational temperature. Acceptance limits for class 2 are greater than, or equal to, those for class 1. Maximum-permitted expanded uncertainties of measurement are also specified.

1.3 Performance requirements are given for designs where the octave frequency ratio and the mid-band frequencies are powers of ten.

1.4 Band-pass filters conforming to the performance requirements of this standard may be part of various measurement systems or may be an integral component of a specific instrument such as a spectrum analyser.

1.5 This standard specifies the ranges of environmental conditions for operation of the filters. The required range depends on whether the instrument containing the filters is designed to be operated in a controlled environment or more generally in the field.

1.6 Band-pass filters conforming to the requirements of this standard are capable of providing frequency-band-filtered spectral information for a wide variety of signals, for example, time-varying, intermittent or steady; broadband or discrete frequency; and long or short durations.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61000-4-2, *Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test*

IEC 61000-4-3:2006, *Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test*

IEC 61000-6-1:2005, *Electromagnetic compatibility (EMC) – Part 6-1: Generic standards – Immunity for residential, commercial and light-industrial environments*