

Australian Standard™

**Sampling procedures for inspection by
attributes**

**Part 2: Sampling plans indexed by
limiting quality (LQ) for isolated lot
inspection**

This Australian Standard was prepared by Committee QR-008, Quality Systems. It was approved on behalf of the Council of Standards Australia on 26 May 2003 and published on 28 July 2003.

The following are represented on Committee QR-008:

Australian Chamber of Commerce and Industry
Australian Industry Group
Australian Information Industry Association
Australian Institute of Petroleum
Australian Organisation for Quality
Bureau of Steel Manufacturers of Australia
Certification Bodies (Australia)
Commonwealth Department of Transport and Regional Services
Department of Agriculture, Fisheries and Forestry (Commonwealth)
Department of Defence (Australia)
Department of Industry Science and Resources (Commonwealth)
Federal Chamber of Automotive Industries
Institute of Materials Engineering Australasia
Institution of Engineers Australia
Main Roads Department, Queensland
Master Builders Australia
Quality Society of Australasia
Royal Australian Chemical Institute

Additional interests participating in the preparation of this Standard:

Australian Quality Council
CSIRO Mathematical and Information Services
Macquarie University
National Association of Testing Authorities Australia
Queensland University of Technology

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

**Sampling procedures for inspection by
attributes**

**Part 2: Sampling plans indexed by
limiting quality (LQ) for isolated lot
inspection**

First published as AS 1199.2—2003.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5390 6

PREFACE

This Standard was prepared by the Standards Australia Committee QR-008, Quality Systems.

This Standard is identical with, and has been reproduced from ISO 2859-2:1985, *Sampling procedures for inspection by attributes, Part 2: Sampling plans indexed by limiting quality (LQ) for isolated lot inspection*.

The objective of this Standard is to establish LQ sampling plans and procedures for inspection by attributes compatible with ISO 2859-1 that can be used when the switching rules given in ISO 2859-1 are not applied, when lots are of an isolated nature.

As this Standard is reproduced from an international Standard, the following applies:

- (a) Its number appears on the cover and title page while the international Standard number appears only on the cover.
- (b) A full point substitutes for a comma when referring to a decimal marker.

The International Organization for Standardization's Committee TC 69 is currently in the process of updating the ISO 2859 series to bring the older documents into line with Parts 1 and 4. Where any inconsistency arises between the sections of this series of Standards, the more recently published document will apply.

CONTENTS

0	Introduction	1
1	Scope and field of application	2
2	Definitions	2
3	Choice of sampling plan	2
4	Rules for acceptance and non-acceptance	3
5	Double and multiple sampling plans	4
6	Examples illustrating how to use this part of ISO 2859	4
7	Compatibility with ISO 2859/1	4
	Tables	5 to 21

AUSTRALIAN STANDARD

Sampling procedures for inspection by attributes — Part 2: Sampling plans indexed by limiting quality (LQ) for isolated lot inspection

0 Introduction

0.1 General

ISO 2859 comprises four parts:

Part 0: General introduction.

Part 1: Sampling plans indexed by acceptable quality level (AQL) for lot-by-lot inspection.

Part 2: Sampling plans indexed by limiting quality (LQ) for isolated lot inspection.

Part 3: Skip lot sampling plan.

ISO 2859/1 sampling plans, indexed in terms of AQL, which is defined as a process average, were primarily designed for the assessment of a continuing series of lots. This enables switching rules to be employed which not only give protection to the consumer (by the switch to tightened inspection and discontinuation where necessary) but also provide an incentive to the producer (by the switch to reduced inspection) with a reduction to test and inspection costs (when consistently good quality is achieved). However, there is little doubt that in many industrial situations today the switching rules are not applied for a variety of reasons or excuses, not all of which may be valid:

- a) individual ISO 2859/1 plans are used alone but "AQL" protection is still claimed or AQL re-defined, to suit "so-called unique products";
- b) "our industry... product is special so ISO 2859/1 standard plans need not apply to us";
- c) production is intermittent (not continuous);
- d) production is from several different sources in varying quantities, i.e. "job lots";
- e) purchases are from stock-holders — no source data available;
- f) lots are "small" (use of hypergeometric distribution required);
- g) lots are "isolated";
- h) lots are re-submitted after initial rejection.

Consequently, in certain of the above cases consumer protection may need to be attained or measured by other methods. This part of ISO 2859 uses the limiting quality to measure consumer protection. It should be remembered, however, that prior information on the supplier's quality assurance system and its effectiveness may play a major part in deciding whether or not to accept a single lot.

0.2 Objectives

In an attempt to reconcile the somewhat diverse requests for assistance made over the past few years by committees of international standardizing bodies representing various product sectors, this part of ISO 2859 was drawn up in accordance with the following principles:

- a) the new LQ plans can be easily integrated with the existing AQL plans in ISO 2859/1;
- b) the LQ indexing uses a preferred series of values that cannot be confused with the preferred series of AQL values;
- c) the five basic numbers associated with a single sampling plan, i.e. lot size, sample size, acceptance number, AQL (or quality accepted with probability 0,95) and LQ, appear in the same table, whenever possible.

0.3 Summary

The problems associated with acceptance sampling inspection involve defining unambiguously the criteria used to judge discrete individual items supplied in quantity, the quality level expected from the manufacturing process, the discrimination offered by the plans and the procedure to be followed when a lot is not accepted. Above all, however, it is necessary to design the sampling scheme so that it may easily be invoked in a purchasing contract. The plans in this part of ISO 2859 make maximum use of the established plans given in ISO 2859/1, so that sub-clause 12.6 of ISO 2859/1 (see 1.1) can be made directly operational, by providing a rationalized series of plans indexed in terms of limiting quality (LQ).