

Australian/New Zealand Standard™

Traffic signal lanterns



Standards Australia



STANDARDS
NEW ZEALAND
Paerewa Aotearoa

AS/NZS 2144:2002

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee LG-006, Road Traffic Signals. It was approved on behalf of the Council of Standards Australia on 25 March 2002 and on behalf of the Council of Standards New Zealand on 14 March 2002. It was published on 2 May 2002.

The following interests are represented on Committee LG-006:

ARRB Transport Research
Australian Electrical and Electronic Manufacturers Association
Australian Industry Group
AUSTROADS
Brisbane City Council
Road and Traffic Authority of N.S.W.
Transport SA
VicRoads
Local Government of New Zealand

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Australia web site at www.standards.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia International or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

Traffic signal lanterns

Originated as AS E32-1947.
Previous edition AS 2144—1995.
Jointly revised and designated AS/NZS 2144:2002.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 4494 X

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee LG-006 Road Traffic Signals to supersede AS 2144—1995. It is one of a number of Standards which set out requirements for the equipment associated with traffic signal installations. These include the following:

AS	
2339	Traffic signal posts and attachments
2353	Pedestrian push-button assemblies
2578	Traffic signal controllers
2578.1	Part 1: Physical and electrical compatibility
2703	Vehicle loop detector sensors
2979	Traffic signal mast arms
4113	Traffic signal lamps
4113.1	Part 1: Lamps for 240 V a.c. operation
4113.2	Part 2: Lamps for a.c. operation at extra-low voltage
4191	Portable traffic signal systems
AS/NZS	
2144	Traffic signal lanterns (this Standard)
4192	Illuminated flashing arrow signs

The Standard includes requirements for the dimensions of certain features of traffic signal lanterns and associated components, arising from a specific desire on the part of road and traffic authorities for uniformity in the appearance of traffic signalling equipment to road users, and from the need to facilitate the compatibility of equipment from different manufacturers. In particular, Appendix F gives recommended dimensions for the attachment of visors and target boards which have the objective of achieving interchangeability between components supplied by different manufacturers.

The requirements have the objective of ensuring that, with the exception of replaceable items such as lamps and LED arrays, lanterns will continue to function effectively for a period of at least 20 years; furthermore, that surface finishes applied to the exterior of lanterns (e.g. powder coatings, paint) will last for at least 10 years without the need for further treatment.

The photometric requirements for vehicular lanterns have been derived from the considerable body of research which has been conducted in Australia into factors affecting the visibility of these signals (see references in Appendix C).

The photometric requirements apply to new lanterns. In service the photometric performance will deteriorate, sometimes appreciably. Therefore to ensure that the lanterns continue to perform at a satisfactory level a maintenance program will be necessary.

It is recommended that the tests necessary to determine compliance with this Standard be conducted by laboratories that are independently accredited as having competence to carry out the type of measurements involved.

A number of changes have been introduced in this edition, all with the objective of enlarging the scope of the Standard to cover traffic signals using light emitting diodes (LEDs) as the light source.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	5
1.2 REFERENCED DOCUMENTS.....	5
1.3 DEFINITIONS.....	5
1.4 MARKING	8
SECTION 2 SIGNAL COLOURS AND DISPLAYS	
2.1 SIGNAL COLOURS	9
2.2 SIGNAL DISPLAYS.....	9
SECTION 3 PHOTOMETRIC PERFORMANCE	
3.1 GENERAL.....	11
3.2 APPEARANCE OF VEHICULAR ASPECTS WITH A CIRCULAR DISPLAY.....	11
3.3 INTENSITY DISTRIBUTION OF VEHICULAR ASPECTS WITH A CIRCULAR DISPLAY	11
3.4 APPEARANCE OF VEHICULAR ASPECTS WITH A SYMBOLIC DISPLAY	15
3.5 LUMINANCE DISTRIBUTION OF VEHICULAR ASPECTS WITH A SYMBOLIC DISPLAY	16
3.6 APPEARANCE OF PEDESTRIAN AND BICYCLE SYMBOL ASPECTS	17
3.7 LUMINANCE DISTRIBUTION OF PEDESTRIAN AND BICYCLE SYMBOL ASPECTS.....	18
3.8 VEILING REFLECTIONS.....	19
3.9 SUN-PHANTOM	20
SECTION 4 MECHANICAL AND PHYSICAL FEATURES AND PROPERTIES	
4.1 GENERAL ARRANGEMENT	21
4.2 MASS OF LANTERN ASPECTS.....	24
4.3 SEALING OF OPTICAL SYSTEM	24
4.4 MATERIALS AND METHODS OF CONSTRUCTION.....	25
4.5 SURFACE FINISH.....	25
4.6 WEATHER RESISTANCE	25
4.7 OPERATING TEMPERATURES	26
SECTION 5 ELECTRICAL REQUIREMENTS	
5.1 ALL TECHNOLOGIES.....	27
5.2 FURTHER REQUIREMENTS FOR LED ASPECTS	28
SECTION 6 OPERATIONAL REQUIREMENTS—LED ASPECTS	
6.1 GENERAL.....	31
6.2 LIGHT OUTPUT STATES.....	31
6.3 SIGNAL SWITCHING RESPONSE TIMES.....	32
6.4 PROGRESSIVE FAILURE OF LEDs	32
6.5 DIMMING OF ASPECTS	32
6.6 OFF OUTPUT	32

SECTION 7 OPTICAL SYSTEM COMPONENTS AND ANCILLARY DEVICES

7.1	ASSEMBLY OF OPTICAL SYSTEM	33
7.2	PROPERTIES OF OPTICAL COMPONENTS	33
7.3	REFLECTORS	33
7.4	LED ARRAYS	33
7.5	LAMP HOLDERS	34
7.6	INCANDESCENT LAMPS	34
7.7	SYMBOLIC DISPLAYS	34
7.8	VISORS AND LOUVRES.....	36
7.9	TARGET BOARDS (FOR VEHICULAR LANTERNS).....	36
7.10	ANTI-SUN-PHANTOM DEVICES.....	36

APPENDICES

A	INFORMATION TO BE SUPPLIED WITH INQUIRY OR ORDER	44
B	LIST OF REFERENCED DOCUMENTS	45
C	REFERENCES	47
D	TEST CONDITIONS AND PROCEDURES FOR PHOTOMETRIC AND COLORIMETRIC MEASUREMENTS	48
E	DERIVATION OF INITIAL LED ASPECT INTENSITIES	58
F	RECOMMENDED DIMENSIONS FOR VISORS AND TARGET BOARDS.....	60
G	RECOMMENDATIONS FOR PEDESTRIAN AND BICYCLE SYMBOLIC DISPLAYS USING UNDIFFUSED LEDs.	65
H	RECOMMENDED TEST PROCEDURE FOR DETERMINING THE TEMPERATURE RISE OF COMPONENTS	67

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard Traffic signal lanterns

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies requirements for the design, construction and performance of traffic signal lanterns that use either incandescent, or light emitting diode (LED) light sources and are intended to control the movement of vehicles, including bicycles, and pedestrians. It does not apply to the control equipment that may be necessary for the functioning of the lanterns.

For vehicular lanterns, two basic levels of performance are specified, namely, for general purpose lanterns and for extended range lanterns. Requirements are also specified for a variety of special purpose lanterns.

NOTES:

- 1 Requirements for the use of traffic signal lanterns in the control of vehicular and pedestrian traffic are set out in the AS 1742 series.
- 2 See Appendix A for the information which should be supplied with an inquiry or order for traffic signal lanterns to this Standard.

1.2 REFERENCED DOCUMENTS

The Standards referred to in this document are listed in Appendix B.

NOTE: See Appendix C for bibliographical details of other sources of information.

1.3 DEFINITIONS

For the purpose of this Standard, the definitions below apply.

NOTE: Definitions of lighting quantities are of the simplified form given in AS 3665, which are intended to convey a basic understanding of the concepts involved. For the more precise primary definitions of these terms reference should be made to AS 1852.845.

1.3.1 Aspect

A single optical system of a traffic signal lantern, capable of being illuminated at any given time.

1.3.2 Beam axis (for vehicular lanterns)

A straight line passing through the geometric centre of the lens in the direction of maximum intensity of the light emitted by the lantern, as determined in accordance with Paragraph D3.1 of Appendix D.

1.3.3 Bicycle lantern

A lantern which is intended for the control of bicycle traffic.

1.3.4 Chromaticity

A term referring to colour quality expressed numerically.