

AS 2641—1983

Australian Standard[®]

**VIBRATION AND SHOCK—
BALANCING—VOCABULARY**

This Australian standard was prepared by Committee ME/41, Vibration and Shock. It was approved on behalf of the Council of the Standards Association of Australia on 20 May 1983 and published on 8 August 1983.

The following interests are represented on Committee ME/41:

Association of Consulting Engineers Australia
Australian Gas Association
Australian Mining Industry Council
Australian Shipbuilders Association
Confederation of Australian Industry
Construction Equipment Importers and Manufacturers of Australia
CSIRO, National Measurement Laboratory
Department of Defence
Department of Defence Support
Department of Industrial Relations, N.S.W.
Department of Science and Technology
Federation of Automotive Products Manufacturers
Institute of Quarrying
Institution of Mechanical Engineers
Metropolitan Water Sewerage and Drainage Board, N.S.W.
Monash University
National Association of Testing Authorities Australia
New South Wales Institute of Technology
University of Melbourne
University of Newcastle
University of New South Wales
University of Queensland

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 82142.

Australian Standard[®]

**VIBRATION AND SHOCK—
BALANCING—VOCABULARY**

First published 1983

PREFACE

This standard was prepared by a subcommittee of the Association's Committee on Vibration and Shock as one of a series relating to mechanical vibration and shock. It is based on, and is substantially in agreement with, the corresponding International Standard ISO 1925, Balancing – Vocabulary.

The aim of the standard is to provide a common language for persons working in the field of mechanical vibration and shock, with a view to eliminating ambiguities and misunderstandings.

Except as indicated in this preface, the entries in this standard are identical with those of ISO 1925.

A very few of the definitions in ISO 1925 have been altered in meaning where this was considered to be essential in order to conform to accepted Australian usage.

A few of the definitions common to acoustics have been presented in a different form, using the definitions already available in AS 1633.

In the preparation of this vocabulary, reference was made to the following standards:

AS 1633	Glossary of Acoustic Terms
AS 2606	Vibration and Shock – Vocabulary
ISO 1925	Balancing – Vocabulary

The following standards are referred to in this standard:

ISO 1940	Balance Quality of Roating Rigid Bodies
ISO 2953	Balancing Machines – Description and Evaluation

CONTENTS

	<i>Page</i>
SECTION 1. MECHANICS	3
SECTION 2. ROTORS	4
SECTION 3. UNBALANCE	5
SECTION 4. BALANCING	6
SECTION 5. BALANCING MACHINES AND EQUIPMENT	7
SECTION 6. FLEXIBLE ROTORS	10
SECTION 7. ROTATING RIGID FREE BODIES	11
INDEX	12

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard

for

VIBRATION AND SHOCK — BALANCING — VOCABULARY

SECTION 1. MECHANICS

<i>No</i>	<i>Term</i>	<i>Definition</i>
1.001	centre of gravity	Point in a body through which passes the resultant of the weights of its component particles for all orientations of the body with respect to a uniform gravitational field.
1.002	principal axis of inertia	<p>For each set of Cartesian coordinates at a given point, the values of the six moments of inertia of a body $I_{x_i x_j}$ ($i, j = 1, 2, 3$) are in general unequal; for one such coordinate system the moments $I_{x_i x_j}$ ($i \neq j$) vanish. The values of $I_{x_i x_j}$ ($i = j$) for this particular coordinate system are called the principal moments of inertia and the corresponding coordinate directions are called the principal axes of inertia.</p> <p>NOTES:</p> <ol style="list-style-type: none"> 1. $I_{x_i x_j} = \int x_i x_j \, dm$ for $i \neq j$ $I_{x_i x_j} = \int (r^2 - x_i^2) \, dm$ for $i = j$ where $r^2 = x_1^2 + x_2^2 + x_3^2$ and x_i and x_j are Cartesian coordinates. 2. If the point is the centre of gravity of the body, the axes and moments are called central principal axes and central principal moments of inertia. 3. In balancing, the term 'principal inertia axis' is used to designate the one central principal axis (of the three such axes) most nearly coincident with the shaft axis of the rotor and is sometimes referred to as the 'balance axis' or the 'mass axis'. 4. The mass properties of a rigid body are the following scalar quantities: <ol style="list-style-type: none"> (a) Mass. (b) Centre of gravity location (three coordinates). (c) Moments of inertia (three axes). (d) Products of inertia (three pairs of axes).
1.003	equilibrium centre	The point at which the shaft axis (<i>see shaft axis</i> 2.007) intersects the plane perpendicular to the shaft axis through the centre of gravity of a rotor, when the rotor is at a standstill.
1.004	critical speed	A characteristic speed at which resonances of a system are excited.
		<p>NOTES:</p> <ol style="list-style-type: none"> 1. Critical speed of a rotating system is a speed of the rotating system that corresponds to a resonance frequency (it may also include multiples and submultiples of the resonance frequency) of the system, e.g. a critical speed will be reached when the rotational speed in revolution per second equals the resonant frequency in hertz. 2. Where there are several rotating systems, there will be several corresponding sets of critical speeds, one for each mode of the overall system. 3. Depending on the relative magnitudes of the bearing stiffness and mass and the rotor stiffness and mass, the significant effect at a critical speed may be motion of the journals or flexure of the rotor (<i>see flexural critical speed</i> 6.001 and <i>rigid-rotor-mode critical speed</i> 6.002).
1.005	axis of rotation (spin axis)	The line about which a body rotates.
		<p>NOTES:</p> <ol style="list-style-type: none"> 1. If the bearings are anisotropic, there is no stationary axis of rotation. 2. For rigid bearings, the axis of rotation is the shaft axis, but if the bearings are not rigid, the axis of rotation is not necessarily the shaft axis.