

Australian Standard[®]

**Measurement of water flow in open
channels**

**Part 4.6: Measurement using flow
gauging structures—Flat-V weirs**



This Australian Standard® was prepared by Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 5 April 2007.
This Standard was published on 6 August 2007.

The following are represented on Committee CE-024:

- Australian Industry Group
 - Australian National Committee on Irrigation and Drainage
 - Department of Environment and Water Resources
 - Institute of Instrumentation, Control and Automation Australia
 - Irrigation Association of Australia
 - National Measurement Institute
 - Plumbing Products Industry Group
 - University of New South Wales
 - University of South Australia
 - Water Services Association of Australia
-

This Standard was issued in draft form for comment as DR 07110.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting **www.standards.org.au**

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at **mail@standards.org.au**, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

**Measurement of water flow in open
channels**

**Part 4.6: Measurement using flow
gauging structures—Flat-V weirs**

Originated as AS 3778.4.6—1991.
Second edition 2007

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia
ISBN 0 7337 8313 9

PREFACE

This Standard was prepared by the Standards Australia Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits, to supersede AS 3778.4.6—1991.

The objective of this Standard is to specify methods for measuring discharge in large rivers and estuaries by the moving-boat technique.

This Standard is identical to and reproduced from ISO 4377:2002, *Hydrometric determinations—Flow measurement in open channels using structures—Flat-V weirs*.

As this Standard is reproduced from an international standard, the following applies:

- (a) Its number appears on the cover and title page while the international standard number appears only on the cover.
- (b) In the source text 'ISO 4377' should read 'AS 3778.4.6'.
- (c) A full point substitutes for a comma when referring to a decimal marker.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the annex to which they apply. A 'normative' is an integral part of a Standard, whereas an 'informative' annex is only for information and guidance.

CONTENTS

	<i>Page</i>
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	3
5 Characteristics of flat-V weirs	4
6 Installation	4
7 Maintenance	7
8 Measurement of head(s)	8
9 Discharge relationships	12
10 Computation of discharge	25
11 Uncertainties in flow measurement	27
12 Examples	30
 Annex	
A Velocity distribution.....	35

Australian Standard**Measurement of water flow in open channels**
Part 4.6: Measurement using flow gauging structures—Flat-V weirs

1 Scope

This International Standard describes the methods of measurement of flow in rivers and artificial channels under steady or slowly varying conditions using flat-V weirs (see Figure 1).

Annex A gives guidance on acceptable velocity distribution.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 772, *Hydrometric determinations — Vocabulary and symbols*

ISO/TR 5168, *Measurement of fluid flow — Evaluation of uncertainties*

Guide to the expression of uncertainty in measurement (GUM), BIPM, IEC, IFCC, ISO, IUPAC, INPAP and OIML

3 Terms and definitions

For the purposes of this International Standard, the terms and definitions given in ISO 772 apply.