

Australian Standard™

**Environmental testing
Part 3.1: Background information—
Section one: Cold and
dry heat tests**

This Australian Standard was prepared by Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic equipment. It was approved on behalf of the Council of Standards Australia on 14 February 2003 and published on 15 April 2003.

The following are represented on Committee EL-026:

Australian Chamber of Commerce and Industry
Australian Electrical and Electronic Manufacturers Association
Electrical Compliance Testing Authorities
Electrical Regulatory Authorities Council
Electricity Supply Association of Australia
Testing Interests (Australia)

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

**Environmental testing
Part 3.1: Background information—
Section one: Cold and
dry heat tests**

Originated as AS 1099.3.1—1980.
Revised and redesignated as AS 60068.3.1—2003.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5087 7

PREFACE

This Standard was prepared by the Standards Australia Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic equipment to supersede AS 1099.3.1—1980, *Basic environmental testing procedures for electrotechnology Part 3: Background information—Section 1: Tests A and B—Cold and dry heat tests*.

The objective of this Standard is to provide the electrotechnology industry with a complete set of environmental test procedures published as a series under AS 60068 *Environmental testing*.

This Standard is Part 3.1 of that series.

This Standard is identical with, and has been reproduced, from IEC 60068-3-1:1974, *Environmental testing – Part 3: Background information – Section One: Cold and dry heat tests*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (b) In the source text ‘this international standard’ should read ‘this Australian Standard’.
- (c) A full point should be substituted for a comma when referring to a decimal marker.
- (d) Any French text on figures should be ignored.

In this Standard, the following print types are used:

- requirements proper: in arial type;
- *test specifications: in italic type;*
- explanatory matter: in smaller arial type.

Any international Standard referenced should be replaced by an equivalent Australian Standard when one is available. The availability of equivalent Australian Standards can be determined either from the Standards Australia catalogue or from the Standards Australia website (www.standards.com.au).

CONTENTS

	<i>Page</i>
1 Introduction	1
1.1 Reference ambient conditions.....	1
1.2 Devices without heat dissipation.....	1
1.3 Devices with heat dissipation.....	1
1.4 Ambient temperature	2
1.5 Surface temperatures	2
2 Reasons for the differing test procedures.....	2
2.1 Mechanisms of heat transfer.....	2
2.1.1 Convection.....	2
2.1.2 Thermal radiation.....	3
2.1.3 Thermal conduction	4
2.1.4 Forced air circulation	4
3 Test chambers	5
3.1 General	5
3.2 Methods of achieving the required conditions in the test chamber.....	6
3.2.1 Design of chambers for simulating the effect of free air condition.....	6
3.2.2 Design of chambers with forced air circulation	6
3.2.3 Emissivity coefficient of walls.....	7
3.2.4 Thermal characteristics of mounting devices.....	7
4 Measurements	7
4.1 Temperature.....	7
4.2 Air velocity.....	7
4.3 Emissivity coefficient	7
Annex A Effects of size of chamber on surface temperature of a specimen when no forced air circulation is used	8
Annex B Effect of airflow on chamber conditions and on surface temperatures of test specimens	10
Annex C Effect of specimen emissivity coefficient on temperature rise	14
Annex D Effect of wire termination dimensions and material on surface temperature of a component.....	15
Annex E Heat transfer calculations and nomograms.....	16
Annex F Thermal conductivities of common materials	23
Annex G Measurement of temperature	24
Annex H Measurement of air velocity	26
Annex J Measurement of emissivity coefficient.....	27
Annex K General block diagram, cold and dry heat tests	35

Figure 1 – Heat dissipation per unit surface area of the test specimen at which the deviation between the surface temperature of the specimen in a very large chamber and in a smaller chamber reaches 5 °C	9
Figure 2 – Experimental data on the effect of airflow on surface temperature of a wirewound resistor – Radial airflow	11
Figure 3 – Experimental data on the effect of airflow on surface temperature of a wirewound resistor – Axial airflow	12
Figure 4 – Temperature distribution on a cylinder with homogeneous heat generation in airflow of velocities 0,5, 1 and 2 m.s ⁻¹	13
Figure 5 – Comparison of the temperature rise as a function of heat dissipation for thermal white and thermal black specimens subjected to an ambient temperature of 70 °C in a chamber with thermal black walls (experimental values)	14
Figure 6	15
Figure 7 – Relationship between the surface temperature T_s of the specimen and the heat-dissipated P per unit time at the ambient temperature T_a	19
Figure 8 – Nomogram for evaluation of surface temperatures of the specimen T_s at different ambient temperatures T_a . Average specimen dimensions $a = 0,2$ m, emissivity coefficient of the specimen $\varepsilon_2 = 0,7$	20
Figure 9 – Nomogram for evaluation of surface temperatures of the specimen T_s at different ambient temperatures T_a . Average specimen dimensions $a = 0,05$ m, emissivity coefficient of the specimen $\varepsilon_2 = 0,7$	21
Figure 10 – Relation between overtemperature and emissivity coefficient ε_2 of the specimen.....	22
Figure 11 – Wien's displacement law.....	33
Figure 12 – Relation between $\frac{M_0 \dots \lambda}{M_s}$ and $\lambda \cdot T$	34

STANDARDS AUSTRALIA

Australian Standard**Environmental testing****Part 3.1: Background information—Section one: Cold and dry heat tests**

1 Introduction

The performance of components and equipments is influenced and limited by their internal temperatures which depend on the external ambient conditions and on the heat generated within the device itself.

Whenever temperature gradients exist in the system formed by a device and its surroundings, a process of heat transfer will ensue.

The tests cover cold and dry heat testing, with both sudden and gradual change of the temperature, and of non-heat-dissipating and heat-dissipating specimens (the latter with or without artificial cooling).

The use of test chambers with and without forced air circulation is covered as appropriate. A general block diagram of the total procedure is given in annex K.

1.1 Reference ambient conditions

Unfortunately, the actual ambient conditions in which the device will have to work are normally neither accurately known nor well defined, so that it is not possible to use them as a basis for design, specification or testing.

For these purposes, it is necessary to define conventional reference ambient conditions which may be specified taking into account the following considerations.

1.2 Devices without heat dissipation

If the ambient temperature is uniform and constant and there is no generation of heat within the device, heat will flow from the ambient atmosphere into the device if the former is at a higher temperature, and from the device into the ambient atmosphere if the latter is at a lower temperature. This heat transfer will continue until the device has reached in all its parts the temperature of the surrounding atmosphere. From that moment on, the heat transfer ceases and will not start again unless the ambient temperature changes. In this case, the definition of a reference ambient temperature is simple, the only condition being that it shall be uniformly distributed and constant. For the case when the device does not reach the temperature of the surrounding atmosphere, the definition of a reference temperature is more complicated and the conclusions in 1.3 apply.

1.3 Devices with heat dissipation

If heat were generated within the device and there were no heat transfer to the ambient atmosphere, the temperature of the device would rise beyond any limit. It follows that if an ultimate steady temperature is reached, this implies that heat is flowing continuously from the device into the atmosphere whereby the device is always cooled, no matter what the ambient atmosphere is. Only if the ambient temperature rises, a further rise of temperature within the device may occur.