

Australian Standard™

Serially produced pressure vessels



S t a n d a r d s Australia

This Australian Standard was prepared by Committee ME-001, Pressure Equipment. It was approved on behalf of the Council of Standards Australia on 15 February 2002 and published on 11 March 2002.

The following interests are represented on Committee ME-001:

A.C.T. WorkCover
Australasian Institute of Engineer Surveyors
Australian Aluminium Council
Australian Building Codes Board
Australian Chamber of Commerce and Industry
Australian Industry Group
Australian Institute of Energy
Australian Institute of Petroleum
Australian Liquefied Petroleum Gas Association
Boiler and Pressure Vessel Manufacturers Association of Australia
Bureau of Steel Manufacturers of Australia
Department for Administrative and Information Services, S.A.
Department of Industrial Relations, Qld
Department of Infrastructure, Energy and Resources, Tas.
Department of Labour, New Zealand
Electricity Engineers Association, New Zealand
Electricity Supply Association of Australia
Institute of Materials Engineering Australasia Limited
Institution of Engineers Australia
Institution of Professional Engineers New Zealand
National Association of Testing Authorities Australia
New Zealand Engineering Federation
New Zealand Heavy Engineering Research Association
New Zealand Institute of Welding
New Zealand Petrochemical Users Group
Victorian WorkCover Authority
Welding Technology Institute of Australia
WorkCover New South Wales
Department of Consumer and Employment Protection, WorkSafe Division (W.A.)

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

Serially produced pressure vessels

Originated as AS 2971—1987.
Second edition 2002.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 4365 X

PREFACE

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee ME-001, Pressure Equipment to supersede AS 2971—1987, *Serially produced pressure vessels*. After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian Standard rather than an Australian/New Zealand Standard.

This Standard covers a wide range of small, usually low-hazard, pressure vessels whose design and construction are based on satisfactory burst and other performance tests of a significant number of representative samples. The main types of vessels falling into this group are small, serially produced refrigeration type vessels, air brake reservoirs, drink dispensers, and consumer items such as pressurized fire extinguisher bodies not covered by other Australian Standards, and beer kegs.

Almost invariably these types of vessels do not comply with AS 1210, *Pressure vessels*, which has been prepared primarily for one-off vessels where the design is based on proven formulas, and construction is based on proven materials, fabrication procedures, personnel, and tests which are predominantly non-destructive. AS 1210 does permit burst testing as a basis for acceptance of design of parts or vessels, but only when they cannot be calculated. Thus, there is a need to cover this alternative method of producing safe vessels where it is frequently equally sound and more economic to use burst and other performance tests to validate design, materials, and fabrication, all simultaneously.

The main changes in this revision include the following:

- (a) An increase in limits on contained energy.
- (b) The introduction of a two-tiered concept for vessels which distinguishes between vessels with a simple shape and design and those with a more complicated shape, higher design strength and incapable of simple analysis.
- (c) A new appendix introducing the concept of an Integrated Pressure Equipment Test Station (IPETS).
- (d) Alignment with Standardization Guide No. 17.1, *Drafting of Standards that may be referenced under occupational health and safety legislation*.

From 1995, there has been, and will continue to be, a phasing out of State and Territory regulatory authorities approving pressure vessel design and testing and a phasing in of competent bodies or persons to undertake this task. This Standard introduces a new concept of a pressure equipment test station, integral to the manufacturing process which will carry out these tasks.

The economy and proven safety record of this alternative approach, which essentially results in the specification of 'performance' type requirements was recognized during the revision of this Standard as was the need for consistency with the principles of AS 1210.

This Standard has been prepared to —

- (i) avoid possible confusion between the various classes of AS 1210 vessels and the four classes of serially produced vessels; and
- (ii) permit coverage of non-metallic vessels or pressure parts, e.g. plastic covers on cream dispensers or rubber protectors for thin bases of some vessels.

The adoption of various classes approximates to the principle established in AS 1210; the classification being based primarily on the minimum safety factor as in AS 1210. In this way, a variety of vessels can be covered in a systematic manner in one document. The basis of these classes is discussed in the Commentary (which follows the appendices to this Standard).

While the Standard primarily considers mass-produced or serially produced vessels, provision has been made for the production of vessels in very small numbers to meet the special needs of the refrigeration industry and the limited production runs in Australia.

Limits have been placed on volume, pressure and contained energy for these vessels to ensure reasonable harmonization with AS 1210 and to cover virtually all vessels currently produced to satisfactory standards by this approach.

It is envisaged that experience gained in the use of the Standard will highlight areas that need to be strengthened. The Standard will be regularly reviewed and revised as necessary to ensure it remains a useful document to all parties concerned and provides safe, reliable pressure plant.

Statements expressed in mandatory terms in notes to tables are deemed to be requirements of this Standard.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	6
1.2 OBJECTIVE.....	6
1.3 APPLICATION	6
1.4 REFERENCED DOCUMENTS.....	7
1.5 DEFINITIONS.....	8
1.6 CLASSIFICATION OF VESSELS.....	9
1.7 DESIGNATION	10
1.8 APPLICATION OF CLASSES AND TIERS OF VESSELS	10
SECTION 2 MATERIALS, DESIGN AND MANUFACTURE	
2.1 MATERIALS.....	11
2.2 DESIGN.....	11
2.3 MANUFACTURE	12
2.4 PROTECTIVE DEVICES AND FITTINGS	13
2.5 CORROSION PROTECTION	13
SECTION 3 PERFORMANCE REQUIREMENTS	
3.1 GENERAL.....	14
3.2 RESISTANCE TO INTERNAL PRESSURE	14
3.3 RESISTANCE TO BURSTING AND FRAGMENTATION	14
3.4 RESISTANCE TO FATIGUE	14
3.5 RESISTANCE TO DROPPING.....	14
3.6 RESISTANCE TO PENETRATION	14
3.7 RESISTANCE TO IMPACT	14
3.8 RESISTANCE TO TORQUE	15
3.9 CLOSURE	15
3.10 RESISTANCE TO CORROSION.....	15
3.11 PRESSURE RELIEF	16
3.12 MARKING PLATE ADHESION	16
3.13 SURFACE QUALITY AND CONFORMANCE.....	16
3.14 OTHER PERFORMANCE CHARACTERISTICS.....	16
SECTION 4 MARKING AND INSTRUCTIONS	
4.1 MARKING	17
4.2 INSTRUCTIONS.....	17
SECTION 5 ASSESSMENT OF COMPLIANCE WITH THE REQUIREMENTS OF THIS STANDARD	
5.1 GENERAL.....	18
5.2 WITNESSING OF TYPE TESTS	18
5.3 REPORT OF TYPE TESTING	18
5.4 MANUFACTURER'S DATA REPORT.....	18
5.5 AUDITING OF MANUFACTURER'S FACILITIES.....	19
5.6 RETESTS	19

APPENDICES

A	INTEGRATED PRESSURE EQUIPMENT TEST STATIONS.....	22
B	INFORMATION TO BE SUPPLIED BY THE CUSTOMER AND THE MANUFACTURER.....	24
C	PROOF PRESSURE TESTS.....	26
D	BURST AND FRAGMENTATION TEST	27
E	FATIGUE TEST	29
F	DROP TEST	30
G	PENETRATION TEST.....	32
H	IMPACT TEST	34
I	CORROSION TESTS	36
J	PRESSURE-RELIEF DEVICE TESTS	38
K	MARKING PLATE ADHESION TEST	40
	COMMENTARY.....	41

STANDARDS AUSTRALIA

Australian Standard
Serially produced pressure vessels

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies requirements for the materials, design, manufacture, inspection and testing of serially produced metallic or non-metallic or combination unfired pressure vessels comprising:

- (a) A maximum volume of 500 L.
- (b) A design pressure exceeding 0.05 MPa.
- (c) A product of the design pressure (in megapascals) and the total vapour space (in litres) that is greater than 1 but less than 3000. Where the vessel contents are classified as harmful or very harmful to AS 4343, the upper limit is 1500 MPa.L. This Standard excludes contents classified as lethal.

NOTE: The vapour space is the maximum volume which will contain compressed gas or vapour or liquefied gas or liquid above its atmospheric boiling point.

- (d) A temperature range of -20°C to 150°C . Vessels designated outside the range of 0°C to 50°C require special tests. Refer to Appendices D, F and G where applicable.

Such vessels may be refillable or non-refillable.

NOTE: Users of this Standard are reminded that it has no legal authority in its own right, but may acquire legal standing if adopted by government or any other authority having jurisdiction, or if specified as part of a commercial contract.

1.2 OBJECTIVE

This Standard is intended to —

- (a) establish minimum requirements for the materials, design, manufacture, inspection and testing for pressure vessels within the range of Clause 1.1; and
- (b) provide a method of design based on destructive type testing and monitoring of manufacture by performance testing of representative samples from production. This method is an alternative to that given in AS 1210 to vessels within the range of Clause 1.1.

1.3 APPLICATION

This Standard is not intended to apply to —

- (a) pressure vessels covered by other Australian Standards, e.g. portable fire extinguishers, LP Gas fuel vessels for automotive use and sterilizers;
- (b) compressed gas cylinders covered by AS 2030 (series) and Supplement No. 1 to AS 2030;
- (c) glass and plastics bottles; or
- (d) vacuum vessels (i.e. vessels that operate only below atmospheric pressure).