

Australian/New Zealand Standard™

**Maritime Survivor Locating Systems
(MSLS)**

Part 1: Operating on 121.5 MHz



AS/NZS 4869.1:2005

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee RC-004, Radiocommunications Equipment—Maritime and Safety of Life. It was approved on behalf of the Council of Standards Australia on 24 May 2005 and on behalf of the Council of Standards New Zealand on 3 June 2005. This Standard was published on 8 August 2005.

The following are represented on Committee RC-004:

- Australian Communications Authority
- Australian Electrical and Electronic Manufacturers Association
- Australian Federal Police
- Australian Maritime Safety Authority
- Civil Aviation Safety Authority
- Electromagnetic Technical Evaluation Committee
- Maritime Safety Authority (New Zealand)
- Ministry of Economic Development (New Zealand)
- New Zealand Marine Safety Interests
- State Maritime Service Departments
- State Police/Emergency Services

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.standards.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

**Maritime Survivor Locating Systems
(MSLS)**

Part 1: Operating on 121.5 MHz

First published as AS/NZS 4869.1:2005.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia, GPO Box 5420, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 6788 5

PREFACE

This Standard was prepared by Joint Standards Australia/Standards New Zealand Committee RC-004, Radiocommunications Equipment—Maritime and Safety of Life.

It has been developed generally based on test methods used in AS/NZS 4330:2000, *121.5 and 243.0 MHz emergency position indicating radio beacons (EPIRBs) including personal EPIRBs* and for receiver sensitivity testing on AS/NZS 4768.2:2003, *Digital radio equipment operating in land mobile and fixed services bands in the frequency range 29.7 MHz to 1 GHz Part 2: Methods of test (IEC 60489-6:1999, MOD)*

The objective of this Standard is to provide the essential standards and minimum requirements for the design and construction of 121.5 MHz Maritime Survivor Locating Systems.

The term ‘normative’ has been used in this Standard to define the application of the appendix to which it applies. A ‘normative’ appendix is an integral part of a Standard.

MSLS systems may be developed and employed on other frequencies including those covered by the Australian Communications Authority’s *Radiocommunications (Low Interference Potential Devices) Class Licence 2000* or the New Zealand Ministry of Economic Development’s *General user radio licence*. Those systems are not within the scope of this part of the Standard. The technical requirements for short-range devices are contained in AS/NZS 4268:2003, *Radio equipment and systems—Short range devices—Limits and methods of measurement*.

CONTENTS

	<i>Page</i>
FOREWORD.....	4
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	5
1.2 APPLICATION	5
1.3 REFERENCED AND RELATED DOCUMENTS	6
1.4 DEFINITIONS	6
SECTION 2 ENVIRONMENTAL AND OPERATIONAL REQUIREMENTS	
2.1 GENERAL	9
2.2 OPERATIONAL REQUIREMENTS	10
2.3 BATTERY REQUIREMENTS.....	11
2.4 CLIMATIC AND DURABILITY REQUIREMENT	12
2.5 DOCUMENTATION.....	12
SECTION 3 MSLS RADIOFREQUENCY REQUIREMENTS	
3.1 GENERAL REQUIREMENTS	13
3.2 MSLS TRANSMITTER REQUIREMENTS	13
3.3 MSLS RECEIVER REQUIREMENTS.....	18
3.4 MSLS LOCATOR REQUIRMENTS.....	20
APPENDIX A CLIMATIC AND DURABILITY TESTS FOR MSLS TRANSMITTERS, RECEIVERS AND LOCATORS	21

FOREWORD

To provide the essential requirements for 121.5 MHz Maritime Survivor Locating Systems (MSLS), this Standard includes both environmental and operational requirements and radio-frequency requirements. These specifications are required by both the appropriate national spectrum management authority and maritime safety authority in each country.

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard
Maritime Survivor Locating Systems (MSLS)

Part 1: Operating on 121.5 MHz

SECTION 1 SCOPE AND GENERAL**1.1 SCOPE**

This Standard provides the minimum requirements for Maritime Survivor Locating Systems (MSLSs) intended for very short-range crew retrieval applications operating on 121.5 MHz commonly referred to as man-overboard systems. The MSLS is designed to allow for self help from the vessel or organization where there is a risk of crew falling overboard by sounding an alert from the onboard receiver. MSLS transmitters are not meant to rely on alerting through the COSPAS-SARSAT satellite system.

These devices are not stand alone personal EPIRBs but are part of an integrated system that also includes a receiver and warning device on the vessel, and may include some form of localizing device such as, but not limited to, direction finding equipment. While this Standard does not cover the requirements for personal beacons given in AS/NZS 4330, personal beacons may be used in conjunction with an MSLS. MSLS receivers and locators should be designed to also operate in conjunction with EPIRBs or other distress beacons using the frequency 121.5 MHz.

These minimum requirements encompass the physical characteristics of the devices, as they pertain to maritime use. For MSLS transmitters, both the radiated power and the length of time for operation are reduced to enable the equipment to be sufficiently small and light to be worn comfortably at all times when a person is operating in an open maritime environment. Some characteristics have been specified in order that MSLS beacons do not interfere with the COSPAS-SARSAT satellite system.

MSLS may also be developed and employed on other frequencies including those covered by the Australian Communications Authority's Class license for low interference impact devices or the New Zealand Ministry of Economic Development's General user radio license. Those systems are not within the scope of this part of the Standard. The technical requirements for short-range devices are contained in AS/NZS 4268.

1.2 APPLICATION

This Standard is intended for use by equipment designers, manufacturers and suppliers to ensure correct operation of 121.5 MHz Maritime Survivor Locating Systems and their compatibility with space satellite systems and other devices and systems utilizing the frequency 121.5 MHz.