

AS 3602—1988

ISO 9661:1988

Australian Standard<sup>®</sup>

---

**INFORMATION PROCESSING—  
DATA INTERCHANGE ON  
12.7 mm WIDE MAGNETIC TAPE  
CARTRIDGES—  
18 TRACKS, 1491 DATA BYTES  
PER MILLIMETRE**

---

(ISO Title: Information processing—Data interchange on 12,7 mm (0.5 in) wide magnetic tape cartridges—18 tracks, 1 491 data bytes per millimetre (37 871 data bytes per inch))

This Australian Standard was prepared by Committee IS/1, Information Processing Systems. It was approved on behalf of the Council of Standards Association of Australia on 12 September 1988 and published on 12 December 1988.

---

The following interests are represented on Committee IS/1:

Australian Association of Permanent Building Societies  
Australian Bankers' Association  
Australian Bureau of Statistics  
Australian Computer Equipment Manufacturers Association  
Australian Computing Services Association  
Australian Computer Users Association  
Australian Information Industry Association  
Canberra College of Advanced Education  
CSIRO, Division of Information Technology  
Department of Defence  
Department of Industry, Technology and Commerce  
Latrobe University  
Life Insurance Federation of Australia  
Public Service Board, N.S.W.  
Telecom Australia  
University of Technology, Sydney

---

**Review of Australian Standards.** *To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

*Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.*

*Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.*

AS 3602—1988

Australian Standard®

---

**INFORMATION PROCESSING—  
DATA INTERCHANGE ON  
12.7 mm WIDE MAGNETIC TAPE  
CARTRIDGES—  
18 TRACKS, 1491 DATA BYTES  
PER MILLIMETRE**

---

(ISO Title: Information processing—Data interchange on 12,7 mm (0.5 in) wide magnetic tape cartridges—18 tracks, 1 491 data bytes per millimetre (37 871 data bytes per inch))

First published as AS 3602—1988.

PUBLISHED BY STANDARDS AUSTRALIA  
(STANDARDS ASSOCIATION OF AUSTRALIA)  
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 5278 6

## PREFACE

This Standard was prepared by the Association's Committee on Information Processing Systems. It is part of a ongoing project of review and addition of Input/Output Media Standards. It is identical with and has been prepared from International Standard ISO 9661—1988, drawn up by ISO/TC97, Information Processing Systems.

For the purpose of this Australian Standard, the text of this ISO Standard should be modified as follows:

- (a) *Terminology*: The words 'Australian Standard' should replace the words 'International Standard' wherever they appear.
- (b) *Substitute* a point (.) for a comma (,) as a decimal marker.
- (c) *Cross-reference*: The references to International Standards should be replaced by references to Australian Standards as follows:

<i>Reference to International Standard</i>	<i>Australian Standard</i>
ISO	AS
646 Information processing—ISO 7-bit coded character set for information interchange	1776 Information processing—ISO 7-bit coded character set for information interchange
1001 Information processing—File structure and labelling of magnetic tapes for information processing interchange	1068 Information processing—File structure and labelling of magnetic tapes for information exchange
1702 Technical drawings—Method indicating surface texture of drawings	1100.201 Technical drawing—Mechanical drawing
2022 Information processing—ISO 7-bit and 8-bit coded character sets—Code extension techniques	1953 Information processing—ISO 7-bit and 8-bit coded character sets—Code extension techniques

## © Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## Contents

	Page
<b>Section 1: General</b>	
1.1 Scope	6
1.2 Conformance	6
1.3 Normative references	6
1.4 Definitions	6
1.4.1 Average Signal Amplitude	6
1.4.2 back surface	6
1.4.3 byte	6
1.4.4 cartridge	6
1.4.5 Cyclic Redundancy Check Character	6
1.4.6 data density	6
1.4.7 Error Correcting Code	6
1.4.8 flux transition position	6
1.4.9 flux transition spacing	6
1.4.10 magnetic tape	6
1.4.11 Master Standard Reference Tape	7
1.4.12 physical recording density	7
1.4.13 Postamble	7
1.4.14 Preamble	7
1.4.15 Reference Field	7
1.4.16 Secondary Standard Reference Tape	7
1.4.17 Standard Reference Amplitude	7
1.4.18 Standard Reference Current	7
1.4.19 Test Recording Current	7
1.4.20 track	7
1.4.21 Typical Field	7
1.5 Environment and safety	7
1.5.1 Cartridge/tape testing environment	7
1.5.2 Cartridge operating environment	7
1.5.3 Cartridge storage environment	7
1.5.4 Safety requirements	7
1.5.4.1 Safety	7
1.5.4.2 Flammability	7
1.5.5 Transportation	7
<b>Section 2: Tape requirements</b>	
2.1 Characteristics of the tape	8
2.1.1 Material	8
2.1.2 Tape length	8
2.1.3 Tape width	8
2.1.4 Tape discontinuity	8
2.1.5 Total thickness of tape	8
2.1.6 Base material thickness	8
2.1.7 Longitudinal curvature	8
2.1.8 Out-of-plane distortions	8
2.1.9 Cupping	8

	Page
2.1.10 Dynamic frictional characteristics .....	8
2.1.10.1 Frictional drag between the recording surface and the tape back surface .....	8
2.1.10.2 Frictional drag between the tape recording surface and ferrite after environmental cycling .....	8
2.1.11 Coating adhesion .....	9
2.1.12 Flexural rigidity .....	9
2.1.13 Electrical resistance of coated surfaces .....	10
2.1.14 Tape durability .....	10
2.1.15 Inhibitor tape .....	10
2.1.16 Tape abrasivity .....	10
2.1.17 Pre-recording condition .....	10
2.1.18 Magnetic recording characteristics .....	10
2.1.18.1 Typical Field .....	11
2.1.18.2 Signal amplitude .....	11
2.1.18.3 Resolution .....	11
2.1.18.4 Overwrite .....	11
2.1.18.5 Narrow-band signal-to-noise ratio (NB-SNR) .....	11
2.1.19 Tape quality .....	12
2.1.19.1 Missing pulses .....	12
2.1.19.2 Missing pulse zones .....	12
2.1.19.3 Coincident missing pulse zones .....	12
 <b>Section 3: Cartridge requirements</b>	
3.1 Dimensional mechanical characteristics of the cartridge .....	13
3.1.1 Overall dimensions .....	13
3.1.2 Write-inhibit mechanism .....	13
3.1.3 Label area of the rear side .....	13
3.1.4 Label area of the top side .....	14
3.1.5 Case opening .....	14
3.1.6 Locating notches .....	14
3.1.7 Locating areas .....	14
3.1.8 Inside configuration of the case around the case opening .....	14
3.1.9 Other external dimensions of the case .....	14
3.1.10 Central window .....	14
3.1.11 Stacking ribs .....	15
3.1.12 Flexibility of the case .....	15
3.1.12.1 Requirements .....	15
3.1.12.2 Procedure .....	15
3.1.13 Tape reel .....	15
3.1.13.1 Locking mechanism .....	15
3.1.13.2 Axis of rotation of the reel .....	15
3.1.13.3 Metallic insert .....	15
3.1.13.4 Toothed rim .....	15
3.1.13.5 Hub of the reel .....	15
3.1.13.6 Relative positions .....	16
3.1.13.7 Characteristics of the toothed rim .....	16
3.1.14 Leader block .....	16
3.1.15 Attachment of the tape to the leader block .....	17
3.1.16 Latching mechanism .....	17
3.1.17 Tape wind .....	17
3.1.18 Wind tension .....	17
3.1.19 Circumference of the tape reel .....	17
3.1.20 Moment of inertia .....	17
 <b>Section 4: Recording requirements</b>	
4.1 Method of recording .....	24
4.1.1 Physical recording density .....	24
4.1.2 Bit cell length .....	24
4.1.3 Average bit cell length .....	24
4.1.4 Long-term average bit cell length .....	24
4.1.5 Short-term average bit cell length .....	24
4.1.6 Rate of change .....	24
4.1.7 Bit shift .....	24

	Page	
4.1.8	Total character skew . . . . .	24
4.1.9	Read signal amplitude . . . . .	24
4.1.10	Coincident missing pulses . . . . .	24
4.2	Track format . . . . .	24
4.2.1	Number of tracks . . . . .	24
4.2.2	Reference Edge . . . . .	24
4.2.3	Track positions . . . . .	25
4.2.4	Track width . . . . .	25
4.2.5	Azimuth . . . . .	25
4.3	Data format . . . . .	25
4.3.1	Types of bytes . . . . .	25
4.3.1.1	Data bytes . . . . .	25
4.3.1.2	Pad bytes . . . . .	25
4.3.1.3	Block-ID bytes . . . . .	25
4.3.2	Frame . . . . .	26
4.3.3	Data block . . . . .	27
4.3.3.1	Prefix . . . . .	27
4.3.3.2	Data Frames . . . . .	27
4.3.3.3	Residual Frame 1 . . . . .	28
4.3.3.4	Residual Frame 2 . . . . .	28
4.3.3.5	Suffix . . . . .	29
4.3.4	Error Correcting Code (ECC) . . . . .	29
4.3.4.1	Diagonal Redundancy Check (DRC) . . . . .	29
4.3.4.2	Vertical Redundancy Check (VRC) . . . . .	29
4.3.4.3	ECC Format . . . . .	29
4.3.4.4	Summary of ECC . . . . .	30
4.3.5	Recording of 8-bit bytes on the tape . . . . .	31
4.3.6	Recorded Data Block . . . . .	31
4.3.6.1	Preamble . . . . .	31
4.3.6.2	Beginning of Data Mark . . . . .	31
4.3.6.3	Resync Control Frame . . . . .	31
4.3.6.4	End of Data Mark . . . . .	31
4.3.6.5	Postamble . . . . .	31
4.3.7	Data density . . . . .	31
4.4	Tape format . . . . .	32
4.4.1	Density Identification Burst . . . . .	32
4.4.2	ID Separator Burst . . . . .	32
4.4.3	Interblock Gaps . . . . .	32
4.4.4	Erase Gaps . . . . .	33
4.4.4.1	Normal Erase Gaps . . . . .	33
4.4.4.2	Elongated Erase Gaps . . . . .	33
4.4.5	Tape Marks . . . . .	33
4.4.6	Relation between Interblock Gaps, Erase Gaps and Tape Marks . . . . .	33
4.4.6.1	Interblock Gap followed by a Tape Mark . . . . .	33
4.4.6.2	Tape Mark followed by an Interblock Gap . . . . .	33
4.4.6.3	Interblock Gap followed by an Erase Gap . . . . .	33
4.4.6.4	Erase Gap followed by an Interblock Gap . . . . .	33
4.4.6.5	Summary of the relation between Interblock Gaps, Erase Gaps and Tape Marks . . . . .	34
4.4.7	First and last recording on the tape . . . . .	34
4.4.8	Summary of the tape format . . . . .	34
4.4.8.1	Characteristics of recording other than Recorded Data Blocks . . . . .	34
4.4.8.2	Arrangement of recording on the tape . . . . .	35
 <b>Annexes</b>		
A	Recommendations for transportation . . . . .	36
B	Inhibitor tape . . . . .	36
C	Tape abrasivity measurement procedure . . . . .	37
D	Recommendations on tape durability . . . . .	39
E	Pre-recording condition . . . . .	40
F	Representation of 8-bit bytes by 9-bit patterns . . . . .	41
G	Measurement of bit shift . . . . .	44
H	Dimensions of the cartridge . . . . .	46

# Information processing—Data interchange on 12.7 mm wide magnetic tape cartridges—18 tracks, 1491 data bytes per millimetre

## Section 1: General

### 1.1 Scope

This International Standard specifies the physical and magnetic characteristics of a 12,7 mm (0.5 in) wide, 18-track magnetic tape cartridge to enable interchangeability of such cartridges. It also specifies a format and recording method thus allowing, together with ISO 1001 for magnetic tape labelling, full data interchange by means of such magnetic tape cartridges.

NOTE — Numeric values in the SI and/or Imperial measurement system in this International Standard may have been rounded off and therefore are consistent with, but not exactly equal to, each other. Either system may be used, but the two should be neither intermixed nor reconverted. The original design was made using SI units.

### 1.2 Conformance

A magnetic tape cartridge shall be in conformance with this International Standard if it meets all mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

### 1.3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 646 : 1983, *Information processing — ISO 7-bit coded character set for information interchange*.

ISO 683-13 : 1986, *Heat-treatable steels, alloy steels and free-cutting steels — Part 13: Wrought stainless steels*.

ISO 1001 : 1986, *Information processing — File structure and labelling of magnetic tapes for information processing interchange*.

ISO 1302 : 1978, *Technical drawings — Method of indicating surface texture on drawings*.

ISO 2022 : 1986, *Information processing — ISO 7-bit and 8-bit coded character sets—Code extension techniques*.

ISO 4873 : 1986, *Information processing — ISO 8-bit code for information interchange—Structure and rules for implementation*.

### 1.4 Definitions

For the purpose of this International Standard, the following definitions apply.

**1.4.1 Average Signal Amplitude:** The average peak-to-peak value of the signal output of the read head measured over a minimum of 25,4 mm (1 in) of tape exclusive of missing pulses.

**1.4.2 back surface:** The surface of the tape opposite the magnetic coating used to record data.

**1.4.3 byte:** An ordered set of eight bits acted upon as a unit and recorded as a 9-bit pattern.

**1.4.4 cartridge:** A container holding a supply reel of magnetic tape with an attached leader block.

**1.4.5 Cyclic Redundancy Check Character:** A character represented by two bytes, placed at the end of a data block and used for error detection.

**1.4.6 data density:** The number of 8-bit bytes stored per unit length of tape, expressed in bytes per millimetre (bytes per inch).

**1.4.7 Error Correcting Code:** A mathematical procedure yielding bits used for the detection and correction of errors.

**1.4.8 flux transition position:** That point which exhibits maximum free-space flux density normal to the tape surface.

**1.4.9 flux transition spacing:** The distance along a track between successive flux transitions.

**1.4.10 magnetic tape:** A tape which will accept and retain the magnetic signals intended for input, output and storage purposes on computers and associated equipment.