

Australian Standard[®]

**Precast reinforced concrete box
culverts**

**Part 2: Large culverts (exceeding
1200 mm span or 1200 mm height and
up to and including 4200 mm span and
4200 mm height)**



This Australian Standard® was prepared by Committee CE-026, Precast Reinforced Concrete Box Culverts. It was approved on behalf of the Council of Standards Australia on 21 March 2013

This Standard was published on 12 August 2013.

The following are represented on Committee CE-026:

- AUSTRROADS
 - Australasian Railway Association
 - Concrete Pipe Association of Australasia
 - Engineers Australia
 - National Precast Concrete Association Australia
 - University of Sydney
-

This Standard was issued in draft form for comment as DR AS 1597.2.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

**Precast reinforced concrete box
culverts**

**Part 2: Large culverts (exceeding
1200 mm span or 1200 mm height and
up to and including 4200 mm span and
4200 mm height)**

First published as AS 1597.2—1996.
Second edition 2013.

COPYRIGHT

© Standards Australia Limited

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968.

Published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 978 1 74342 554 1

PREFACE

This Standard was prepared by the Standards Australia Committee CE-026, Precast Reinforced Concrete Box Culverts, to supersede AS 1597.2—1996, *Precast reinforced concrete box culverts, Part 2: Large culverts (from 1500 mm span and up to and including 4200 mm span and 4200 mm height)*.

The objective of this Standard is to provide designers, manufacturers, installers and specifiers of culverts with minimum requirements for the design, manufacture and installation of precast reinforced concrete rectangular box culverts of spans up to 4200 mm.

The objective of this revision is to align the Standard with current manufacturing and installation practices as well as governing design codes.

The revised Standard provides for four types of culvert and a range of standard sizes up to and including 4200 mm width and 4200 mm height. Design requirements are based on the AS 5100 series, *Bridge design* and AS 3600, *Concrete structures*.

Where the Standard departs from these Standards, or includes additional requirements in excess of those specified in these Standards, it identifies that the purchaser has the option to adopt the design requirement in this Standard, or to revert back to AS 5100 series or AS 3600 series requirements. Appendix A also contains advice and recommendations on the information that should be supplied by the purchaser at the time of inquiry or order to assist with these design requirements.

Statements expressed in mandatory terms in notes to tables are deemed to be requirements of this Standard.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the appendix to which they apply. A ‘normative’ appendix is an integral part of a Standard, whereas an ‘informative’ appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	5
1.2 APPLICATION	5
1.3 NORMATIVE REFERENCES	6
1.4 DEFINITIONS.....	7
1.5 NOTATION.....	9
1.6 TYPES OF CULVERTS.....	12
1.7 CLASSIFICATION	12
SECTION 2 MATERIALS, MANUFACTURE AND DIMENSIONING	
2.1 SCOPE OF SECTION	14
2.2 FORMWORK.....	14
2.3 REINFORCEMENT	14
2.4 CONCRETE MATERIALS	15
2.5 CONCRETE SPECIFICATION AND COVER TO REINFORCEMENT	16
2.6 CONCRETE PRODUCTION, PLACEMENT AND CURING	16
2.7 JOINTS.....	18
2.8 DIMENSIONS.....	18
2.9 MEASUREMENT OF DIMENSIONS	20
2.10 TOLERANCES.....	20
2.11 STORAGE AND HANDLING.....	21
2.12 WORKMANSHIP AND FINISH.....	22
2.13 DEFECTS.....	22
2.14 FINISHING AND REPAIRS.....	23
2.15 MARKING	23
SECTION 3 DESIGN REQUIREMENTS AND PROCEDURES	
3.1 SCOPE OF SECTION	24
3.2 GENERAL DESIGN REQUIREMENTS.....	24
3.3 DESIGN LOADS.....	25
3.4 LOAD COMBINATIONS	32
3.5 LOAD EFFECT ANALYSIS AND DESIGN	34
3.6 STRENGTH AND SERVICEABILITY DESIGN	34
3.7 REINFORCEMENT	35
3.8 FATIGUE DESIGN.....	35
SECTION 4 SAMPLING AND TESTING	
4.1 SCOPE OF SECTION	37
4.2 GENERAL.....	37
4.3 PROCESS TESTING.....	37
4.4 ROUTINE SAMPLING AND TESTING	39
SECTION 5 INSTALLATION	
5.1 SCOPE OF SECTION	41
5.2 EXCAVATION	41
5.3 FOUNDATION PREPARATION.....	41
5.4 PLACING PRECAST UNITS	42
5.5 COMPACTION	42
5.6 BACKFILLING.....	42
5.7 CONSTRUCTION LOADS ON CULVERTS	43
5.8 ACCEPTABLE CRACK WIDTHS UNDER SERVICE LOADS	44

	Page
APPENDICES	
A PURCHASING GUIDELINES	45
B MEANS OF DEMONSTRATING COMPLIANCE WITH THIS STANDARD	47
C LOW PRESSURE STEAM CURING OF CONCRETE UNITS	49
D METHODS FOR COVER TESTING OF UNITS	51
E MEASUREMENT OF CRACK WIDTH	53
F SAMPLING SCHEME FOR ROUTINE TESTING.....	55
G ADDITIONAL DESIGN INFORMATION	57
H ALTERNATIVE SHEAR STRENGTH PROVISIONS FOR CULVERTS.....	64
BIBLIOGRAPHY	66

STANDARDS AUSTRALIA

Australian Standard

Precast reinforced concrete box culverts

Part 2: Large culverts (exceeding 1200 mm span or 1200 mm height and up to and including 4200 mm span and 4200 mm height)

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard sets out minimum requirements for the design, manufacture and installation of precast reinforced concrete rectangular box culverts for conveying water not under pressure, and for carrying roadway and railway loadings specified by the AS 5100 series.

This Standard is applicable to the design of culverts in dry or intermittently wet conditions.

NOTES:

- 1 For culverts to be designed for embankments that occasionally impound water, specialist design advice should be sought regarding the overall embankment stability.
- 2 Culvert units, lids and base slabs manufactured in accordance with this Standard can be expected to achieve a design life of 100 years.
- 3 Design requirements are based on the methods of limit state design, using theoretical strength and serviceability calculations. Alternatively, design by prototype testing in accordance with the general principles and requirements of the AS 5100 series or AS 3600 is acceptable.
- 4 The testing procedure and test loads for prototype testing should demonstrate that the units tested satisfy the design loads and manufacturing requirements of this Standard.

1.2 APPLICATION

This Standard is applicable to rectangular precast culvert units having a standard length of 1200 mm, a maximum height of 4200 mm and a span exceeding 1200 mm up to 4200 mm.

NOTES:

- 1 Guidelines to purchasers on requirements that may need to be agreed upon at the time of calling for tenders or quotations are detailed in Appendix A.
- 2 Information on means for demonstrating compliance with this Standard is given in Appendix B.
- 3 Lengths greater than 1200 mm may be ordered, preferably in multiples of 1200 mm (e.g. 2400 mm and 3600 mm).
- 4 For precast reinforced concrete box culverts of internal dimensions not exceeding 1200 mm nominal span and 1200 mm nominal height, refer to AS 1597.1.
- 5 Additional design considerations may be required for special culverts (e.g. larger spans, skewed ends, culvert units with large holes, roadway culverts subjected to loadings other than standard roadway loadings and railway culverts).