

Australian Standard[®]

**COMPLETE, FILLED
TRANSPORT PACKAGES—
GENERAL RULES FOR
THE COMPILATION OF
PERFORMANCE SCHEDULES**

Part 2—QUANTITATIVE DATA

This Australian standard was prepared by Committee PK/12, Physical Testing of Packages and Containers. It was approved on behalf of the Council of the Standards Association of Australia on 27 November 1982 and published on 9 May 1983.

The following interests are represented on Committee PK/12:

- Australia Post
 - Australian Institute of Packaging
 - Australian and New Zealand Pulp and Paper Industry Technical Association
 - Confederation of Australian Industry
 - CSIRO, Division of Chemical Technology
 - Department of Agriculture, Victoria
 - Department of Primary Industries, Queensland
 - Department of Science and Technology
 - Department of Transport
 - Packaging Council of Australia
 - Plastics Institute of Australia Incorporated
 - Railways of Australia Committee
-

Review of Australian Standards. *To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

First published 1983

This standard was issued in draft form for comment as DR 82126.

PREFACE

This standard was prepared by the Association's Committee on Physical Testing of Packages and Containers. It is technically identical with International Standard ISO 4180/2, drawn up by Technical Committee ISO/TC 122, Packaging. SAA, as the Australian member body of ISO, approved the ISO standards at the ballot stage.

This standard has been prepared in order to fulfil a need of organizations concerned with the compilation of test schedules for complete, filled transport packages.

Such test schedules can be as diverse as the journeys that packages undergo. Accordingly, this standard is intended to set guidelines for the compilation of appropriate test schedules, rather than to provide a rigid framework or to be specified by regulatory or other authorities.

It is expected that, once compiled, a particular test schedule, including the test methods and intensities to be applied, could be the subject of Australian standards or would become a matter for agreement between the parties concerned, for example the package designer, the manufacturer of the contents, the transport authority, the customer, the statutory regulating body, or any combination of them.

Except for Clause 2 which contains Australia references, the text of the international standard has been accepted as suitable without deviation, but some terms used in the international standards may not be identical with those used in existing Australian standards. In this connection, reference should be made to AS 2400, Part 1, SAA Packaging Code — Glossary of packaging terms.

CONTENTS

	<i>Page</i>
STANDARD	
1 Scope	4
2 Referenced Documents	4
3 Factors Requiring Quantification in Test Methods	4
4 Preferred Values of Test Intensities	4
5 Test Intensity Modifying Factors	4
6 Examples of the Compilation of Test Schedules	5

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard

for

**COMPLETE, FILLED TRANSPORT PACKAGES—GENERAL RULES FOR THE
COMPILATION OF PERFORMANCE SCHEDULES****PART 2—QUANTITATIVE DATA**

1 SCOPE. This standard establishes general rules to be used for the compilation of performance test schedules for complete, filled transport packages intended for use within any distribution system, whether transported by road, rail, sea, air or inland waterway, or by a combination of these modes of transport.

AS 2584.1 states the general principles entailed in compiling test schedules. It also gives the factors to be considered in assessing the criteria of acceptance of such packages after they have been subjected to a package performance test schedule.

This standard incorporates all the quantitative data necessary to establish test intensities and other quantitative features of test schedules.

AS 2584.1 and this standard are intended to be read in conjunction with one another.

NOTE: For the distribution trials of packages containing dangerous goods the relevant regulations for the transport of dangerous goods by road, rail, sea and air must be followed, i.e.—

Australian Code for Transport of Dangerous Goods by Road and Rail

International Air Transport Association's Restricted Articles Regulations

International Maritime Dangerous Goods Code.

2 REFERENCED DOCUMENTS. The following standards are referred to in this standard:

- AS 2400 SAA Packaging Code
Part 1 — Glossary of Packaging Terms
- AS 2582 Complete, Filled Transport Packages—
Methods of Test
2582.1 — Identification of parts when
testing
2582.2 — Conditioning for testing
2582.3 — Stacking, compression test
2582.4 — Vertical impact test by dropping
2582.5 — Horizontal impact test (Inclined
plane test, Pendulum test)
2582.6 — Vibration Test
2582.7 — Low pressure test
- AS 2583 Complete, Filled Transport Packages—
Distribution Trials—Information to be
Recorded
- AS 2584 Complete, Filled Transport Packages—
General Rules for the Compilation of
Performance Schedules
Part 1 — General principles

**3 FACTORS REQUIRING QUANTIFICATION
IN TEST METHODS.** Relevant test methods, and the factors requiring quantification before each test can be used, are given in Table 1.

4 PREFERRED VALUES OF TEST INTENSITIES.

Basic test intensities, which are considered to be normal for a common distribution system and which are based upon a package of 'average' mass and size (i.e. of mass 20 kg and dimensions 400 mm × 400 mm × 400 mm) are given in Table 2, for the road, rail, water and air modes of transport and for storage.

Where a test intensity other than the basic value is appropriate (see Clause 4) the value selected should be chosen, as far as is practicable, from the preferred values given in Table 3.

For comparative investigations or research it may be necessary to select values of test intensity other than those given in Table 3.

5 TEST INTENSITY MODIFYING FACTORS.

5.1 General. Guidelines for modifying basic values of test intensity, due to known features of the distribution system or of the package, are given in Table 4.

The special circumstances introduced by palletization and by the use of freight containers are outlined in Clause 5.2.

5.2 Modification of Test Intensity by Palletization or by the Use of Freight Containers.

5.2.1 Palletization. Packages may be grouped into a unit load on a pallet or similar device for the whole or part of their life.

The subsequent handling of the unit load by mechanical means can change the magnitude of the hazards to which the packages are exposed, primarily vertical impact and stacking hazards.

- (a) *Vertical impact.* Manual palletization subjects the individual packages to vertical impacts of intensity similar to those sustained in loading the packages on to a road vehicle. Mechanical palletization, however, subjects the packages to a very small, if any, vertical impact hazard.

Mechanical handling of the resultant unit loads, into and out of storage and in the loading and unloading of vehicles, results in the packages being subjected to a smaller vertical impact than that normally associated with the comparable manual operation (see Tables 2 and 4).

Palletization, coupled with a suitable distribution system for handling pallets may therefore justify a reduction in intensity of more than one step in the preferred range of values of drop height (see Tables 2, 3 and 4).

- (b) *Storage.* The ability of mechanical equipment to lift unit loads to a greater height than is normal using manual methods can result in packages being stacked to greater heights. In addition, certain