

AS 2956.4—1988/ISO 6405—1982

Australian Standard[®]

**EARTH-MOVING MACHINERY—
INSTRUMENTATION AND
OPERATOR'S CONTROLS**

Part 4—SYMBOLS

(ISO Title: Earth-moving machinery—Symbols—Operator controls
and others)

This Australian Standard was prepared by Committee ME/63, Earthmoving Equipment. It was approved on behalf of the Council of the Standards Association of Australia on 3 March 1988 and published on 17 June 1988.

The following interests are represented on Committee ME/63:

Australian Mining Industry Council
Bureau of Steel Manufacturers of Australia
Construction Equipment Importers and Manufacturers of Australia
Department of Administrative Services
Department of Conservation, Forests and Lands, Vic.
Department of Defence
Department of Forestry, Qld.
Department of Industrial Relations and Employment, N.S.W.
Department of Labour, Vic.
Department of Mines, Qld.
Earth-movers and Road Contractors Association of Australia
Forestry Commission of New South Wales
Local Government Engineers Association of New South Wales
Metal Trades Industry Association of Australia
National Association of Australian State Road Authorities
Rural Water Commission, Vic.
Safety Institute of Australia
Telecom Australia
Tractor and Machinery Association of Australia
Water Board, Sydney

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 85205.

AS 2956.4—1988/ISO 6405—1982

Australian Standard[®]

**EARTH-MOVING MACHINERY—
INSTRUMENTATION AND
OPERATOR'S CONTROLS**

Part 4—SYMBOLS

(ISO Title: Earth-moving machinery—Symbols—Operator controls
and others)

First published as AS 2956.4/ISO 6405—1988.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 5020 1

CONTENTS

	<i>Page</i>
1 SCOPE AND FIELD OF APPLICATION	3
2 GENERAL	3
3 REFERENCE	3
DESIGNATION AND ILLUSTRATION OF SYMBOLS	
4 GENERAL	4
5 ELECTRIC	5
6 LIGHTS	5
7 ENGINE	5
8 TRANSMISSION	6
9 FUEL	6
10 ENGINE OIL	7
11 COOLANT	7
12 DRIVE TRAIN OIL (INCLUDING TRANSMISSION AND TORQUE CONVERTER)	7
13 HYDRAULIC OIL	8
14 AIR	8
15 BRAKE FLUID	8
16 BUCKET—LOADER	8
17 BUCKET—MULTI-PURPOSE	9
18 BLADE	9
19 RIPPER	10
20 EXCAVATOR ARM	10
21 GRADER	11
22 DUMPER	12
23 TRACTOR SCRAPER	13
24 STABILIZER	14
25 WINCH	14
26 CAB	15

FOREWORD

1. This Australian Standard corresponds with ISO 6405—1982, *Earth-moving machinery — Symbols — Operator controls and others*.
2. Introduction to and complete listing of the SAA series of earth-moving machinery Standards (AS 2951 to AS 2958) is available on request.
3. For the purpose of this Australian Standard the words 'International Standard' should be replaced by 'Australian Standard'.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Earth-moving machinery—Instrumentation and operator's controls

Part 4—Symbols

1 Scope and field of application

This International Standard establishes:

- a) symbols for operator controls,
- b) symbols for controls other than operator controls, for use on earth-moving machines.

2 General

2.1 The symbols shall be as given in clauses 4 to 25, except for deviations necessary to reproduce an accurate representation to the operator's line of sight.

2.2 If, in a symbol, an earth-moving machine or parts of the machine are shown in a side view, a machine driving from right to left shall be assumed.

2.3 Symbols on controls shall be of a good contrast with their background (preferably light symbol on dark background).

2.4 The shading (i.e. shown in black) of the elements of a control depicted on a symbol shall be applied only to the parts which move with direct movement of the designated control device.

2.5 Symbols shall be located on or adjacent to the control for the function depicted.

2.6 Where more than one symbol is required (for example on, off, move left, move right), the symbols shall be so located in relation to the control device that movement of the device, in a direction indicated by the relation of the symbols to the control device, shall indicate the sense of the control.

3 Reference

ISO 3461, *Graphic symbols — General principles for presentation*.