

Australian Standard[®]

SPIRIT LEVEL VIALS

[Title Allocated by Defence Cataloguing
Authority: VIAL, LEVEL . . . 5210]

The following scientific, industrial and governmental organizations were officially represented on the committee entrusted with the preparation of this standard:

Associated Chamber of Manufactures of Australia
Department of Defence
Department of Productivity
Federal Chamber of Automotive Industries
Institution of Production Engineers
Metal Trades Industry Association of Australia
National Measurement Laboratory
Queensland Institute of Technology
Railways of Australia Committee
Society of Manufacturing Engineers
The Institution of Engineers, Australia
University of New South Wales
Weapons Research Establishment

This standard, prepared by Committee ME/27, Metrology, was approved on behalf of the Council of the Standards Association of Australia on 26 October 1977 and was published on 1 August 1977.

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This standard was issued in draft form for public review as DR 75139.

AS 1983—1977

Australian Standard[®]

SPIRIT LEVEL VIALS

First published 1977

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 1127 3

PREFACE

This standard was prepared by the Association's Committee on Metrology as part of its program of providing a rational range of specifications for measuring equipment in metric units.

Currently there is no international agreement on the subject of spirit levels within ISO/TC 3, Dimensional Metrology, nor does any appear likely in the foreseeable future. With this in mind, the committee took into account practices specified in BS 3509, Spirit Levels for Use in Precision Engineering.

The only Australian standard to refer to spirit level vials is AS 2054, Spirit Levels for Use in Precision Engineering, and that document also has been taken into account in the preparation of this standard.

The standard includes provisions for spirit levels used in surveying instruments, general levelling instruments, and also in various inspection techniques. These spirit levels have previously been designed to suit the instruments in which they were fitted and used, and consequently although the sensitivity required of any particular vial has been directly related to the accuracy and function of the instrument its size has been governed by the space available for fitting its individual casing.

The purpose of the standard is to provide the designer and the user with the choice of vials of an optimum size for all given accuracies. In this connection it should be pointed out that there is little to be gained in accuracy by increasing the sensitivity of a vial beyond the values given for a particular size.

Attention is drawn to the fact that spirit level vials may be tested for compliance with this standard by laboratories registered with the National Association of Testing Authorities (NATA) for the class and field of testing.

In accordance with the practice adopted in AS 1100, Drawing Practice, the decimal comma has been used in this standard.

This standard may require reference to the following Australian standards:

AS 1652 Dental Laboratory Plaster

AS 2054 Spirit Levels for Use in Precision Engineering.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

SPECIFICATION		<i>Page</i>
1	Scope	4
2	Classification	4
3	Definitions	4
4	Materials	5
5	Scale Marks	5
6	Dimensions	7
7	Performance	9
APPENDICES		
A	Recommended Method of Testing Vials	14
B	Recommendations for Standard Mounts	17

STANDARDS ASSOCIATION OF AUSTRALIA

**Australian Standard Specification
for
SPIRIT LEVEL VIALS**

1 SCOPE. This standard specifies the sizes and performance requirements for both precise and coarse vials for spirit levels. The vials are for use in instruments for precision surveying, inspection, and general levelling. Ranges for the parameters of spirit level vials are related to the sensitivity of the vial, and preferred sets of parameters for given sensitivities are indicated.

NOTES:

1. Appendix A gives recommended methods of testing vials.
2. Appendix B gives recommendations for standard mounts for vials.

2 CLASSIFICATION Straight cylindrical spirit level vials shall be classified according to their dimensions, and designated as Types I to VI, as shown in Table 1.

3 DEFINITIONS For the purpose of this standard, the following definitions apply. For further definitions refer to AS Z23*.

3.1 Spirit level vial—a glass vessel suitably processed, partially filled with a liquid of low freezing point and viscosity, and completely sealed.

3.2 Straight cylindrical vial—a vial made from nominally straight glass tube which has been fully barrel-ground or partially ground internally to a required radius of curvature longitudinally.

3.3 Bent cylindrical vial—a vial made by bending a glass tube to a required radius of curvature longitudinally.

3.4 Circular vial—a vial possessing a spherical functional surface whereby inclinations in all directions can be detected (in contradistinction to vials defined in Clauses 3.2 and 3.3 which are only required to be sensitive to tilts along their longitudinal axis).

3.5 Bubble—the small space created inside the sealed glass tube by partial filling, occasionally referred to as the air space or air bell.

NOTE: It is customary to refer to spirit level vials themselves as 'bubbles'; to avoid confusion of terms this mode of reference is not used in this standard.

3.6 Sensitivity—that angle of tilt which causes the bubble in the vial to move through one scale division.

* AS Z23, Glossary of Terms Relating to the Performance of Measuring Instruments.