

Australian/New Zealand Standard™

406 MHz satellite distress beacons

**Part 1: Marine emergency position-
indicating radio beacons (EPIRB)
(IEC 61097-2:2002, MOD)**



AS/NZS 4280.1:2003

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee RC-004, Radiocommunications Equipment—Maritime. It was approved on behalf of the Council of Standards Australia on 25 September 2003 and on behalf of the Council of Standards New Zealand on 9 September 2003. This Standard was published on 7 November 2003.

The following are represented on Committee RC-004:

Australian Communications Authority
Australian Electrical and Electronic Manufacturers Association
Australian Federal Police
Australian Maritime Safety Authority
Australian Yachting Federation
Department of Defence, Australia
Electromagnetic Technical Evaluation Committee
Maritime Safety Authority, New Zealand
Ministry of Economic Development, New Zealand
New Zealand Marine Safety Interests
State Maritime Service Departments
State Police/Emergency Services
Telstra Corporation

Additional Interests:

Volunteer Marine Rescue Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

This Standard was issued in draft form for comment as DR 03266.

Australian/New Zealand Standard™

406 MHz satellite distress beacons

Part 1: Marine emergency position- indicating radio beacons (EPIRB) (IEC 61097-2:2002, MOD)

Originated as part of AS/NZS 4280:1995.
Previous edition AS/NZS 4280.1:2002.
Second edition 2003.
Reissued incorporating Amendment No. 1 (April 2005).
Reissued incorporating Amendment No. 2 (September 2006).
Reissued incorporating Amendment No. 3 (April 2010).
Reissued incorporating Amendment No. 4 (September 2013).

COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140.

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee RC-004, Radiocommunications Equipment—Maritime to supersede AS/NZS 4280.1:2002.

This Standard incorporates Amendments No. 1 (April 2005), No. 2 (September 2006), No. 3 (April 2010) and No. 4 (September 2013). The changes required by the Amendments are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.

The objective of this Standard is to provide manufacturers, suppliers and testing facilities of 406 MHz satellite distress beacons with the minimum radiofrequency and environmental requirements and associated test methods to enable design and confirmation of compliance with Australia and New Zealand radiofrequency spectrum and maritime regulatory requirements.

The committee has developed relaxed requirements for a 406 MHz EPIRB designed for use on vessels not subject to the International Convention for the Safety of Life at Sea 1974 (SOLAS) applications.

This Standard is Part 1 of AS/NZS 4280, *406 MHz satellite distress beacons*, which is published in parts as follows:

Part 1: Marine emergency position-indicating beacons (EPIRB) (this Standard)

Part 2: Personal locator beacons (PLBs)

This Standard covers 406 MHz satellite distress beacons (EPIRBs) operating in the maritime service. It is reproduced from IEC 61097-2:2002, *Global maritime distress and safety system (GMDSS)—Part 2: COSPAS-SARSAT EPIRB—Satellite emergency position indicating radio beacon operating on 406 MHz—Operational and performance requirements, methods of testing and required test results*. Some variations have been made for Australian/New Zealand conditions and Annexes ZA, ZB and ZC have been added.

Variations to IEC 60197-2:2002 are indicated at the appropriate places throughout this Standard. Strikethrough (~~example~~) identifies IEC tables, figures and passages of text which, for the purposes of this Australian/New Zealand Standard, are deleted. Where Australian/New Zealand tables, figures or passages of text are added, each is set in its proper place and identified by shading (~~example~~). Added figures are not themselves shaded, but are identified by a shaded border.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (b) In the source text ‘this standard’ should read ‘this Australian/New Zealand Standard’.
- (c) A full point should be substituted for a comma when referring to a decimal marker.

A4

The NOAA checksum calculation method for 15-character hexadecimal ID (UIN) codes has been reproduced as a new Annex ZD.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the annex to which they apply. A normative annex is an integral part of a Standard, whereas an informative annex is only for information and guidance.

CONTENTS

	<i>Page</i>
INTRODUCTION.....	v
1 Scope	1
2 Normative references	2
3 Performance requirements.....	3
3.1 Compliance.....	3
3.2 General	3
3.3 Operational.....	4
3.4 Distress function	6
3.5 Float-free arrangements.....	6
3.6 Environment	7
3.7 Environment for float-free arrangement.	7
3.8 Interference – electromagnetic compatibility	8
3.9 Maintenance	8
3.10 Safety precautions	8
A3 3.11 User equipment manuals.....	8
3.12 Labelling.....	10
3.13 Installation	11
4 Technical characteristics	11
4.1 Transmitted frequency	11
4.2 Signal and message format.....	12
4.3 Distress message memory	12
4.4 Beacon identification code	12
4.5 121,5 MHz homing signal.....	12
4.6 Power source.....	12
4.7 Antenna characteristics (C/S T.001)	13
5 Methods of testing and required test results	13
5.1 General	13
5.2 General tests	15
5.3 Operational tests	16
5.4 Distress function	18
5.5 Float-free arrangements.....	18
5.6 Environment	19
5.7 Maintenance	20
5.8 Safety precautions	20
A3 5.9 User equipment manuals.....	20
5.10 Labelling.....	20
5.11 Installation	20
5.12 Power source.....	20
5.13 Environment	21

5.14	Interference testing	22
5.15	Spurious emissions	22
5.16	Compass safe distance	23
5.17	Conducted interference	23
Annex A (normative) Sequence of tests		24
A.1	Compulsory sequence of tests	24
A.2	Additional tests	24
Annex B (normative) List of COSPAS-SARSAT tests		26
B.1	Power output	26
B.2	Digital message	26
B.3	Digital message generator.....	26
B.4	Modulation.....	26
B.5	406 MHz transmitted frequency	27
B.6	Spurious emissions (into 50 Ω).....	27
B.7	406 MHz VSWR check	27
B.8	Self-test mode	27
B.9	Thermal shock (30 °C change).....	27
B.10	Operating lifetime at minimum temperature.....	28
B.11	Temperature gradient (5 °C/h)	28
B.12	Long-term frequency stability	28
B.13	Protection against continuous transmission	28
B.14	Satellite qualitative tests	28
B.15	Antenna characteristics	28
B.16	Beacon coding software	29
B.17	Navigation system.....	29
Annex C (normative) Standard for a manually activated satellite EPIRB without a float-free mechanism		30
C.1	Requirements	30
Annex D (normative) Technical standard for 121,5 MHz homing device.....		31
D.1	General	31
D.2	Performance requirements	31
D.3	Technical characteristics.....	31
D.4	Methods of testing and required test results.....	32
Annex E (informative) User experience of COSPAS-SARSAT EPIRB operation		38
Annex ZA (informative) Procurement of COSPAS-SARSAT documents.....		39
Annex ZB (normative) National registration authorities		40
Annex ZC (normative) Sample beacon registration cards		41
Annex ZD (informative) NOAA calculations of checksums for 15-character hexadecimal id (UIN) codes		42

INTRODUCTION

This revision of IEC 61097-2 is due to changes to the Radio Regulations, COSPAS-SARSAT requirements and amendments to the IMO performance standards for 406 MHz Satellite emergency position indicating radio beacons (EPIRBs).

The document has been renumbered and rearranged to comply in certain aspects with ISO/IEC Directives, and the requirements have been regrouped in a more logical order.

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard**406 MHz satellite distress beacons****Part 1: Marine emergency position-indicating radio beacons (EPIRB)
(IEC 61097-2:2002, MOD)**

Any table, figure or text of the international standard that is struck through is not part of this standard. Any Australian/New Zealand table, figure or text that is added is part of this standard and is identified by shading.

1 Scope

This part of IEC 61097 specifies the minimum performance requirements, technical characteristics and type-testing requirements of the satellite emergency position-indicating radio beacon used in the COSPAS-SARSAT satellite system (satellite EPIRB), as required by Regulation IV/7.1.6 of the 1988 amendments to the 1974 International Convention for Safety of Life at Sea (SOLAS), and which is associated with IEC 60945 (General requirements). When a requirement in this standard is different from IEC 60945, the requirement in this standard shall take precedence.

This standard also includes minimum performance standards for a manually activated satellite EPIRB without float-free release mechanism (see annex C).

This standard incorporates the performance standards of IMO Resolutions A.810(19) *Performance Standards for float-free satellite emergency position-indicating radio beacons (EPIRBs) operating on 406 MHz* and A.662(16) *Performance Standards for float-free release and activation arrangements for emergency radio equipment*, the International Telecommunication Union (ITU) Radio Regulations as well as the technical characteristics for such transmitters contained in Recommendation ITU-R M.633 (as amended), and takes account of the general requirements contained in IMO Resolution A.694(17).

All texts of this standard, whose wording is identical to that in the IMO SOLAS Convention 1974 as amended in 1988 and Resolutions A.658(16), A.662(16), A.689(17), A.694(17), A.696(17), A.702(17) and A.810(19) and Recommendation ITU-R M.633 (as amended) will be printed in italics and the Resolution/Recommendation and paragraph number indicated between brackets.

NOTE 1 Classes of satellite EPIRB's considered in this document are:

– Class 1: Float-free (–40°C to +55°C). The float-free release mechanism (A.662(16)) should be capable of operating throughout the temperature range of –40°C to +65°C.

This class is not required by IMO Resolutions but may be applied at the discretion of each Administration.

– Class 2: Float-free (–20°C to +55°C). The float-free release mechanism (A.662(16)) should be *capable of operating throughout the temperature range of –30°C to +65°C*.

– Class 3: Manually activated, non float free (–20°C to +55°C). Primarily intended for use by NON-SOLAS vessels.

NOTE 2 Non-float-free, manually activated satellite EPIRB's in all classes are considered in annex C.

NOTE 3 All classes shall include a 121,5 MHz homing device, described in annex D.

User experience of COSPAS-SARSAT EPIRB operation leading to some clarification of IMO performance standards, and providing some useful information for satellite EPIRB users is included in annex E.