

Australian Standard<sup>®</sup>

**Measurement of water flow in open  
channels**

**Method 4.3: Measurement using flow  
gauging structures—Round-nose  
horizontal broad-crested weirs**



This Australian Standard® was prepared by Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 12 July 1991.  
This Standard was published on 23 September 1991.

---

The following are represented on Committee CE-024:

- Association of Consulting Engineers, Australia
  - Australian Water and Wastewater Association
  - Board of Works, Melbourne
  - Department of Water Resources, N.S.W.
  - Engineering and Water Supply Department of South Australia
  - Forestry Commission, N.S.W.
  - Institute of Instrumentation and Control
  - Monash University
  - Snowy Mountains Engineering Corporation
  - University of New South Wales
  - University of Queensland
  - Water Authority of Western Australia
  - Water Board, Sydney—Illawarra—Blue Mountains
  - Water Resources Commission, Queensland
- 

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee.

---

### **Keeping Standards up-to-date**

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting **[www.standards.org.au](http://www.standards.org.au)**

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at **[mail@standards.org.au](mailto:mail@standards.org.au)**, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

---

STANDARDS AUSTRALIA

---

**RECONFIRMATION**

**OF**

**AS 3778.4.3—1991**

**Measurement of water flow in open channels  
Method 4.3: Measurement using flow gauging structures  
—Round-nose horizontal broad-crested weirs**

---

**RECONFIRMATION NOTICE**

Technical Committee CE-024 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 28 November 2019.

The following are represented on Technical Committee CE-024:

Australian Bureau of Meteorology  
Australian Hydrographers Association  
Australian Industry Group  
Institute of Instrumentation, Control & Automation  
Irrigation Australia Limited  
National Measurement Institute  
Office of Finance & Services (NSW)

## NOTES

Australian Standard<sup>®</sup>

**Measurement of water flow in open  
channels**

**Method 4.3: Measurement using flow  
gauging structures—Round-nose  
horizontal broad-crested weirs**

First published as AS 3778.4.3—1991.  
Reconfirmed 2009.

**COPYRIGHT**

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia  
ISBN 0 7262 7061 X

## PREFACE

This Standard was prepared by the Standards Australia Committee on Measurement of Water Flow in Open Channels and Closed Conduits. It is identical with and has been reproduced from ISO 4374:1990, *Liquid flow measurement in open channels—Round-nose horizontal broad-crested weirs*.

Under arrangements made between Standards Australia and the International Standards Bodies, ISO and IEC, as well as certain other Standards organizations, users of this Australian Standard are advised of the following:

- (a) Copyright is vested in Standards Australia.
- (b) The number of this Standard is not reproduced on each page; its identity is shown only on the cover and title pages.
- (c) There may be occasional dual language sections, but English is always one of the languages reproduced.
- (d) Where any cross-references to page numbers appear within the text, these relate to page numbering in the International Standard and are to be disregarded.

This Standard is one of a series which deals with methods of measurement of water flow in open channels. The series when complete will consist of the following parts:

- Part 1: *Vocabulary and symbols*
- Part 2.1: *General—Guidelines for the selection of methods of measurement*
- Part 2.2: *General—Establishment and operation of a gauging station*
- Part 2.3: *General—Determination of the stage-discharge relation*
- Part 2.4: *General—Estimation of uncertainty of a flow-rate measurement*
- Part 2.5: *General—Guidelines for the selection of flow gauging structures*
- Part 3: *Velocity-area methods*
- Method 3.1: *Measurement by current-meters and floats*
- Method 3.2: *Measurement by moving-boat method*
- Method 3.3: *Measurement by slope-area method*
- Method 3.4: *Collection and processing of data for determination of errors in measurement*
- Method 3.5: *Investigation of total error*
- Method 3.6: *Measurement of flow in tidal channels*
- Method 3.7: *Measurement by ultrasonic (acoustic) method*
- Method 3.8: *Electromagnetic method using a full-channel-width coil*
- Part 4: *Measurement using flow gauging structures*
- Method 4.1: *Thin-plate weirs*
- Method 4.2: *Rectangular broad-crested weirs*
- Method 4.3: *Round-nose horizontal broad-crested weirs (this Standard)*
- Method 4.4: *V-shaped broad-crested weirs*
- Method 4.5: *Triangular profile weirs*
- Method 4.6: *Flat-V weirs*
- Method 4.7: *Rectangular, trapezoidal and U-shaped flumes*
- Method 4.8: *Trapezoidal profile weirs*
- Method 4.9: *Parshall and Saniiri flumes*
- Method 4.10: *End-depth method for estimation of flow in rectangular channels with a free overfall*
- Method 4.11: *End-depth method for estimation of flow in non-rectangular channels with a free overfall (approximate method)*
- Part 5: *Dilution methods*
- Method 5.1: *Constant-rate injection method for the measurement of steady flow*
- Method 5.2: *Integration method for the measurement of steady flow*
- Part 6.1: *Measuring devices, instruments and equipment—Rotating element current-meters*
- Part 6.2: *Measuring devices, instruments and equipment—Direct depth sounding and suspension equipment*
- Part 6.3: *Measuring devices, instruments and equipment—Calibration of rotating element current-meters in straight open tanks*
- Part 6.4: *Measuring devices, instruments and equipment—Echo sounders for water depth measurements*
- Part 6.5: *Measuring devices, instruments and equipment—Water level measuring devices*
- Part 6.6: *Measuring devices, instruments and equipment—Cableway system for stream gauging*
- Part 6.7: *Measuring devices, instruments and equipment—Ultrasonic (acoustic) velocity meters*
- Part 6.8: *Measuring devices, instruments and equipment—Position fixing equipment for hydrometric boats*

For the purposes of this Australian Standard, the ISO text should be modified as follows:

- (i) Wherever the words 'International Standard' appear, referring to this Standard, they should be read as 'Australian Standard'.
- (ii) Wherever the word 'fluid' appears, it should be read as 'water'.
- (iii) Substitute a full point (.) for a comma (,) as a decimal marker.
- (iv) The references to other publications should be replaced by references to Australian Standards as follows:

| <i>Reference to International Standard</i>  | <i>Australian Standard</i>  |
|---|---|
| ISO   | AS  |
|   | 3778 Measurement of water flow in open channels                                 |
| 772 Liquid flow measurement in open channels—Vocabulary and symbols                 | 3778.1 Part 1: Vocabulary and symbols   |
| 5168 Measurement of fluid flow—Estimation of uncertainty of a flow-rate measurement | 3778.2.4 Part 2.4: General—Estimation of uncertainty of a flow-rate measurement |

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

# Measurement of water flow in open channels

## Part 4: Measurement using flow gauging structures

### Method 4.3: Round-nose horizontal broad-crested weirs

#### 1 Scope

**1.1** This International Standard deals with the measurement of flow in rivers and artificial channels under steady flow conditions using round-nose horizontal broad-crested weirs (see figures 1 and 2).

**1.2** The flow conditions considered are limited to steady flows which are uniquely dependent on the upstream head. Drowned flows, which depend on downstream as well as upstream levels, are not covered by this International Standard.

**1.3** The round-nose horizontal broad-crested weir has a good discharge range and modular limit and is appropriate for use in small- and medium-sized installations. It is particularly robust and insensitive to minor damage.

#### 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 772: 1988, *Liquid flow measurement in open channels — Vocabulary and symbols*.

ISO 5168: 1978, *Measurement of fluid flow — Estimation of uncertainty of a flow-rate measurement*.

#### 3 Definitions and symbols

For the purposes of this International Standard, the definitions given in ISO 772 apply. A full list of symbols with the corresponding units of measurement is given in annex A.

#### 4 Installation

##### 4.1 Selection of site

**4.1.1** The weir shall be located in a straight section of channel, avoiding local obstructions, roughness or unevenness of the bed.

**4.1.2** A preliminary study shall be made of the physical and hydraulic features of the proposed site, to check that it conforms (or can be made to conform) to the requirements necessary for measurement of discharge by the weir. Particular attention should be paid to the following features in selecting the site:

- a) the adequacy of the length of channel of regular cross-section available (see 4.2.2.2);
- b) the uniformity of the existing velocity distribution (see annex B);
- c) the avoidance of a steep channel (but see 4.2.2.6);
- d) the effects of any increased upstream water level due to the measuring structure;
- e) the conditions downstream (including influences such as tides, confluences with other streams, sluice gates, mill dams and other controlling features which might cause drowning);
- f) the impermeability of the ground on which the structure is to be founded and the necessity for piling, grouting or other means of controlling seepage;
- g) the necessity for flood banks, to confine the maximum discharge to the channel;
- h) the stability of the banks, and the necessity for trimming and/or revetment in natural channels;
- i) the uniformity of the cross-section of the approach channel;
- j) the prevailing wind, which can have a considerable effect on the flow in a river, or over a weir or flume, especially when the river, weir or flume is wide and the head is small and when the prevailing wind is in a transverse direction;
- k) aquatic weed growth;
- l) sediment transportation.

**4.1.3** If the site does not possess the characteristics necessary for satisfactory measurements, or if an inspection of the stream shows that the velocity distribution in the approach channel deviates appreciably from the examples described in annex B, the site shall not be used unless suitable improvements are practicable. Alternatively, the performance of the installation may be checked by independent flow measurements.