

Under Revision See DR 93275
Superseded by AS 3610-1995

AS 3610—1990

Australian Standard®

Formwork for concrete



This Australian Standard was prepared by Committee BD/43, Formwork. It was approved on behalf of the Council of Standards Australia on 20 October 1989 and published on 9 April 1990.

The following interests are represented on Committee BD/43:

Aluminium Development Council
Association of Consulting Engineers, Australia.
Australian Federation of Construction Contractors
Australian Precast Concrete Manufacturers Association
Austroads
Cement and Concrete Association of Australia
CSIRO, Division of Building, Construction and Engineering
Department of Employment, Vocational Education, Training and Industrial Relations, Qld.
Department of Occupational Health Safety and Welfare, W.A.
Formwork Contractors of Western Australia
Master Builders Construction and Housing Association Australia
Metal Trades Industry Association of Australia
Plywood Association of Australia Ltd
Precast Concrete Manufacturers Association of New South Wales
Public Works Department New South Wales
Queensland University of Technology
Workcover Authority New South Wales

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 86123. (in part)

Australian Standard®

Formwork for concrete

✓
For history before 1989 see Preface.
AS 1509—1974, 1510.1—1974 and AS 1082—1971
revised, amalgamated and redesignated
AS 3610—1990.

PREFACE

This Standard was prepared by the Standards Australia Committee on Formwork as a replacement for AS 1509—1974, *SAA Formwork Code—Metric*, AS 1510 *Code of Practice for Control of Concrete Surfaces, Part 1—1974: Formwork* and AS 1082—1971 *Glossary of Formwork Terms*. AS 1509, and AS 1510.1 were both first published in 1971 as AS CA 70 and AS CA 72.1 respectively.

Being the product of a review of three current Standards, this edition is a totally new document and its arrangement bears no resemblance to that of its predecessors. Care has been taken to group in specific sections the requirements that are relevant to specific parties, namely the project designer (Sections 2 and 3), the formwork designer (Section 4), those involved in the erection and supervision of formwork on site, and those matters related to the evaluation of completed work and repairs (Section 5).

Where mandatory notes to tables are used in this Standard, they are deemed to form an integral part of the Standard.

Photographic charts for the assessment of colour and surface finish are provided in the Appendices. Additional copies of these charts are available as AS 3610, Supplement 1.

AS 3610 Supplement 2 provides a commentary on this Standard. The commentary includes background information on the Standard, guidance on its use, and suggestions on good practice.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the Head Office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SECTION 1 GENERAL	
1.1 SCOPE	4
1.2 APPLICATION	4
1.3 REFERENCED DOCUMENTS	4
1.4 NEW MATERIALS OR METHODS	4
1.5 DEFINITIONS	4
1.6 NOTATION	6
SECTION 2 THE PROJECT DOCUMENTATION	
2.1 SCOPE OF SECTION	8
2.2 GENERAL	8
2.3 INFORMATION TO BE PROVIDED IN THE PROJECT DOCUMENTATION	8
SECTION 3 SURFACE FINISH	
3.1 SCOPE OF SECTION	9
3.2 APPLICATION OF SECTION	9
3.3 CLASSES OF SURFACE FINISH	9
3.4 PHYSICAL QUALITY	9
3.5 COLOUR CONTROL OF UNTREATED SURFACES	15
3.6 TEST PANELS	15
SECTION 4 STRUCTURAL DESIGN AND DOCUMENTATION	
4.1 SCOPE OF SECTION	16
4.2 APPLICATION OF SECTION	16
4.3 DESIGN REQUIREMENTS	16
4.4 LOADS	16
4.5 ANALYSIS AND DESIGN	21
4.6 CONSTRUCTION CONSIDERATIONS	25
4.7 FORMWORK DOCUMENTATION	26
SECTION 5 CONSTRUCTION	
5.1 SCOPE OF SECTION	27
5.2 APPLICATION OF SECTION	27
5.3 GENERAL FORMWORK REQUIREMENTS— <i>IN SITU</i> CONCRETE	27
5.4 FORMWORK CONSTRUCTION— <i>IN SITU</i> CONCRETE	30
5.5 FORMWORK CONSTRUCTION—PRECAST CONCRETE	31
5.6 EVALUATION OF COMPLETED WORK AND REPAIRS	31
APPENDICES	
A TESTING OF FORMWORK	36
B BLOWHOLE AND COLOUR EVALUATION CHARTS	42

STANDARDS AUSTRALIA

Australian Standard
Formwork for concrete

SECTION 1. GENERAL

1.1 SCOPE. This Standard sets out requirements for the design, fabrication, erection and stripping of formwork, as well as the specification, evaluation and repair of the quality of the formed concrete surface and the influence of this activity on the design and construction of an *in situ* concrete structure. Design by testing is considered separately, the requirements being set out in Appendix A. Some Sections of the Standard are also applicable to precast concrete, in particular some aspects of Sections 3 and 5.

This Standard does not apply to unformed concrete surfaces, eg tops of slabs.

1.2 APPLICATION. Formwork requirements in the project documentation shall comply with Section 2. The concrete surface finish shall comply with Section 3. The structural design of formwork shall comply with Section 4. The procedures to be followed in construction, checking the completed work and carrying out repairs shall be in accordance with Section 5.

1.3 REFERENCED DOCUMENTS. The documents below are referred to in this Standard:

AS

- 1170 SAA Loading Code
- 1170.2 Part 2: Wind loads
- 1250 SAA Steel Structures Code
- 1315 Portland cement
- 1317 Blended cement
- 1575 Tubes, couplers and accessories used in metal scaffolding
- 1576 SAA Metal Scaffolding Code
- 1657 SAA Code for Fixed Platforms, Walkways, Stairways and Ladders
- 1664 SAA Aluminium structures code
- 1720 SAA Timber Structures Code
- 2082 Visually stress-graded hardwood for structural purposes
- 2121 SAA Earthquake Code
- 2269 Structural plywood
- 2271 Plywood and blockboard for exterior use
- 2327 Composite construction in structural steel and concrete
- 2858 Timber—Softwood—Visually stress-graded for structural purposes
- 3600 SAA Concrete Structures Code
- 3700 SAA Masonry Code

BS

- 5975 Code of practice for falsework.

CIRIA Concrete Pressure on Formwork (published Report 108 by the Construction Industry Research and Information Association (UK)).

1.4 NEW MATERIALS OR METHODS. Provided the requirements of this Standard are met, this Standard shall not be interpreted to prevent the use of materials or methods of design or construction not specifically referred to herein.

1.5 DEFINITIONS. For the purpose of this Standard, the definitions below apply:

1.5.1 Administrative definitions.

Engineer—a person qualified for Corporate Membership of the Institution of Engineers, Australia, and with experience in the area of formwork.

NOTE: The definition of 'Engineer' does not require that an Engineer be a Corporate Member of the Institution of Engineers, Australia.

Formwork documentation—drawings, specifications, brochures and associated documents that describe the formwork assembly to be erected.

May—indicates a practice which complies with the requirements of this Standard.

Project documentation—drawings, specifications and associated documents that describe the permanent structure to be constructed.

Regulatory Authority—a body having statutory powers to control the design and erection of the formwork.

Shall—indicates a mandatory statement to be adopted in order to comply with this Standard.

1.5.2 Technical definitions.

Adjustable prop (also called 'telescopic prop')—a prop (see 'prop') capable of coarse and fine adjustment of its overall length.

Backpropping—process by which adjustable supports are placed to give support to the permanent structure during the removal of the formwork to the soffit. (See Figure 1.5.1.)

Bearing area—effective area over which a force is transferred to a supporting structural system.

Blowhole—indentation in the formed surface of the concrete caused by a bubble of fluid or air trapped against the form surface.

Bracing—secondary structural members which normally do not support gravity loads but are required to provide lateral stability to other structural members or to transfer horizontal loads to supports.

Camber—the intentional curvature of formwork prior to concrete placement to compensate for the deflection of the formwork or the permanent structure under load.

Cast-in situ concrete—concrete which is placed, as plastic concrete, in its final location as part of the permanent structure.

Class of surface finish (or 'Class')—Standard of the untreated concrete surface of the formed concrete.