

Australian Standard™

Environmental testing

**Part 2.39: Tests—Test Z/AMD:
Combined sequential cold, low air
pressure and damp heat test**

This Australian Standard was prepared by Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic Equipment. It was approved on behalf of the Council of Standards Australia on 21 October 2003 and published on 1 December 2003.

The following are represented on Committee EL-026:

Australian Chamber of Commerce and Industry
Australian Electrical and Electronic Manufacturer's Association
Electrical Compliance Testing Association
Electrical Regulatory Authorities Council
Electricity Supply Association of Australia
Testing Interests (Australia)

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

Environmental testing

Part 2.39: Tests—Test Z/AMD: Combined sequential cold, low air pressure and damp heat test

Originated as AS 1099.2Z/AMD—1980.
Revised and redesignated as AS 60068.2.39—2003.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5613 1

PREFACE

This Standard was prepared by the Standards Australia Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic Equipment to supersede AS 1099.2Z/AMD, *Basic environmental testing procedures for electrotechnology*, Part 2Z/AMD: *Tests—Test Z/AMD—Combined sequential cold, low air pressure and damp heat test*.

The objective of this Standard is to provide the electrotechnology industry with a complete set of environmental test procedures published as a series under AS 60068 *Environmental testing*. This Standard is Part 2.39 of that series.

This Standard is identical with, and has been reproduced from, IEC 60068-2-39:1976, *Environmental testing – Part 2-39: Tests—Test Z/AMD: Combined sequential cold, low air pressure and damp heat test*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (b) In the source text ‘this international standard’ should read ‘this Australian Standard’.
- (c) A full point should be substituted for a comma when referring to a decimal marker.
- (d) any French text on figures should be ignored.

In this Standard, the following print types are used:

- requirements proper: in arial type;
- *test specifications: in italic type;*
- explanatory matter: in smaller arial type.

Any international Standard referenced should be replaced by an equivalent Australian Standard when one is available. The availability of equivalent Australian Standards can be determined either from the Standards Australia catalogue or from the Standards Australia website (www.standards.com.au).

CONTENTS

	<i>Page</i>
1 Object	1
2 General description of the test.....	1
3 Description of test apparatus	1
4 Testing procedure	2
5 Preconditioning	2
6 Initial measurements	2
7 Conditioning	2
8 Recovery.....	3
9 Final measurements	3
10 Information to be given in the relevant specification	3

STANDARDS AUSTRALIA

Australian Standard**Environmental testing****Part 2.39: Tests—Test Z/AMD: Combined sequential cold,
low air pressure and damp heat test**

1 Object

To provide a standard environmental test procedure consisting of the application of cold, low air pressure and damp heat; the first two conditions in combination and the second condition combining with the third during the sequential transition from the first. The tests employed are Test A and Test M, but although introduction of moisture is not exactly in accordance with Test D, this letter has been used in the identification Z/AMD as being the most appropriate and informative.

The test is intended for components and equipment used in aircraft, particularly in zones that are unheated and unpressurized.

2 General description of the test

The test simulates the conditions encountered within unpressurized and non-temperature-controlled zones of an aircraft during ascent and descent. A non-heat-dissipating component that incorporates elastomeric seals (such as a plug-and-socket connector) will experience hardening of the seals and contraction of materials as it becomes cold, and may suffer failure of such seals, with consequent loss of internal pressure, as the surrounding air pressure decreases. When the aircraft descends into a humid atmosphere and the air pressure increases again, the cold component suffers frosting and the humid atmosphere itself, or free water formed by the melting of the frost, may be driven into the component by the differential pressure and be trapped inside by the seals as they recover their normal elasticity. The same sequence may cause water or ice to accumulate inside a piece of equipment with an unsealed but closely fitting cover and no drain holes.

3 Description of test apparatus

3.1 The test chamber must be capable of subjecting the specimen to simultaneous low temperature and low pressure within the range of severities prescribed by Test A and Test M respectively. It must incorporate heaters that can raise the ambient temperature within the chamber from the extreme cold condition to between 30 °C and 35 °C in a period of not more than 1 h. It must also incorporate means of admitting water vapour to, or generating water vapour within, the working space containing the specimen during the time that the temperature is being raised, while at the same time maintaining a substantially constant low air pressure.

3.2 As the test is concerned with the ingress of moisture and as this is frequently detected by a lowering of insulation resistance, leads to the specimen shall be taken through the chamber wall without break or junction and through pressure-tight seals. The leads themselves must be of appropriate size and insulation for sealing to the specimen.

3.3 If the specimen contains moving parts, the movement of which may be prevented by the formation of ice inside the specimen, means must be provided in the chamber for monitoring such movement either mechanically or electrically.