

Australian Standard™

Environmental testing

**Part 2.45: Tests—Test XA and guidance:
Immersion in cleaning solvents**

This Australian Standard was prepared by Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic Equipment. It was approved on behalf of the Council of Standards Australia on 21 October 2003 and published on 1 December 2003.

The following are represented on Committee EL-026:

Australian Chamber of Commerce and Industry
Australian Electrical and Electronic Manufacturer's Association
Electrical Compliance Testing Association
Electrical Regulatory Authorities Council
Electricity Supply Association of Australia
Testing Interests (Australia)

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

Environmental testing

**Part 2.45: Tests—Test XA and guidance:
Immersion in cleaning solvents**

First published as AS 60068.2.45—2003.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5617 4

PREFACE

This Standard was prepared by the Standards Australia Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic Equipment.

The objective of this Standard is to provide the electrotechnology industry with a complete set of environmental test procedures published as a series under AS 60068 *Environmental testing*. This Standard is Part 2.45 of that series.

This Standard is identical with, and has been reproduced from, IEC 60068-2-45:1980, *Environmental testing – Part 2-45: Tests—Test XA and guidance: Immersion in cleaning solvents* including Amendment 1:1993 and Corrigendum 1:1981.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (b) In the source text ‘this international standard’ should read ‘this Australian Standard’.
- (c) A full point should be substituted for a comma when referring to a decimal marker.
- (d) any French text on figures should be ignored.

In this Standard, the following print types are used:

- requirements proper: in arial type;
- *test specifications: in italic type;*
- explanatory matter: in smaller arial type.

Any international Standard referenced should be replaced by an equivalent Australian Standard when one is available. The availability of equivalent Australian Standards can be determined either from the Standards Australia catalogue or from the Standards Australia website (www.standards.com.au).

CONTENTS

	<i>Page</i>
1 Scope	1
2 Object	1
3 Types of test solvents and conditions	1
4 Initial measurements	2
5 Conditioning	2
6 Recovery	3
7 Final measurements	3
8 Information to be given in the relevant specification	3
Annex A Guide to Test XA	4
Annex B Suitable apparatus for boiling solvent test	7

STANDARDS AUSTRALIA

Australian Standard**Environmental testing**
Part 2.45: Tests—Test XA and guidance:
Immersion in cleaning solvents

1 Scope

This standard comprises a test procedure whereby specimens to be tested are immersed in a certain solvent at a specified temperature and for a specified time.

If required by the relevant specification, after immersion and drying, specimens shall be rubbed with cotton wool or wrapping tissue paper.

Guidance on the test is given in the annex.

2 Object

To determine the effects of prescribed cleaning solvents on electronic components and other parts suitable to be mounted on printed boards when subjected to immersion in the cleaning solvents stated below.

NOTE – This test is not intended to simulate the effects of handling.

3 Types of test solvents and conditions**3.1 Solvents**

Three commonly used solvents are specified for the purpose of this test.

NOTE – Successful compliance with this test does not imply resistance to other solvents.

3.1.1 A mixture of 1,1,2-trichlorotrifluoroethane, 70 ± 5 % by weight and 2-propanol (isopropyl alcohol), 30 ± 5 % by weight. Commercially available grades (industrial use) shall be used.

NOTES

- 1 1,1,2-trichlorotrifluoroethane will be hereinafter referred to as R 113, in accordance with ISO/ R 817.
- 2 The above mixture is obtainable as a finished product from suppliers of chemicals.

Warning: the component 1,1,2-trichlorotrifluoroethane is hazardous to the environment; therefore this solvent shall not be used where the solvent specified in 3.1.2 is adequate.

3.1.2 Propan-2-ol (isopropyl alcohol) – industrial use – shall be used whenever possible.

NOTE – This solvent is obtainable as a finished product from suppliers of chemicals.

3.1.3 Demineralized or distilled water having a resistivity of not less than $500 \Omega\text{m}$ corresponding to a conductivity of 2 mS/m .

NOTE – In technically justified cases other solvents similar in activity to the recommended ones may be used as prescribed in the relevant specifications.