

Australian/New Zealand Standard™

**Technical systems and aids for people
with disability—Wheelchair tiedown and
occupant-restraint systems**

**Part 1: Requirements and test methods
for all systems (ISO 10542-1:2012, MOD)**



AS/NZS 10542.1:2015

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee ME-067, Assistive Technology Products for Persons with Disability. It was approved on behalf of the Council of Standards Australia on 25 September 2015 and on behalf of the Council of Standards New Zealand on 10 September 2015.

This Standard was published on 16 October 2015.

The following are represented on Committee ME-067:

Assistive Technology Suppliers Australia
Association of Consultants in Access Australia
Australian Rehabilitation and Assistive Technology Association
Bus and Coach Association of New Zealand
Consumers' Federation of Australia
Department of Communities and Social Inclusion, SA
Engineers Australia
Independent Living Centre Australia
Medical Aids Subsidy Scheme
New Zealand Transport Agency
Novita Children's Services
Occupational Therapy Australia
Physical Disability Australia
Royal Perth Hospital
TAD Australia
The Commercial Vehicle Industry Association of Australia
Therapeutic Goods Administration

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

This Standard was issued in draft form for comment as DR AS/NZS ISO 10542.1.

Australian/New Zealand Standard™

Technical systems and aids for people with disability—Wheelchair tiedown and occupant-restraint systems

Part 1: Requirements and test methods for all systems (ISO 10542-1:2012, MOD)

Originated in Australia in part as AS 2942—1967.
Previous and first joint editions AS/NZS 10542.1:2009 and AS/NZS 10542.2:2009.
Jointly revised, amalgamated and designated as AS/NZS 10542.1:2015.

COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140.

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee ME-067, Assistive Technology Products for Persons with Disability, to supersede AS/NZS 10542.1:2009, *Technical systems and aids for disabled or handicapped persons—Wheelchair tiedown and occupant-restraint systems, Part 1: Requirements and test methods for all systems*, and AS/NZS 10542.2:2009, *Technical systems and aids for disabled or handicapped persons—Wheelchair tiedown and occupant-restraint systems, Part 2: Four-point strap-type tiedown systems*.

The objective of this Standard to specify design and performance requirements and associated test methods for wheelchair tiedown and occupant-restraint systems (WTORS), as well as requirements for product marking and labelling, and manufacturers' instructions and warnings to installers and consumers. It is applicable to all WTORS that use belt-type occupant restraints that are intended for occupied wheelchairs used as forward facing seats by passengers and drivers of motor vehicles.

This Standard is an adoption with national modifications and has been reproduced from ISO 10542-1:2012, *Technical systems and aids for disabled or handicapped persons—Wheelchair tiedown and occupant-restraint systems, Part 1: Requirements and test methods for all systems*, and its Corrigendum No.1 (2013), which is located at the end of the source text. The source document has been varied as indicated to take account of Australian/New Zealand conditions. The modifications are specified in Appendix ZZ and Appendix ZA. Response from consumers and industry has called for changes to AS/NZS 10542.1 to better describe the above-the-head clear space requirements (addressed in Appendix ZZ) and vehicle anchorage point requirements and occupant restraint upper anchorage points (addressed in Appendix ZA).

Clear space requirements shown in Figure 6 are modified to include a seated head height (HHT). The original Figure 6 could be interpreted as requiring the clear space to be equivalent to HHT, level with the top of the occupant's head. This figure has been modified to change this and now also includes a wheelchair with a headrest, which is consistent with best practice guidelines.

The 1550 mm minimum dimension is consistent with the '*Disability Standards for Accessible Public Transport 2002*' requirements for access to accessible taxis (Clause 12.4).

The modifications contained in Appendix ZA set out minimum requirements for vehicle anchorage points consistent with Australian Design Rules, and the occupant restraint upper anchorage points. The specifications for occupant restraint upper anchorage points are provided as informative guidance in ISO 10524-1, Annex H, but are made normative in Appendix ZA.

As this Standard is reproduced from an International Standard, the following applies:

- (a) In the source text 'this part of ISO 10542' should read 'this Australian/New Zealand Standard'.
- (b) A full point substitutes for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to Australian or Australian/New Zealand Standards, as follows:

<i>Reference to International Standard</i>	<i>Australian/New Zealand Standard</i>
ISO	AS/NZS
7176 Wheelchairs	3696 Wheelchairs
7176-19 Part 19: Wheeled mobility devices for use as seats in motor vehicles	3696.19 Part 19: Wheeled mobility devices for use as seats in motor vehicles (ISO 7176-19:2008, MOD)

Only normative references that have been adopted as Australian or Australian/New Zealand Standard have been listed.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the annex or appendix to which they apply. A ‘normative’ annex or appendix is an integral part of a Standard, whereas an ‘informative’ annex or appendix is only for information and guidance.

CONTENTS

1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Design requirements	6
4.1	WTORS	6
4.2	Wheelchair tiedowns	7
4.3	Wheelchair securement adaptors	9
4.4	Occupant restraints	10
5	Performance requirements	11
5.1	WTORS components	11
5.2	Frontal impact requirements	13
5.3	Webbing slippage at tiedown adjustment devices	14
5.4	Partial engagement of anchorage and securement components	14
5.5	Linear and rotational wheelchair movement	14
6	Identification, labelling, instruction and warning requirements	14
6.1	Identification and labelling	14
6.2	Instructions for installers	15
6.3	User and maintenance instructions	19
6.4	Instructions for replacement parts and accessory WTORS components and subassemblies (when sold separately)	22
7	Test reports	22
	Annex A (normative) Test method for frontal impact	25
	Annex B (normative) Measurement of WTORS belt lengths and geometry	33
	Annex C (normative) Test for webbing slippage at manual adjustment devices of wheelchair tiedown straps	37
	Annex D (normative) Test method for partial engagement	39
	Annex E (normative) Surrogate wheelchair specifications	41
	Annex F (informative) Specifications for the universal docking interface geometry (UDIG)	46
	Annex G (informative) Tests for movement of wheelchairs secured by docking tiedown devices	51
	Annex H (informative) Recommendations for design, performance and documentation	57
	Annex I (informative) Recommendations for securement point locations on wheelchairs and adjustment lengths of strap assemblies	64
	Annex J (informative) Information sources	66
	Bibliography	68

INTRODUCTION

Many wheelchair users remain in their wheelchairs during motor-vehicle transport and hence their wheelchair serves as a vehicle seat. This usually means that the occupant restraint system installed by the vehicle manufacturer cannot be used to provide protection in a crash. In addition, the wheelchair needs to be secured to the vehicle so that it does not impose forces on its occupant and/or become a hazard to other vehicle occupants in collisions or sudden vehicle manoeuvres. Providing safe transportation for wheelchair-seated occupants therefore requires that equipment be used to provide effective wheelchair securement and occupant restraint.

This part of ISO 10542 applies to the design, testing, installation and use of wheelchair tiedown and occupant restraint systems (WTORS) used by forward-facing wheelchair-seated occupants. Transportation-related requirements for wheelchairs that are suitable for forward-facing occupant seating during motor vehicle transportation are specified in ISO 7176-19.

The primary purpose of this part of ISO 10542 is to reduce the risk of serious injuries to wheelchair-seated occupants involved in frontal collisions and it is anticipated that additional parts of ISO 10542 will be developed to address different impact conditions and directions. However, it can be expected that the proper use of equipment that complies with this part of ISO 10542 will also reduce the risk of injury in other types of crashes, as well as in vehicle rollovers, emergency vehicle manoeuvres, and normal operating conditions.

The provisions of this part of ISO 10542 are based on the premise that WTORS manufacturers are generally not able to control the end use of their products. This part of ISO 10542 therefore requires that WTORS intended for general use in all types and sizes of motor vehicles are dynamically tested for crashworthiness performance in a nominally worst-case 48 km/h, 20 g frontal sled impact test using an 85 kg surrogate wheelchair (SWC) and a midsize adult male anthropomorphic test device (ATD) to dynamically load the WTORS.

Although the forces on WTORS components in a small percentage of real-world crash events may exceed those produced in the nominally worst-case frontal-impact test in this part of ISO 10542 due to a number of factors, including higher crash severities, angled frontal impacts, a higher wheelchair mass, and a higher occupant mass, there is currently no evidence of any WTORS system or component failing in a real-world crash. Thus, while the performance of WTORS in real-world crash events needs to be carefully and continuously monitored, at this time there is no basis for increasing the mass of the surrogate wheelchair, the crash-test dummy, or the crash severity used in the frontal-impact test of WTORS intended for general use in this part of ISO 10542. However, in addition to testing to the conditions set forth in this part of ISO 10542, WTORS manufacturers can also test their equipment to higher test conditions than those required by this part of ISO 10542.

This part of ISO 10542 requires that every WTORS include a belt-type occupant restraint since this approach to occupant protection has been shown to be the most effective in frontal crashes, vehicle rollovers, and a large percentage of side impacts, and can be implemented relatively straightforwardly in forward-facing seating positions of passenger vehicles. Since the use of only a pelvic belt restraint will not provide the same level of crash protection and safety as the use of both a pelvic belt restraint and an upper-torso belt restraint, this part of ISO 10542 requires, and only specifies test methods for, WTORS that include both pelvic and upper-torso belt restraint systems.

In this regard, while ISO 7176-19 does not require wheelchairs to be crash-tested with a wheelchair-anchored pelvic-belt restraint, it does allow for this restraint condition, which can offer benefits to wheelchair passengers in terms of improved belt-restraint fit to their lower pelvic region and reduced interference with their personal space by drivers or attendants. In this situation, the tiedown portion of a WTORS will be subjected to higher loading conditions than with vehicle-anchored pelvic belts since a portion of the occupant restraint loads will be transferred through the wheelchair to the wheelchair tiedown/securement system. Thus, WTORS manufacturers may also wish to crash-test their tiedown/securement systems with a pelvic-belt restraint anchored to the surrogate wheelchair.

For accessible transport vehicles intended for use by both sitting and standing passengers (ATV-SS) for which crash events of any significance are rare events, it is generally sufficient to provide equipment and/or systems that provide for effective wheelchair containment and retention of the wheelchair-seated passenger in their wheelchair seating system. Such systems can be evaluated using simulated non-crash vehicle accelerations and decelerations that are less than 1g that are generated in emergency vehicle manoeuvres. For this reason, the use of rearward-facing wheelchair passenger spaces (RF-WPS) can provide a reasonably safe approach

to transporting wheelchair-seated passengers in a manner that is more acceptable to the operational needs of the transportation system. Performance of RF-WPSs is therefore addressed by ISO 10865-1.

At the time this part of ISO 10542 was developed, the four-point strap-type tiedown system was considered to be the most effective and universal method for securing a wide range of wheelchairs occupied by passengers travelling in public, school, and private vehicles. For this reason, ISO 7176-19 requires that wheelchairs intended for use as seats in motor vehicles provide for securement using a four-point strap-type tiedown system by providing at least four designated securement points, with two at the front and two at the back. However, wheelchairs can also be secured in motor vehicles using docking-type tiedown devices, such that the wheelchair is automatically secured when the wheelchair user moves his/her wheelchair into the designated wheelchair space. Currently, use of these types of securement systems is primarily limited to private vehicles where docking securement components added to the wheelchair are matched to the securement device in the vehicle. Annex F provides specifications for a universal docking interface geometry (UDIG), which, when implemented into the securement components of wheelchairs, either by wheelchair manufacturers or by after-market wheelchair adaptors, will allow wheelchair users increased independence and reduce the time required for loading and unloading wheelchair passengers in public vehicle environments.

This part of ISO 10542 establishes additional requirements for WTORS that are intended to be used with specific makes and models of wheelchairs. The belt-type occupant restraints may attach to the wheelchair such that occupant-restraint loads will be transferred through the wheelchair. As such, the performance of both the WTORS and wheelchair are evaluated as a total system.

AUSTRALIAN/NEW ZEALAND STANDARD

Technical systems and aids for people with disability—Wheelchair tiedown and occupant-restraint systems

Part 1:

Requirements and test methods for all systems (ISO 10542-1:2012, MOD)

1 Scope

This part of ISO 10542 specifies design and performance requirements and associated test methods for wheelchair tiedown and occupant-restraint systems (WTORS), as well as requirements for product marking and labelling and manufacturers' instructions and warnings to installers and consumers. It is applicable to all WTORS that use belt-type occupant restraints that are intended for occupied wheelchairs used as forward-facing seats by passengers and drivers of motor vehicles.

This part of ISO 10542 is applicable to WTORS intended for use with all types of manual and powered wheelchairs, including three- and four-wheeled scooters, used by children and adults with a body mass equal to or greater than 22 kg. It is applicable also to WTORS designed for limited use with a particular make or model of wheelchair.

This part of ISO 10542 is applicable primarily to complete WTORS, but portions can also be applied to components and subassemblies sold separately and for replacement parts.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3795, *Road vehicles, and tractors and machinery for agriculture and forestry — Determination of burning behaviour of interior materials*

ISO 6487, *Road vehicles — Measurement techniques in impact tests — Instrumentation*

ISO 7176-19:2008, *Wheelchairs — Part 19: Wheeled mobility devices for use as seat in motor vehicles*

ECE R 16:2009, *Uniform provisions concerning the approval of safety belts, restraint systems, child restraint systems and isofix child restraint systems for occupants of power-driven vehicles*, Revision 6, 19 May 2009

FMVSS 209, *Seat belt assemblies*, Federal Motor Vehicle Safety Standards, 49 CFR part 571.209, 1 October 2004

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1**adult**

person having a mass equal to or greater than 43 kg

3.2**airbag**

device installed to supplement occupant restraint systems in power-driven vehicles, i.e. system which, in the event of a severe impact affecting the vehicle, automatically deploys a flexible structure intended to limit, by compression of the gas contained within it, the gravity of the contacts of one or more parts of the body of an occupant of the vehicle with the interior of the passenger compartment