

Australian/New Zealand Standard™

**Information technology—Generic
cabling for customer premises
(ISO/IEC 11801:2011, MOD)**



AS/NZS 3080:2013

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee CT-001, Communications Cabling. It was approved on behalf of the Council of Standards Australia on 9 May 2013 and on behalf of the Council of Standards New Zealand on 13 May 2013.

This Standard was published on 29 May 2013.

The following are represented on Committee CT-001:

Australian Chamber of Commerce and Industry
Australian Communications and Media Authority
Australian Industry Group
Australian Information Industry Association
BICSI Australia
Communications Alliance
Electrical Compliance Testing Association
Electrical Trades Union
Energy Networks Association
Engineers Australia
National Electrical and Communications Association
Telecommunications Users Association of New Zealand
Telstra Corporation

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

Information technology—Generic cabling for customer premises (ISO/IEC 11801:2011, MOD)

First published in Australia as AS 3080—1992.
First joint edition AS/NZS 3080:1996.
Previous edition AS/NZS 3080:2003.
Sixth edition 2013.

COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140.

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee CT-001, Communications Cabling, to supersede AS/NZS 3080:2003, *Telecommunications installations—Generic cabling for commercial premises (ISO/IEC 11801:2002, MOD)*.

The objective of this Standard is to provide building owners, managers, architects, designers, manufacturers, installers, maintainers and users, with requirements to ensure compatibility with equipment and services and to ensure performance of infrastructure to meet present and foreseeable future requirements.

This Standard applies to the use of generic cabling within commercial premises, which may comprise single buildings or multiple buildings on a campus.

The application of this Standard should lead to the installation of cabling systems that satisfy user requirements and provide a useful life of at least 10 years.

This Standard is an adoption with national modifications and has been reproduced from ISO/IEC 11801:2011, *Information technology—Generic cabling for customer premises* and has been varied to take account of Australian/New Zealand conditions. Appendix ZA and Appendix ZB have been added to the source text as set out below.

Appendix ZA provides additional normative requirements and clarifications on ISO/IEC 11801:2011 for Australia and New Zealand.

Appendix ZB provides additional information and guidance for Australian and New Zealand users.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number appears on the cover and title page while the International Standard number appears only on the cover.
- (b) In the source text ‘this International Standard’ should read ‘this Australian/New Zealand Standard’.
- (c) A full point substitutes for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to Australian or Australian/New Zealand Standards, as follows:

| <i>Reference to International Standard</i> | | <i>Australian/New Zealand Standard</i> | |
|--|---|--|--|
| ISO/IEC | | AS/NZS | ISO/IEC |
| 14763 | Information technology— Implementation and operation of customer premises cabling | 14763 | Telecommunications installations— Implementation and operation of customer premises cabling |
| 14763-3 | Part 3: Testing of optical fibre cabling | 14763.3 | Part 3: Testing of optical fibre cabling (ISO/IEC 14763-3:2011, MOD) |
| 15018 | Information technology—Generic cabling for homes | 15018 | Information technology—Generic cabling for homes |
| ISO/IEC | | AS/NZS | |
| 18010 | Information technology—Pathways and spaces for customer premises cabling | 3084 | Telecommunications installations— Telecommunications pathways and spaces for commercial buildings (ISO/IEC 18010:2002, MOD) |

| | | | |
|----------|--|------------|--|
| IEC | | AS/NZS IEC | |
| 60825 | Safety of laser products | 60825 | Safety of laser products |
| 60825-1 | Part 1: Equipment classification and requirements | 60825.1 | Part 1: Equipment classification and requirements |
| 60825-2 | Part 2: Safety of optical fibre communication systems (OFCS) | 60825.2 | Part 2: Safety of optical fibre communication systems (OFCS) |
| IEC TR | | | |
| 60825-14 | Part 14: A user's guide | 60825.14 | Part 14: A user's guide |
| IEC | | | |
| 61935 | Specification for the testing of balanced communication cabling in accordance with ISO/IEC 11801 | 61935 | Specification for the testing of balanced and coaxial information technology cabling |
| 61935-1 | Installed cabling | 61935.1 | Part 1: Installed balanced cabling as specified in ISO/IEC 11801 and related standards (IEC 61935-1, Ed.3.0 (2009) MOD) |

Only international references that have been adopted as Australian or Australian/New Zealand Standards have been listed.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the annex or appendix to which they apply. A 'normative' annex or appendix is an integral part of a Standard, whereas an 'informative' annex or appendix is only for information and guidance.

CONTENTS

| | | |
|-------|--|----|
| 1 | Scope..... | 16 |
| 2 | Normative references | 16 |
| 3 | Terms, definitions, abbreviations and symbols..... | 20 |
| 3.1 | Terms and definitions | 20 |
| 3.2 | Abbreviations | 30 |
| 3.3 | Symbols | 32 |
| 3.3.1 | Variables | 32 |
| 3.3.2 | Indices | 33 |
| 4 | Conformance..... | 33 |
| 5 | Structure of the generic cabling system | 34 |
| 5.1 | General..... | 34 |
| 5.2 | Functional elements | 34 |
| 5.3 | Cabling subsystems | 35 |
| 5.3.1 | General | 35 |
| 5.3.2 | Campus backbone cabling subsystem | 36 |
| 5.3.3 | Building backbone cabling subsystem..... | 36 |
| 5.3.4 | Horizontal cabling subsystem | 36 |
| 5.3.5 | Design objectives | 37 |
| 5.4 | Interconnection of subsystems | 37 |
| 5.4.1 | General | 37 |
| 5.4.2 | Centralised cabling architecture..... | 38 |
| 5.5 | Accommodation of functional elements..... | 39 |
| 5.6 | Interfaces..... | 39 |
| 5.6.1 | Equipment interfaces and test interfaces | 39 |
| 5.6.2 | Channel and permanent link | 41 |
| 5.6.3 | External network interface | 41 |
| 5.7 | Dimensioning and configuring..... | 41 |
| 5.7.1 | Distributors..... | 41 |
| 5.7.2 | Cables..... | 43 |
| 5.7.3 | Work area cords and equipment cords..... | 43 |
| 5.7.4 | Patch cords and jumpers | 43 |
| 5.7.5 | Telecommunications outlet (TO) | 43 |
| 5.7.6 | Consolidation point..... | 45 |
| 5.7.7 | Telecommunications rooms and equipment rooms..... | 45 |
| 5.7.8 | Building entrance facilities..... | 45 |
| 5.7.9 | External services cabling..... | 45 |
| 6 | Performance of balanced cabling..... | 46 |
| 6.1 | General..... | 46 |
| 6.2 | Layout..... | 47 |
| 6.3 | Classification of balanced cabling..... | 48 |

| | <i>Page</i> |
|--------|--|
| 6.4 | Balanced cabling performance 48 |
| 6.4.1 | General 48 |
| 6.4.2 | Return loss 48 |
| 6.4.3 | Insertion loss/attenuation 50 |
| 6.4.4 | NEXT 51 |
| 6.4.5 | Attenuation to crosstalk ratio at the near-end (ACR-N) 55 |
| 6.4.6 | Attenuation to crosstalk ratio at the far-end (ACR-F) 56 |
| 6.4.7 | Direct current (d.c.) loop resistance 59 |
| 6.4.8 | Direct current (d.c.) resistance unbalance 59 |
| 6.4.9 | Current carrying capacity 59 |
| 6.4.10 | Dielectric withstand 60 |
| 6.4.11 | Power capacity 60 |
| 6.4.12 | Propagation delay 60 |
| 6.4.13 | Delay skew 61 |
| 6.4.14 | Unbalance attenuation and coupling attenuation 61 |
| 6.4.15 | Alien crosstalk 63 |
| 7 | Reference implementations for balanced cabling 69 |
| 7.1 | General 69 |
| 7.2 | Balanced cabling 69 |
| 7.2.1 | General 69 |
| 7.2.2 | Horizontal cabling 70 |
| 7.2.3 | Backbone cabling 73 |
| 8 | Performance of optical fibre cabling 75 |
| 8.1 | General 75 |
| 8.2 | Component choice 76 |
| 8.3 | Channel attenuation 76 |
| 8.4 | Channel topology 76 |
| 8.5 | Propagation delay 78 |
| 9 | Cable requirements 78 |
| 9.1 | General 78 |
| 9.2 | Balanced cables 78 |
| 9.2.1 | Performance for balanced cables 78 |
| 9.2.2 | Additional requirements 79 |
| 9.2.3 | Additional performance requirements for flexible cables 82 |
| 9.3 | Additional crosstalk considerations for balanced cables 82 |
| 9.3.1 | Cable sharing 82 |
| 9.3.2 | Power summation in backbone cables 82 |
| 9.3.3 | Hybrid, multi-unit and cables connected to more than one TO 83 |
| 9.4 | Optical fibre cable (cabled optical fibres) 83 |
| 9.4.1 | Cabled optical fibre Categories 83 |
| 9.4.2 | Generic performance requirements 83 |
| 9.4.3 | Multimode optical fibre cable 83 |
| 9.4.4 | Single-mode optical fibre cables 84 |
| 10 | Connecting hardware requirements 85 |
| 10.1 | General requirements 85 |

| | <i>Page</i> |
|---|-------------|
| 10.1.1 Applicability | 85 |
| 10.1.2 Location | 85 |
| 10.1.3 Design | 86 |
| 10.1.4 Operating environment | 86 |
| 10.1.5 Mounting | 86 |
| 10.1.6 Installation practices | 86 |
| 10.1.7 Marking and colour coding | 87 |
| 10.2 Connecting hardware for balanced cabling | 87 |
| 10.2.1 General requirements | 87 |
| 10.2.2 Performance marking | 87 |
| 10.2.3 Mechanical characteristics | 87 |
| 10.2.4 Electrical characteristics | 89 |
| 10.2.5 TO requirements | 100 |
| 10.2.6 Design considerations for installation | 102 |
| 10.3 Optical fibre connecting hardware | 102 |
| 10.3.1 General requirements | 102 |
| 10.3.2 Marking and colour coding | 103 |
| 10.3.3 Mechanical and optical characteristics | 103 |
| 10.3.4 TO requirements | 104 |
| 10.3.5 Connection schemes for optical fibre cabling | 104 |
| 11 Screening practices | 107 |
| 11.1 General | 107 |
| 11.2 Electromagnetic performance | 107 |
| 11.3 Earthing | 107 |
| 12 Administration | 108 |
| 13 Balanced cords | 108 |
| 13.1 Introduction | 108 |
| 13.2 Insertion loss | 108 |
| 13.3 Return loss | 109 |
| 13.4 NEXT | 109 |
| Annex A (normative) Balanced permanent link and CP link performance | 113 |
| A.1 General | 113 |
| A.2 Balanced cabling | 114 |
| A.2.1 General | 114 |
| A.2.2 Return loss | 115 |
| A.2.3 Insertion loss/attenuation | 116 |
| A.2.4 NEXT | 118 |
| A.2.5 Attenuation to crosstalk ratio at the near-end (ACR-N) | 122 |
| A.2.6 Attenuation to crosstalk ratio at the far-end (ACR-F) | 124 |
| A.2.7 Direct current (d.c.) loop resistance | 127 |
| A.2.8 Direct current (d.c.) resistance unbalance | 128 |
| A.2.9 Propagation delay | 129 |
| A.2.10 Delay skew | 130 |
| A.2.11 Alien crosstalk | 132 |
| Annex B (normative) Test procedures | 139 |

| | <i>Page</i> |
|-----------------------|--|
| B.1 | General 139 |
| B.2 | Channel and link performance testing 139 |
| B.2.1 | General 139 |
| B.2.2 | Installation conformance testing of balanced cabling channels, permanent links and CP links 139 |
| B.2.3 | Installation conformance testing of optical fibre cabling channels 140 |
| B.3 | Overview of test regimes 140 |
| Annex C (normative) | Mechanical and environmental performance testing of connecting hardware for balanced cabling 144 |
| C.1 | Overview 144 |
| C.2 | Solderless connections 144 |
| C.3 | Free and fixed connectors (modular plugs and jacks) 145 |
| C.4 | Other connecting hardware 146 |
| Annex D (informative) | 148 |
| Annex E (informative) | Acronyms for balanced cables 149 |
| Annex F (informative) | Supported applications 152 |
| F.1 | Supported applications for balanced cabling 152 |
| F.2 | Supported applications for optical fibre cabling 155 |
| Annex G (informative) | Channel and permanent link models for balanced cabling 161 |
| G.1 | General 161 |
| G.2 | Insertion loss 161 |
| G.2.1 | Insertion loss of the channel configuration 161 |
| G.2.2 | Insertion loss of the permanent link configurations 162 |
| G.2.3 | Assumptions for insertion loss 162 |
| G.3 | NEXT 163 |
| G.3.1 | NEXT of the channel configuration 163 |
| G.3.2 | NEXT of the permanent link configurations 163 |
| G.3.3 | Assumptions for NEXT 164 |
| G.4 | ACR-F 167 |
| G.4.1 | ACR-F of the channel configuration 167 |
| G.4.2 | ACR-F for the permanent link configurations 167 |
| G.4.3 | Assumptions for ACR-F 168 |
| G.5 | Return loss 168 |
| G.5.1 | Return loss of the channel and permanent link configurations 168 |
| G.5.2 | Assumptions for the return loss circuit analysis method 169 |
| G.6 | PS ANEXT link modelling 171 |
| G.6.1 | General 171 |
| G.6.2 | PS ANEXT between connectors 171 |
| G.6.3 | PS ANEXT between cable segments 171 |
| G.6.4 | Principles of link modelling 172 |
| G.7 | PS AACR-F link modelling 172 |
| G.7.1 | General 172 |
| G.7.2 | PS AFEXT between connectors 172 |
| G.7.3 | PS AACR-F between cable segments 172 |
| G.7.4 | Principles of link modelling 173 |

| | <i>Page</i> |
|--|-------------|
| G.7.5 Impact of PS AACR-F in channels and links with substantially different lengths | 173 |
| G.8 Component assumptions for modelling purposes | 175 |
| Annex H (informative) Significant changes to balanced cabling requirements with respect to earlier editions of this International Standard | 178 |
| H.1 General | 178 |
| H.2 References | 178 |
| H.3 Structural elements | 178 |
| H.4 Product designation | 178 |
| H.5 Component requirements | 178 |
| H.6 Installed cabling requirements | 179 |
| Figure 1 – Structure of generic cabling | 35 |
| Figure 2 – Hierarchical structure of generic cabling | 37 |
| Figure 3 – Structures for centralised generic cabling | 38 |
| Figure 4 – Accommodation of functional elements | 39 |
| Figure 5 – Interconnect models | 40 |
| Figure 6 – Cross-connect models | 40 |
| Figure 7 – Equipment and test interfaces | 40 |
| Figure 8 – Example of a generic cabling system with combined BD and FD | 42 |
| Figure 9 – Inter-relationship of functional elements in an installation with redundancy | 43 |
| Figure 10 – Balanced cabling: channel, permanent link and CP link | 46 |
| Figure 11 – Example of a system showing the location of cabling interfaces and extent of associated channels | 47 |
| Figure 12 – Horizontal cabling models | 72 |
| Figure 13 – Backbone cabling model | 74 |
| Figure 14 – Combined backbone/horizontal channels | 77 |
| Figure 15 – Pin grouping and pair assignments for IEC 60603-7 series interface for Categories 5, 6 and 6 _A (front view of fixed connector (jack), not to scale) | 100 |
| Figure 16 – Pin grouping and pair assignment for the IEC 60603-7 series interface for Categories 7 and 7 _A | 101 |
| Figure 17 – Pin grouping and pair assignments for Categories 7 and 7 _A (IEC 61076-3-104) interface | 101 |
| Figure 18 – Duplex-able LC connectivity configuration with an example of polarity identification | 105 |
| Figure 19 – Duplex SC connectivity configuration | 106 |
| Figure 20 – Optical fibre cord | 107 |
| | |
| Figure A.1 – Link options | 114 |
| | |
| Figure E.1 – Cable naming schema | 150 |
| Figure E.2 – Examples of cable types | 151 |
| | |
| Figure G.1 – Example of computation of NEXT with higher precision | 164 |

| | |
|---|-----|
| Figure G.2 – Example of increased impact of PS AFEXT | 173 |
| Figure H.1 – Horizontal cabling model | 180 |
| Figure H.2 – Backbone cabling model | 180 |
| Table 1 – Maximum channel lengths | 41 |
| Table 2 – Return loss for channel | 49 |
| Table 3 – Informative return loss values for channel at key frequencies | 50 |
| Table 4 – Insertion loss for channel | 51 |
| Table 5 – Informative insertion loss values for channel at key frequencies | 51 |
| Table 6 – NEXT for channel | 52 |
| Table 7 – Informative NEXT values for channel at key frequencies | 53 |
| Table 8 – PS NEXT for channel | 54 |
| Table 9 – Informative PS NEXT values for channel at key frequencies | 54 |
| Table 10 – Informative ACR-N values for channel at key frequencies | 55 |
| Table 11 – Informative PS ACR-N values for channel at key frequencies | 56 |
| Table 12 – ACR-F for channel | 57 |
| Table 13 – Informative ACR-F values for channel at key frequencies | 57 |
| Table 14 – PS ACR-F for channel | 58 |
| Table 15 – Informative PS ACR-F values for channel at key frequencies | 59 |
| Table 16 – Direct current (d.c.) loop resistance for channel | 59 |
| Table 17 – Current carrying capacity for channel | 60 |
| Table 18 – Propagation delay for channel | 60 |
| Table 19 – Informative propagation delay values for channel at key frequencies | 61 |
| Table 20 – Delay skew for channel | 61 |
| Table 21 – TCL for channel for unscreened systems | 62 |
| Table 22 – ELTCTL for channel for unscreened systems | 62 |
| Table 23 – Coupling attenuation for channel for screened systems | 63 |
| Table 24 – PS ANEXT for channel | 64 |
| Table 25 – Informative PS ANEXT values for channel at key frequencies | 64 |
| Table 26 – PS ANEXT _{avg} for channel | 65 |
| Table 27 – Informative PS ANEXT _{avg} values for channel at key frequencies | 66 |
| Table 28 – PS AACR-F for channel | 68 |
| Table 29 – Informative PS AACR-F values for channel at key frequencies | 68 |
| Table 30 – PS AACR-F _{avg} for channel | 69 |
| Table 31 – Informative PS AACR-F _{avg} values for channel at key frequencies | 69 |
| Table 32 – Length assumptions used in the mathematical modelling of balanced horizontal cabling | 72 |
| Table 33 – Horizontal channel length equations | 73 |
| Table 34 – Backbone channel length equations | 75 |
| Table 35 – Channel attenuation | 76 |

| | |
|---|----|
| Table 36 – Performance for balanced cables | 79 |
| Table 37 – Mechanical characteristics of balanced cables | 79 |
| Table 38 – ACR-F for cables..... | 80 |
| Table 39 – Informative ACR-F values for cables at key frequencies | 80 |
| Table 40 – PS ACR-F for cables | 81 |
| Table 41 – Informative PS ACR-F values for cables at key frequencies | 81 |
| Table 42 – Current carrying capacity for channel | 81 |
| Table 43 – Cabled optical fibre attenuation | 83 |
| Table 44 – Multimode optical fibre modal bandwidth | 84 |
| Table 45 – Mechanical characteristics of connecting hardware for use with balanced cabling..... | 88 |
| Table 46 – Electrical characteristics of TOs intended for use with balanced cabling..... | 89 |
| Table 47 – Return loss for connector | 90 |
| Table 48 – Informative return loss values for connector at key frequencies | 90 |
| Table 49 – Insertion loss for connector | 91 |
| Table 50 – Informative insertion loss values for connector at key frequencies..... | 91 |
| Table 51 – Near end crosstalk (NEXT) for connector | 92 |
| Table 52 – Informative NEXT values for connector at key frequencies | 92 |
| Table 53 – Power sum near end crosstalk (PS NEXT) for connector (for information only)..... | 92 |
| Table 54 – Informative PS NEXT values for connector at key frequencies..... | 93 |
| Table 55 – Far end crosstalk (FEXT) for connector | 93 |
| Table 56 – Informative FEXT values for connector at key frequencies..... | 94 |
| Table 57 – Power sum far end crosstalk (PS FEXT) for connector (for information only) | 94 |
| Table 58 – Informative PS FEXT values for connector at key frequencies | 94 |
| Table 59 – Input to output resistance | 95 |
| Table 60 – Input to output resistance unbalance | 95 |
| Table 61 – Current carrying capacity..... | 95 |
| Table 62 – Propagation delay | 95 |
| Table 63 – Delay skew..... | 96 |
| Table 64 – Transverse conversion loss (TCL) | 96 |
| Table 65 – Informative TCL values for connector at key frequencies..... | 96 |
| Table 66 – Transverse conversion transfer loss (TCTL) | 97 |
| Table 67 – Informative TCTL values for connector at key frequencies..... | 97 |
| Table 68 – Transfer impedance (screened connectors only) | 97 |
| Table 69 – Informative transfer impedance values (screened connectors only) at key frequencies..... | 97 |
| Table 70 – Coupling attenuation (screened connectors only) | 98 |
| Table 71 – Informative coupling attenuation values (screened connectors only) at key frequencies..... | 98 |
| Table 72 – Insulation resistance | 98 |
| Table 73 – Voltage proof..... | 98 |
| Table 74 – Power sum alien near end crosstalk (PS ANEXT)..... | 99 |

| | <i>Page</i> |
|---|-------------|
| Table 75 – Informative PS ANEXT values at key frequencies | 99 |
| Table 76 – Power sum alien far end crosstalk (PS AFEXT) | 99 |
| Table 77 – Informative PS AFEXT values at key frequencies | 100 |
| Table 78 – Matrix of backward compatible mated free and fixed connector (plug and jack) performance | 102 |
| Table 79 – Mechanical and optical characteristics of optical fibre connecting hardware | 104 |
| Table 80 – Minimum return loss for balanced cords | 109 |
| Table 81 – Informative values of return loss for balanced cords at key frequencies | 109 |
| Table 82 – Assumptions for cabling components used in the calculation of NEXT informative values | 111 |
| Table 83 – Informative values of NEXT for 2 m balanced cords at key frequencies | 111 |
| Table 84 – Informative values of NEXT for 5 m balanced cords at key frequencies | 111 |
| Table 85 – Informative values of NEXT for 10 m balanced cords at key frequencies | 112 |
| | |
| Table A.1 – Return loss for permanent link or CP link | 115 |
| Table A.2 – Informative return loss values for permanent link at key frequencies | 116 |
| Table A.3 – Insertion loss for permanent link or CP link | 117 |
| Table A.4 – Informative insertion loss values for permanent link with maximum implementation at key frequencies | 118 |
| Table A.5 – NEXT for permanent link or CP link | 119 |
| Table A.6 – Informative NEXT values for permanent link with maximum implementation at key frequencies | 120 |
| Table A.7 – PS NEXT for permanent link or CP link | 121 |
| Table A.8 – Informative PS NEXT values for permanent link with maximum implementation at key frequencies | 122 |
| Table A.9 – Informative ACR-N values for permanent link with maximum implementation at key frequencies | 123 |
| Table A.10 – Informative PS ACR-N values for permanent link with maximum implementation at key frequencies | 124 |
| Table A.11 – ACR-F for permanent link or CP link | 125 |
| Table A.12 – Informative ACR-F values for permanent link with maximum implementation at key frequencies | 126 |
| Table A.13 – PS ACR-F for permanent link or CP link | 127 |
| Table A.14 – Informative PS ACR-F values for permanent link with maximum implementation at key frequencies | 127 |
| Table A.15 – Direct current (d.c.) loop resistance for permanent link or CP link | 128 |
| Table A.16 – Informative d.c. loop resistance for permanent link with maximum implementation | 128 |
| Table A.17 – Propagation delay for permanent link or CP link | 129 |
| Table A.18 – Informative propagation delay values for permanent link with maximum implementation at key frequencies | 130 |
| Table A.19 – Delay skew for permanent link or CP link | 131 |
| Table A.20 – Informative delay skew for permanent link with maximum implementation | 131 |

| | <i>Page</i> |
|---|-------------|
| Table A.21 – PS ANEXT for permanent link or CP link | 133 |
| Table A.22 – Informative PS ANEXT values for permanent link at key frequencies..... | 133 |
| Table A.23 – PS ANEXT _{avg} for permanent link or CP link | 134 |
| Table A.24 – Informative PS ANEXT _{avg} values for permanent link at key frequencies | 134 |
| Table A.25 – PS AACR-F for permanent link or CP link..... | 136 |
| Table A.26– Informative PS AACR-F values for permanent link at key frequencies | 137 |
| Table A.27 – PS AACR-F _{avg} for permanent link or CP link | 137 |
| Table A.28– Informative PS AACR-F _{avg} values for permanent link at key frequencies..... | 138 |
| | |
| Table B.1 – Test regime for reference conformance and installation conformance – Balanced cabling..... | 141 |
| Table B.2 – Test regime for reference conformance and installation conformance – Optical fibre cabling..... | 143 |
| | |
| Table C.1 – Standards for solderless connections..... | 144 |
| Table C.2 – Standards for free and fixed connectors (modular plugs and jacks)..... | 145 |
| Table C.3 – Free and fixed connectors (modular plugs and jacks) operations matrix | 146 |
| Table C.4 – Reference for reliability testing of other connecting hardware | 146 |
| Table C.5 – Other connecting hardware operations matrix | 147 |
| | |
| Table F.1 – Applications using balanced cabling..... | 153 |
| Table F.2 – Modular connector pin assignment for applications | 155 |
| Table F.3 – Supported applications using optical fibre cabling | 157 |
| Table F.4 – Maximum channel lengths supported by optical fibre applications for multimode optical fibre..... | 159 |
| Table F.5 – Maximum channel length supported by optical fibre applications for single-mode optical fibre..... | 160 |
| | |
| Table G.1 – Insertion loss deviation | 162 |
| Table G.2 – Modelling assumptions for cable transmission parameters..... | 176 |
| Table G.3 – Model input assumptions used in the statistical calculation (Class E _A) | 176 |
| | |
| Table H.1 - Principal transmission performance requirements of 150 Ω connecting hardware | 179 |
| Table H.2 – Minimum return loss limits for links, permanent links and channels for the different cabling classes | 181 |
| Table H.3 – Maximum attenuation limits for links, permanent links and channels for the different cabling classes | 181 |
| Table H.4 – Minimum NEXT limits for links, permanent links and channels for the different cabling classes | 182 |
| Table H.5 – Minimum ACR limits for links, permanent links and channels for the different cabling classes | 182 |
| Table H.6 – Maximum propagation delay limits for links, permanent links and channels for the different cabling classes..... | 183 |

| | |
|---|-----|
| Table H.7 – Maximum d.c. loop resistance limits for links, permanent links and channels for the different cabling classes..... | 183 |
| Table H.8 – Minimum unbalance attenuation (LCL/LCTL) limits for links, permanent links and channels for the different cabling classes | 183 |
| Table H.9 – Minimum PS NEXT, PS ACR, ELFEXT and PS ELFEXT limits for permanent links and channels for the different cabling classes..... | 184 |
| Table H.10 – Maximum delay skew limits for permanent links and channels for the different cabling classes | 184 |

INTRODUCTION

Within customer premises, the importance of the cabling infrastructure is similar to that of other fundamental building utilities such as heating, lighting and mains power. As with other utilities, interruptions to service can have a serious impact. Poor quality of service due to lack of design foresight, use of inappropriate components, incorrect installation, poor administration or inadequate support can threaten an organisation's effectiveness.

Historically, the cabling within premises comprised both application specific and multipurpose networks. The original edition of this standard enabled a controlled migration to generic cabling and the reduction in the use of application-specific cabling.

The subsequent growth of generic cabling designed in accordance with ISO/IEC 11801 has

- a) contributed to the economy and growth of Information and Communications Technology (ICT),
- b) supported the development of high data rate applications based upon a defined cabling model, and
- c) initiated development of cabling with a performance surpassing the performance classes specified in ISO/IEC 11801:1995 and ISO/IEC 11801 Ed1.2:2000.

NOTE ISO/IEC 11801, edition 1.2 consists of edition 1.0 (1995) and its amendments 1 (1999) and 2 (1999).

This second edition of ISO/IEC 11801 has been developed to reflect these increased demands and opportunities.

This International Standard provides:

- a) users with an application independent generic cabling system capable of supporting a wide range of applications;
- b) users with a flexible cabling scheme such that modifications are both easy and economical;
- c) building professionals (for example, architects) with guidance allowing the accommodation of cabling before specific requirements are known; that is, in the initial planning either for construction or refurbishment;
- d) industry and applications standardization bodies with a cabling system which supports current products and provides a basis for future product development.

This International Standard specifies a multi-vendor cabling system which may be implemented with material from single and multiple sources, and is related to:

- a) international standards for cabling components developed by committees of the IEC, for example copper cables and connectors as well as optical fibre cables and connectors (see Clause 2 and bibliography);
- b) standards for the installation and operation of information technology cabling as well as for the testing of installed cabling (see Clause 2 and bibliography);
- c) applications developed by technical committees of the IEC, by subcommittees of ISO/IEC JTC 1 and by study groups of ITU-T, for example for LANs and ISDN;
- d) planning and installation guides which take into account the needs of specific applications for the configuration and the use of cabling systems on customer premises (ISO/IEC 14709 series).

Physical layer requirements for the applications listed in Annex F have been analysed to determine their compatibility with cabling classes specified in this standard. These application requirements, together with statistics concerning the topology of premises and the model described in 7.2, have been used to develop the requirements for Classes A to D and the optical class cabling systems. New Classes E and F have been developed in anticipation of future network technologies.

As a result, generic cabling defined within this International Standard

- a) specifies a cabling structure supporting a wide variety of applications,
- b) specifies channel and link Classes A, B, C, D and E meeting the requirements of standardised applications,
- c) specifies channel and link Classes E and F based on higher performance components to support the development and implementation of future applications,
- d) specifies optical channel and link Classes OF-300, OF-500, and OF-2000 meeting the requirements of standardised applications and exploiting component capabilities to ease the implementation of applications developed in the future,
- e) invokes component requirements and specifies cabling implementations that ensure performance of permanent links and of channels that meet or exceed the requirements for cabling classes,
- f) is targeted at, but not limited to, the general office environment.

This International Standard specifies a generic cabling system that is anticipated to have a usable life in excess of 10 years.

INTRODUCTION to Amendment 1

This amendment provides requirements for new Class E_A and F_A channels plus additions and corrections to ISO/IEC 11801:2002. Amendment 2 of ISO/IEC 11801:2002 will provide balanced cabling models, requirements and normative references for Category 6_A and 7_A components, requirements for Class E_A and F_A links, together with amendments to the requirements for optical fibre cabling.

INTRODUCTION to Amendment 2

Amendment 2 of ISO/IEC 11801:2002 provides balanced cabling models, requirements and normative references for Category 6_A and Category 7_A components, requirements for Class E_A and Class F_A links, together with amendments to the requirements for optical fibre cabling.

AUSTRALIAN/NEW ZEALAND STANDARD

**Information technology—Generic cabling for customer premises
(ISO/IEC 11801:2011, MOD)****1 Scope**

ISO/IEC 11801 specifies generic cabling for use within premises, which may comprise single or multiple buildings on a campus. It covers balanced cabling and optical fibre cabling.

ISO/IEC 11801 is optimised for premises in which the maximum distance over which telecommunications services can be distributed is 2 000 m. The principles of this International Standard may be applied to larger installations.

Cabling defined by this standard supports a wide range of services, including voice, data, text, image and video.

This International Standard specifies directly or via reference the:

- a) structure and minimum configuration for generic cabling,
- b) interfaces at the telecommunications outlet (TO),
- c) performance requirements for individual cabling links and channels,
- d) implementation requirements and options,
- e) performance requirements for cabling components required for the maximum distances specified in this standard,
- f) conformance requirements and verification procedures.

Safety (electrical safety and protection, fire, etc.) and Electromagnetic Compatibility (EMC) requirements are outside the scope of this International Standard, and are covered by other standards and by regulations. However, information given by this standard may be of assistance.

ISO/IEC 11801 has taken into account requirements specified in application standards listed in Annex F. It refers to available International Standards for components and test methods where appropriate.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

The provisions of the referenced specifications other than ISO/IEC, IEC, ISO and ITU documents, as identified in this clause, are valid within the context of this International Standard. The reference to such a specification within this International Standard does not give it any further status within ISO or IEC. In particular, it does not give the referenced specification the status of an International Standard.

IEC 60352 (all parts), *Solderless connections*

IEC 60352-3, *Solderless connections – Part 3: Solderless accessible insulation displacement connections – General requirements, test methods and practical guidance*