

Australian/New Zealand Standard™

**Geographic information—Linear
referencing**



AS/NZS ISO 19148:2012

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee IT-004, Geographical Information/Geomatics. It was approved on behalf of the Council of Standards Australia on 6 November 2012 and on behalf of the Council of Standards New Zealand on 1 November 2012.
This Standard was published on 30 November 2012.

The following are represented on Committee IT-004:

ANZLIC—The Spatial Information Council
Australasian Fire and Emergency Service Authorities Council
Australian Antarctic Division
Australian Hydrographic Office
Australian Map Circle
CSIRO Exploration and Mining
Department of Lands, NSW
Department of Primary Industries and Water, Tas.
Geoscience Australia
Land Information New Zealand
Mercury Project Solutions
Office of Spatial Data Management
University of Melbourne

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

This Standard was issued in draft form for comment as DR AS/NZS ISO 19148.

Australian/New Zealand Standard™

Geographic information—Linear referencing

First published as AS/NZS ISO 19148:2012.

COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140.

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee IT-004, Geographical Information/Geomatics.

The objective of this Standard is to specify a conceptual schema for locations relative to a one-dimensional object as measurement along (and optionally offset from) that object. It defines a description of the data and operations required to use and support linear referencing.

This Standard is identical with, and has been reproduced from, ISO 19148:2012, *Geographic information—Linear referencing*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number appears on the cover and title page while the International Standard number appears only on the cover.
- (b) In the source text ‘this International Standard’ should read ‘this Australian/New Zealand Standard’.
- (c) A full point substitutes for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to Australian or Australian/New Zealand Standards, as follows:

<i>Reference to International Standard</i>		<i>Australian/New Zealand Standard</i>	
ISO/TS		AS/NZS ISO	
19103	Geographic information—Conceptual schema language	19103	Geographic information—Conceptual schema language
ISO			
19107	Geographic information—Spatial schema	19107	Geographic information—Spatial schema
19108	Geographic information—Temporal schema	19108	Geographic information—Temporal schema
19111	Geographic information—Spatial referencing by coordinates	19111	Geographic information—Spatial referencing by coordinates

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the annex to which they apply. A ‘normative’ annex is an integral part of a Standard, whereas an ‘informative’ annex is only for information and guidance.

CONTENTS

1	Scope	1
2	Conformance	1
2.1	Conformance overview	1
2.2	Conformance classes	2
3	Normative references	3
4	Terms and definitions	3
5	Abbreviated terms	6
6	Linear referencing	6
6.1	Introduction	6
6.2	Package: Linear Referencing System	17
6.3	Package: Linear Referencing Towards Referent	31
6.4	Package: Linear Referencing Offset	33
6.5	Package: Linear Referencing Offset Vector	39
6.6	Package: Linearly Located Event	41
6.7	Package: Linear Segmentation	47
Annex A	(normative) Abstract test suite	52
Annex B	(informative) Generalized model for linear referencing	56
Annex C	(informative) Commonly used linear referencing methods and models	59
Annex D	(informative) Event and segmentation examples	79
	Bibliography	86

INTRODUCTION

This International Standard is a description of the data and operations required to support linear referencing. This includes Linear Referencing Systems, linearly located events and linear segments.

Linear Referencing Systems enable the specification of positions along linear objects. The approach is based upon the Generalized Model for Linear Referencing^[3] first standardized within ISO 19133:2005, 6.6. This International Standard extends that which was included in ISO 19133, both in functionality and explanation.

ISO 19109 supports features representing discrete objects with attributes having values which apply to the entire feature. ISO 19123 allows the attribute value to vary, depending upon the location within a feature, but does not support the assignment of attribute values to a single point or length along a linear feature. Linearly located events provide the mechanism for specifying attribution of linear objects when the attribute value varies along the length of a linear feature. A Linear Referencing System is used to specify where along the linear object each attribute value applies. The same mechanism can be used to specify where along a linear object another object is located, such as guardrail or a traffic accident.

It is common practice to segment a linear object having linearly located events, based upon one or more of its attributes. The resultant linear segments are attributed with just the attributes used in the segmentation process, insuring that the linear segments are homogeneous in value for these segmenting attributes.

This International Standard differs from ISO 19133:2005, 6.6 in the following areas.

- a) All occurrences of Linear Reference Method and Linear Reference System have been changed to Linear Referencing Method and Linear Referencing System, respectively.
- b) LR_Element has been renamed LR_LinearElement and further defined as being a feature or geometry or topology. These shall support the newly introduced interface ILinearElement, meaning that it is possible to measure (linearly) along them.
- c) The newly introduced ILinearElement interface includes operations for returning the default Linear Referencing Method of the linear element and any of its length or weight attribute values. It also includes operations for translating between Linear Referencing Methods and/or linear elements.
- d) The types of Linear Referencing Methods have been formalized as a CodeList. Names of common Linear Referencing Methods have been added as an informative annex.
- e) An additional attribute, constraint[0..*], has been added to Linear Referencing Method to specify the constraints imposed by the method, such as “only allows reference marker referents”. This is an alternative to subtyping the methods that would force a too-structured approach, inconsistent with the Generalized Model, and would be indeterminate due to the wide variety of Linear Referencing Methods currently in use.
- f) The Linear Referencing Method “project” operation has been renamed “lrPosition” and moved to the ISpatial interface and a second, opposite, operation “point” has been added. Only LR_Curves realize this interface since their spatial representation is requisite for the two operations, along with the ILinearElement interface.
- g) The LR_PositionExpression measure attribute has been extracted out into a Distance Expression along with the optional referent and offset roles consistent with the original theoretical model. This allows for specifying only an LR_DistanceExpression when the LR_LinearElement and LR_LinearReferencingMethod are already known.
- h) Reference Marker has been generalized to LR_Referent to enable support for other referent types such as intersections, boundaries and landmarks. This type has been formalized as a CodeList.

- i) A second, optional (towards) Referent has been added in a new (optional) package, Linear Referencing Towards Referent (LRTR), for those Linear Referencing Methods which allow this to disambiguate measurement direction.
- j) Lateral Offsets have been moved to a new (optional) package, Linear Referencing Offset (LRO). Horizontal, vertical, and combined horizontal and vertical offsets are now supported. Offset referent has been generalized to allow for feature instances as well as character strings.
- k) Vector Offsets have been adopted from ISO 19141. They exist in a new (optional) package, Linear Referencing Offset Vector (LROV). An optional offset vector Coordinate Reference System (CRS) can be provided if it is different from the CRS of the linear element.
- l) The theoretical model on which the original standard was built is explained in Annex B.
- m) More descriptive text is added throughout this International Standard to explain the concepts being presented.
- n) Minor changes to some class, attribute and role names have been made.
- o) A new (optional) package, Linearly Located Event (LE) has been added which uses linearly referenced positions to specify where along a linear feature a particular attribute value or other feature instance applies.
- p) A new (optional) package, Linear Segmentation (LS) has been added to support the generation of homogeneous attributed linear segments from linear features with length-varying attribution.
- q) Absolute Linear Referencing Method with non-zero linear element start is now accommodated.
- r) `lateralOffsetReferentType` and `verticalOffsetReferentType` have been changed from CodeLists to Character Strings.

AUSTRALIAN/NEW ZEALAND STANDARD

Geographic information—Linear referencing**1 Scope**

This International Standard specifies a conceptual schema for locations relative to a one-dimensional object as measurement along (and optionally offset from) that object. It defines a description of the data and operations required to use and support linear referencing.

This International Standard is applicable to transportation, utilities, location-based services and other applications which define locations relative to linear objects.

2 Conformance**2.1 Conformance overview**

Clause 6 of this International Standard uses the Unified Modelling Language (UML) to present conceptual schemas for describing the constructs required for Linear Referencing. These schemas define conceptual classes that shall be used in application schemas, profiles and implementation specifications. This International Standard concerns only externally visible interfaces and places no restriction on the underlying implementations other than what is required to satisfy the interface specifications in the actual situation, such as

- interfaces to software services using techniques such as SOAP;
- interfaces to databases using techniques such as SQL;
- data interchange using encoding as defined in ISO 19118.

Few applications require the full range of capabilities described by this conceptual schema. Clause 6, therefore, defines a set of conformance classes that support applications whose requirements range from the minimum necessary to define data structures to full object implementation. This flexibility is controlled by a set of UML types that can be implemented in a variety of manners. Implementations that define full object functionality shall implement all operations defined by the types of the chosen conformance class, as is common for UML designed object implementations. It is not necessary for implementations that choose to depend on external “free functions” for some or all operations, or forgo them altogether, to support all operations, but they shall always support a data type sufficient to record the state of each of the chosen UML types as defined by its member variables. It is acceptable to use common names for concepts that are the same but have technically different implementations. The UML model in this International Standard defines abstract types, application schemas define conceptual classes, various software systems define implementation classes or data structures, and the XML from the encoding standard (ISO 19118) defines entity tags. All of these reference the same information content. There is no difficulty in allowing the use of the same name to represent the same information content even though at a deeper level there are significant technical differences in the digital entities being implemented. This “allows” types defined in the UML model to be used directly in application schemas.