

Australian Standard[®]

**SAMPLING PROCEDURES AND
TABLES FOR INSPECTION BY
ATTRIBUTES**

This Australian Standard was prepared by Committee QR/4, Statistical Quality Procedures. It was approved on behalf of the Council of the Standards Association of Australia on 4 January 1988 and published on 15 April 1988.

The following interests are represented on Committee QR/4:

Australian Organization for Quality Control
Bureau of Steel Manufacturers of Australia
Confederation of Australian Industry
CSIRO Division of Mathematics and Statistics
Department of Defence
Department of Primary Industry
Federal Chamber of Automotive Industries
Federation of Automotive Products Manufacturers
Institute of Quality Assurance
National Association of Testing Authorities Australia
Telecom Australia
University of Wollongong

Review of Australian Standards. *To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

AS 1199—1988

Australian Standard[®]

**SAMPLING PROCEDURES AND
TABLES FOR INSPECTION BY
ATTRIBUTES**

First published as AS 1199—1972.
Second edition 1988.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 4901 7

PREFACE

This Standard was prepared by the Association's Committee on Statistical Quality Procedures to supersede AS 1199—1972. AS 1199—1972 was based to a large extent on the ABCA-ARMY-STD-105A prepared by a working group representing the military services of the US, the UK and Canada, and on the US, UK, Canadian and Australian versions of that Standard published as MIL-STD-105D, DEF-131-A, CA-C-115, and DEF(AUST)165, respectively.

The Australian Standard differed from the ABCA-ARMY-STD in that the definitions of terms given were in accord with AS 1057—1972, *Glossary of terms relating to quality control*. The appendix on sequential sampling given in the British Defence Specification DEF-131-A had been added, and a further appendix was included which gave tables relating to the occurrence of no defectives in a sample.

This Standard contains essentially the same material as AS 1199—1972, but with typographical changes. Editorial changes are confined to the revision of some definitions and clarification of some clauses.

For convenience of publication, Tables 1 to 10-S have been taken from ISO/DIS 2859/1, however, wherever the decimal comma appears in these tables it should be replaced by the decimal point.

A major revision, however, is the substitution of the words 'nonconformity' and 'nonconforming item', for the words 'defect' and 'defective' used in the 1972 edition. This is in line with ISO policy of using 'nonconformity' to denote departure from specification, as opposed to 'defect' denoting the inability to satisfy normal usage requirements. To avoid any conflict with the definitions of AS 1057—1985, *Quality assurance and quality control glossary of terms*, this Standard does not use the words 'defect' or 'defective'.

Most users of this Standard will find it sufficiently descriptive to stand on its own. However, more guidance in its theory and application is available in AS 1399—1973 (under revision) *Guide to AS 1199*.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SECTION 1. SCOPE AND GENERAL	
1.1 SCOPE	6
1.2 APPLICATION	6
1.3 REFERENCED DOCUMENTS	6
1.4 DEFINITIONS	6
SECTION 2. NONCONFORMANCE—NONCONFORMITIES AND NONCONFORMING ITEMS	
2.1 DEFINITIONS APPLICABLE TO SECTION 2	7
2.2 CLASSIFICATION OF NONCONFORMITIES	7
SECTION 3. ACCEPTABLE QUALITY LEVEL (AQL)	
3.1 DEFINITION APPLICABLE TO SECTION 3	8
3.2 USE	8
3.3 LIMITATION	8
3.4 SPECIFYING AQLS	8
3.5 PREFERRED AQLS	8
SECTION 4. SUBMISSION OF PRODUCT	
4.1 DEFINITIONS APPLICABLE TO SECTION 4	8
4.2 PRESENTATION OF BATCHES OR LOTS	8
SECTION 5. DRAWING OF SAMPLES	
5.1 DEFINITIONS APPLICABLE TO SECTION 5	9
5.2 SELECTION OF SAMPLES	9
5.3 TIME OF SAMPLING	9
5.4 DOUBLE, MULTIPLE OR SEQUENTIAL SAMPLING	9
SECTION 6. ACCEPTANCE OR REJECTION	
6.1 ACCEPTANCE OF A BATCH OR LOT	9
6.2 NONCONFORMING ITEMS OR UNITS OF PRODUCT	9
6.3 SPECIAL RESERVATION FOR CRITICAL NONCONFORMITIES	9
6.4 RESUBMITTED BATCHES OR LOTS	9
SECTION 7. NORMAL, TIGHTENED AND REDUCED INSPECTION	
7.1 DEFINITIONS APPLICABLE TO SECTION 7	10
7.2 GENERAL	10
7.3 INITIATION OF INSPECTION	10
7.4 CONTINUATION OF INSPECTION	10
7.5 SWITCHING PROCEDURES	10
7.6 DISCONTINUATION OF INSPECTION	10
SECTION 8. SAMPLING PLANS	
8.1 DEFINITIONS APPLICABLE TO SECTION 8	11
8.2 SELECTION OF INSPECTION LEVEL	11
8.3 CODE LETTERS	11
8.4 OBTAINING A SAMPLING PLAN	11
8.5 TYPES OF SAMPLING PLANS	11
SECTION 9. DETERMINATION OF ACCEPTABILITY	
9.1 PERCENT NONCONFORMING INSPECTION	12
9.2 NONCONFORMITIES PER HUNDRED ITEMS OR UNITS OF PRODUCT INSPECTION	12

	<i>Page</i>
SECTION 10. SUPPLEMENTARY INFORMATION	
10.1 DEFINITIONS APPLICABLE TO SECTION 10	13
10.2 OPERATING CHARACTERISTIC (OC) CURVES (TABLES 10-A TO 10-R)	13
10.3 AVERAGE OUTGOING QUALITY LIMIT (AOQL) (TABLES 5-A AND 5-B)	13
10.4 AVERAGE SAMPLE SIZE CURVES (TABLE 9)	13
10.5 LIMITING QUALITY (LQ) PROTECTION (TABLES 6-A, 6-B, 7-A AND 7-B)	13
10.6 USE OF TABLES B-1 AND B-2	13
TABLES	
1 Sample Size Code letters	14
2-A Single Sampling Plans for Normal Inspection (Master Table)	15
2-B Single Sampling Plans for Tightened Inspection (Master Table)	16
2-C Single Sampling Plans for Reduced Inspection (Master Table)	17
3-A Double Sampling Plans for Normal Inspection (Master Table)	18
3-B Double Sampling Plans for Tightened Inspection (Master Table)	19
3-C Double Sampling Plans for Reduced Inspection (Master Table)	20
4-A Multiple Sampling Plans for Normal Inspection (Master Table)	21
4-B Multiple Sampling Plans for Tightened Inspection (Master Table)	24
4-C Multiple Sampling Plans for Reduced Inspection (Master Table)	27
5-A Average Outgoing Quality Limit Factors for Normal Inspection (Single Sampling)	30
5-B Average Outgoing Quality Limit Factors for Tightened Inspection (Single Sampling)	31
6-A Limiting Quality (in percent nonconforming) for which $P_a = 10$ percent (for normal inspection, single sampling)	32
6-B Limiting Quality (in nonconformities per hundred items or units of product) for which $P_a = 10$ percent (for normal inspection, single sampling)	33
7-A Limiting Quality (in percent nonconforming) for which $P_a = 5$ percent (for normal inspection, single sampling)	34
7-B Limiting Quality (in nonconformities per hundred items or units of product) for which $P_a = 5$ percent (for normal inspection, single sampling)	35
8 Limit Numbers for Reduced Inspection	36
9 Average Sample Size Curves for Double and Multiple Sampling (Normal and Tightened Inspection)	37
10 Sampling Plans and Operating Characteristic Curves (and Data) for:	
-A Sample Size Code letter A	38
-B Sample Size Code letter B	40
-C Sample Size Code letter C	42
-D Sample Size Code letter D	44
-E Sample Size Code letter E	46
-F Sample Size Code letter F	48
-G Sample Size Code letter G	50
-H Sample Size Code letter H	52
-J Sample Size Code letter J	54
-K Sample Size Code letter K	56
-L Sample Size Code letter L	58
-M Sample Size Code letter M	60
-N Sample Size Code letter N	62
-P Sample Size Code letter P	64
-Q Sample Size Code letter Q	66
-R Sample Size Code letter R	68
-S Sample Size Code letter S	70

	<i>Page</i>
APPENDICES	
A Sequential Sampling	71
Table A-1 Sequential Sampling Plans for Normal Inspection (Master Table)	72
Table A-2 Sequential Sampling Plans for Tightened Inspection (Master Table)	73
B Probabilities of Finding No Nonconfirming Items in Samples	
Table B-1 Probability of Finding No Nonconfirming Items when Sample Size is less than 10 percent of Batch or Lot Size	74
Table B-2 Probability of Finding No Nonconfirming items when Sample Size is equal to or greater than 10 percent of Batch or Lot Size	81
(A) Sample size is 10 percent of batch or lot size	81
(B) Sample size is 15 percent of batch or lot size	86
(C) Sample size is 20 percent of batch or lot size	89
(D) Sample size is 25 percent of batch or lot size	93
(E) Sample size is 30 percent of batch or lot size	96
(F) Sample size is 35 percent of batch or lot size	99
(G) Sample size is 40 percent of batch or lot size	102
(H) Sample size is 45 percent of batch or lot size	105
(J) Sample size is 50 percent of batch or lot size	108

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard

SAMPLING PROCEDURES AND TABLES FOR INSPECTION BY ATTRIBUTES

SECTION 1. SCOPE AND GENERAL

1.1 SCOPE. This Standard establishes sampling plans and procedures for inspection by attributes.

The main sampling plans covered are single, double and multiple, but provision is also made for sequential sampling plans in Appendix A.

1.2 APPLICATION. The sampling plans are applicable to inspection of the following:

- End items
- Components and raw materials
- Operations
- Materials in process
- Supplies in storage
- Maintenance operations
- Data or records
- Administrative procedures.

A characteristic feature of these sampling plans is the switching procedure, which permits reduced inspection on processes of demonstrated high quality and requires tightened inspection on processes of demonstrated lesser quality. In some cases a user may feel the need to reduce inspection effort to even less than is provided by AS 1199—particularly with respect to suppliers of exceptionally and consistently high quality products. In such cases the user is advised to consult ISO Standard 2859/3, Sampling procedures for inspection by attributes, Part 3: Skip lot sampling plan.

The sampling plans and procedures are intended to be used primarily for a continuing series of batches or lots. They may also be used for the inspection of isolated batches or lots, but, the user is cautioned then to consult the operating characteristic curves to find a plan which will yield the desired protection (see Clause 10.5).

If no operating characteristic provides a satisfactory plan, the user is advised to consult ISO/2859/2—1985, sampling procedures for inspection by attributes, Part 2: Sampling plans indexed by limiting quality (LQ) for isolated lot inspection.

When specified by the responsible authority, this Standard shall be called up in the specification, contract, inspection instructions, or other documents, and the provisions in the Standard shall apply.

The responsible authority shall be nominated in one of the above documents.

1.3 REFERENCED DOCUMENTS. The following Standards are referred to in this Standard:

AS	
1057	Quality assurance and quality control—Glossary of terms
1399	Guide to AS 1199
ISO	
2859/2	Sampling procedures for inspection by attributes, Part 2: Sampling plans indexed by limiting quality (LQ) for isolated lot inspection
2859/3	Sampling procedure for inspection by attributes, Part 3: Skip lot sampling plan.

1.4 DEFINITIONS. For the purpose of this Standard the definitions in AS 1057 and the following apply:

1.4.1 Inspection—the activity of measuring, testing or otherwise examining goods and services (including, when appropriate, raw materials, components and intermediate assemblies) for determining conformity with the specified requirements.

1.4.2 Attribute—a characteristic which is appraised in terms of whether it does or does not meet (e.g. go or no-go) a given requirement.

1.4.3 Inspection by attributes—inspection wherein the item or unit of product is either classified simply as conforming or nonconforming, or the number of nonconformities in the item is counted, with respect to a given requirement or set of requirements.

1.4.4 Item or unit of product—an object or a defined quantity of goods and services on which an observation or a measurement may be made.

1.4.5 Responsible authority—the consumer or the contracting authority or a person authorized by them, to act in all matters related to the assurance of quality in relation to the supply of goods and services.