

Australian/New Zealand Standard™

Explosive atmospheres

**Part 18: Equipment protection by
encapsulation ‘m’**



AS/NZS 60079.18:2016

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee EL-014, Equipment for Explosive Atmospheres. It was approved on behalf of the Council of Standards Australia on 9 March 2016 and by the Standards New Zealand Approval Board on 20 April 2016. This Standard was published on 10 May 2016.

The following are represented on Committee EL-014:

Auckland Regional Chamber of Commerce
Australian Chamber of Commerce and Industry
Australian Industry Group
Australian Institute of Petroleum
Australian Petroleum Production and Exploration Association
Australian Pipelines and Gas Association
Aviation and Marine Engineers Association
Bureau of Steel Manufacturers of Australia
Department of Industry, Skills and Regional Development, NSW
Department of Natural Resources and Mines, Qld (SIMTARS)
Electrical Contractors Association of New Zealand
Electrical Regulatory Authorities Council
Engineers Australia
Institute of Electrical Inspectors
Institute of Instrumentation, Control and Automation Australia
Institution of Professional Engineers New Zealand
Mining Electrical and Mining Mechanical Engineering Society
SafeWork NSW
University of Newcastle
WorkSafe New Zealand

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com or Standards New Zealand web site at www.standards.govt.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of Standards Australia or the New Zealand Standards Executive at the address shown on the back cover.

This Standard was issued in draft form for comment as DR AS/NZS 60079.18:2015.

Australian/New Zealand Standard™

Explosive atmospheres

Part 18: Equipment protection by encapsulation 'm'

Originated in Australia as AS 2431—1981.
Previous edition AS/NZS 60079.18:2011.
Third edition 2016.

COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, PO Box 10729, Wellington 6011.

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee EL-014, Equipment for Explosive Atmospheres, to supersede AS/NZS 60079.18:2011.

The objective of this Standard is to establish the specific requirements for construction, testing and marking of electrical equipment, parts of electrical equipment and Ex components with the type of protection encapsulation ‘m’ intended for use explosive gas atmospheres or explosive dust atmospheres. The objective of the revision is to adopt the current edition of IEC 60079-18.

The particular requirements of this Standard supplement the general requirements specified in AS/NZS 60079.0. This Standard is intended to be read in conjunction with AS/NZS 60079.0.

This Standard is identical with, and has been reproduced from IEC 60079-18, Ed. 4.0 (2014), *Explosive atmospheres, Part 18: Equipment protection by encapsulation “m”*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) In the source text ‘this part of IEC 60079’ should read ‘this Australian/New Zealand standard’.
- (b) A full point substitutes for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to Australian or Australian/New Zealand Standards, as follows:

<i>Reference to International Standard</i>		<i>Australian/New Zealand Standard</i>	
IEC		AS/NZS	
60079	Explosive atmospheres	60079	Explosive atmospheres
60079-0	Part 0: Equipment—General requirements	60079.0	Part 0: Equipment—General requirements
60079-11	Part 11: Equipment protection by intrinsic safety “i”	60079.11	Part 11: Equipment protection by intrinsic safety ‘i’
60079-15	Part 15: Equipment protection by type of protection “n”	60079.15	Part 15: Equipment protection by type of protection ‘n’
60079-31	Part 31: Equipment dust ignition protection by enclosure “t”	60079.31	Part 31: Equipment dust ignition protection by enclosure ‘t’
61558	Safety of power transformers, power supplies, reactors and similar products	61558	Safety of power transformers, power supplies, reactors and similar products
61558-1	Part 1: General requirements and tests	61558.1	Part 1: General requirements and tests (IEC 61558-1 Ed 2.1, MOD)
61558	Safety of transformers, reactors, power supply units and similar products for supply voltages up to 1 100 V	61558	Safety of transformers, reactors, power supply units and similar products for supply voltages up to 1 100 V
61558-2-6	Part 2-6: Particular requirements and tests for safety isolating transformers and power supply units incorporating safety isolating transformers	61558.2.6	Part 2.6: Particular requirements and tests for safety isolating transformers and power supply units incorporating safety isolating transformers (IEC 61558-2-6 Ed 2, MOD)

Only normative references that have been adopted as Australian or Australian/New Zealand Standards have been listed.

The term ‘informative’ has been used in this Standard to define the application of the annex to which it applies. An ‘informative’ annex is only for information and guidance.

CONTENTS

1	Scope	8
2	Normative references	8
3	Terms and definitions	9
4	General	10
4.1	Level of protection (equipment protection level (EPL))	10
4.2	Additional requirements for levels of protection “ma” and “mb”	10
4.3	Additional requirements for level of protection “ma”	10
4.4	Rated voltage and prospective short circuit current	11
5	Requirements for compounds	11
5.1	General	11
5.2	Specification	11
5.3	Properties of the compound	11
5.3.1	Water absorption	11
5.3.2	Dielectric strength	11
6	Temperatures	12
6.1	General	12
6.2	Determination of the limiting temperatures	12
6.2.1	Maximum surface temperature	12
6.2.2	Temperature of the compound	12
6.3	Temperature limitation	12
7	Constructional requirements	12
7.1	General	12
7.2	Determination of faults	13
7.2.1	Fault examination	13
7.2.2	Components considered as not subject to fail	13
7.2.3	Isolating components	14
7.2.4	Infallible separation distances	14
7.3	Free space in the encapsulation	15
7.3.1	Group III “m” equipment	15
7.3.2	Group I and Group II “m” equipment	16
7.4	Thickness of the compound	17
7.4.1	“m” equipment	17
7.4.2	Windings for electrical machines	19
7.4.3	Rigid, multi-layer printed wiring boards with through connections	19
7.5	Switching contacts	20
7.5.1	General	20
7.5.2	Level of protection “ma”	21
7.5.3	Level of protection “mb”	21
7.5.4	Level of protection “mc”	21
7.6	External connections	21
7.6.1	General	21
7.6.2	Additional requirements for “ma” equipment	21
7.7	Protection of bare live parts	21
7.8	Cells and batteries	21
7.8.1	General	21

7.8.2	Prevention of gassing	22
7.8.3	Protection against inadmissible temperatures and damage to the cells or batteries	22
7.8.4	Reverse current	22
7.8.5	Current limitation	23
7.8.6	Protection against the polarity inversion and deep discharge of the cells	23
7.8.7	Charging of cells or batteries	23
7.8.8	Requirements for control safety devices for cells or batteries	24
7.9	Protective devices	24
7.9.1	General	24
7.9.2	Electrical protective devices	25
7.9.3	Thermal protective devices	25
7.9.4	Built-in protective devices	26
8	Type tests	26
8.1	Tests on the compound	26
8.1.1	Water absorption test	26
8.1.2	Dielectric strength test	26
8.2	Tests on the apparatus	26
8.2.1	Test sequence	26
8.2.2	Maximum temperature	27
8.2.3	Thermal endurance test	27
8.2.4	Dielectric strength test	28
8.2.5	Cable pull test	28
8.2.6	Pressure test for Group I and Group II electrical equipment	29
8.2.7	Test for resettable thermal protective device	30
8.2.8	Sealing test for built-in protective devices	30
9	Routine verifications and tests	30
9.1	Visual inspections	30
9.2	Dielectric strength test	30
10	Marking	31
	Annex A (informative) Basic requirements for compounds for “m” equipment	32
	Annex B (informative) Allocation of test samples	33
	Bibliography	34
	Figure 1 – Dimensional key for thickness through the compound	18
	Figure 2 – Minimum distances for multi-layer printed wiring boards	20
	Figure 3 – Fitting of blocking diodes	23
	Figure A.1 – Basic requirements for compounds for “m” equipment	32
	Table 1 – Distances through the compound	15
	Table 2 – Minimum thickness of compound adjacent to free space for Group III “m” equipment	16
	Table 3 – Minimum thickness of compound adjacent to free space for Group I and Group II “m” equipment	17
	Table 4 – Thickness of the compound	19

Table 5 – Minimum distances for multi-layer printed wiring boards	20
Table 6 – Test pressure	29
Table B.1 – Allocation of test samples	33

NOTES

NOTES

AUSTRALIAN/NEW ZEALAND STANDARD

Explosive atmospheres**Part 18:
Equipment protection by encapsulation 'm'****1 Scope**

This part of IEC 60079 gives the specific requirements for the construction, testing and marking of electrical equipment, parts of electrical equipment and Ex components with the type of protection encapsulation "m" intended for use in explosive gas atmospheres or explosive dust atmospheres.

This part applies only for encapsulated electrical equipment, encapsulated parts of electrical equipment and encapsulated Ex components (hereinafter always referred to as "m" equipment) where the rated voltage does not exceed 11 kV.

The application of electrical equipment in atmospheres, which may contain explosive gas as well as combustible dust simultaneously, may require additional protective measures.

This standard does not apply to dusts of explosives, which do not require atmospheric oxygen for combustion, or to pyrophoric substances

This standard does not take account of any risk due to an emission of flammable or toxic gas from the dust.

This standard supplements and modifies the general requirements of IEC 60079-0. Where a requirement of this standard conflicts with a requirement of IEC 60079-0, the requirement of this standard takes precedence.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60079-0, *Explosive atmospheres – Part 0: Equipment – General requirements*

IEC 60079-7, *Explosive atmospheres – Part 7: Equipment protection by increased safety "e"*

IEC 60079-11, *Explosive atmospheres – Part 11: Equipment protection by intrinsic safety "i"*

IEC 60079-15, *Explosive atmospheres – Part 15: Equipment protection by type of protection "n"*

IEC 60079-26, *Explosive atmospheres – Part 26: Equipment with equipment protection level (EPL) Ga*

IEC 60079-31, *Explosive atmospheres – Part 31: Equipment dust ignition protection by enclosure "t"*

IEC 60127 (all parts), *Miniature fuses*