AS 4002.1—2001
ISO 4406:1999

AS 4002.1

Australian Standard™

Hydraulic fluid power—Particulate contamination of systems

Part 1: Method for coding the level of contamination

[ISO title: Hydraulic fluid power—Fluids—Method for coding the level of contamination by solid particles]

Standards Australia

This Australian Standard was prepared by Committee ME-035, Fluid Power Systems and Components. It was approved on behalf of the Council of Standards Australia on 30 September 2001 and published on 12 October 2001.

The following interests are represented on Committee ME-035:

Australian Chamber of Commerce and Industry

Australian Industry Group

Australian Institute of Petroleum

Bureau of Steel Manufacturers Australia

Department of Defence (Australia)

Department of Mineral Resources, N.S.W.

Institution of Engineers Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

This Standard was issued in draft form for comment as DR 01138.

Australian Standard™

Hydraulic fluid power—Particulate contamination of systems

Part 1: Method for coding the level of contamination

Originated as part of AS 4002.1—1992.
Revised and designated in part as AS 4002.1—2001.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 4143 6

PREFACE

This Standard was prepared by the Standards Australia Committee ME-035, Fluid Power Systems and Components to supersede AS 4002.1—1992, *Fluid power systems and components—Cleanness levels in hydraulic systems,* Part 1: *Classification and determination of cleanness,* in part.

The objective of this Standard is to provide manufacturers and users of hydraulic fluid power systems with a code for defining the quantity of solid particles in the fluid in a given hydraulic fluid power system.

This edition introduces a three-part code for contamination levels measured with automatic particle calibrated in accordance with ISO 11171, *Hydraulic fluid power—Calibration of automatic particle counters for liquids*, and it also introduces equivalent particle sizes for such counters, based on calibration with NIST standard reference material SRM 2806.

The particle sizes to be reported for measurement by using a microscope, ≥5µm and ≥15µm, are unchanged from those specified in AS 4002.1—1992.

Defining the automatic particle counter code sizes in this way validates direct comparison of measurements made in accordance with this Standard using either measurement method, or between such measurements and data records based on AS 499.1:1992.

This Standard is identical with and has been reproduced from ISO 4406:1999, *Hydraulic fluid power—Fluids—Method for coding the level of contamination by solid particles.*

Statements expressed in mandatory terms in notes to text, tables and figures are deemed to be requirements of this Standard.

The term 'normative' has been used in this Standard to define the application of the annex to which it applies. A 'normative' annex is an integral part of a Standard.

As this Standard is reproduced from an International Standard, the following applies:

(a) Its number appears on the cover and title page while the International Standard number appears only on the cover.

(b) In the source text 'this International Standard' should read 'this Australian Standard'.

(c) A full point substitutes for a comma when referring to a decimal marker.

None of the documents referenced in this Standard has been adopted as an Australian Standard.

CONTENTS

1 Scope 1
2 Normative references 1
3 Code definition 1
4 Identification statement 4
Annex A Graphical presentation of the code number 5
Bibliography 7

NOTES

AUSTRALIAN STANDARD

Hydraulic fluid power—Particulate contamination of systems

Part 1:
Method for coding the level of contamination

1 Scope

This International Standard specifies the code to be used in defining the quantity of solid particles in the fluid used in a given hydraulic fluid power system.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 4407:1991, *Hydraulic fluid power — Fluid contamination — Determination of particulate contamination by the counting method using a microscope.*

ISO 11171:1999, *Hydraulic fluid power — Calibration of automatic particle counters for liquids.*

ISO 11500:1997, *Hydraulic fluid power — Determination of particulate contamination by automatic counting using the light extinction principle.*

3 Code definition

3.1 General

The purpose of this code is to simplify the reporting of particle count data by converting the numbers of particles into broad classes or codes, where an increase in one code is generally a doubling of the contamination level.

The original code in accordance with ISO 4406:1987 stated the reporting at two sizes, ⩾5 µm and ⩾15 µm, but the sizes in this revision have been changed to account for the use of a different calibration standard for optical automatic particle counters. The reported sizes are ⩾4 µm(c), ⩾6 µm(c) and ⩾14 µm(c), the last two of these being equivalent to the 5 µm and 15 µm particle sizes obtained using the ISO 4402:1991 method of calibrating automatic particle counters. ISO 4402:1991 has been replaced by ISO 11171:1999. Throughout this International Standard, the use of µm(c) means that particle size measurements are carried out using an automatic particle counter which has been calibrated in accordance with ISO 11171.

Measurement of particles using an optical microscope as specified in ISO 4407:1991 establishes the size of a particle as being equal to its longest dimension, whereas an automatic particle counter derives the size of an equivalent particle from its cross-sectional area, a value different in most cases from that determined using a microscope. The particle sizes to be reported for measurement by microscope, ⩾5 µm and ⩾15 µm, are unchanged from those specified in ISO 4406:1987.

 © Standards Australia