

AS 2799—1992

Australian Standard®

**Resistance welding equipment—
Single-phase a.c. transformer
type**

[Title allocated by Defence Cataloguing Authority:
RESISTANCE WELDING MACHINES, SINGLE PHASE—
TRANSFORMER TYPE (NSC 3432)]

This Australian Standard was prepared by Committee EL/19, Electrical Welding Plant. It was approved on behalf of the Council of Standards Australia on 7 May 1992 and published on 20 July 1992.

The following interests are represented on Committee EL/19:

Confederation of Australian Industry
Railways of Australia Committee
Welding Technology Institute of Australia

Additional interests participating in preparation of Standard:

Designers and manufacturers of resistance welding equipment
Motor-car manufacturers

***Review of Australian Standards.** To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 91192.

AS 2799—1992

Australian Standard®

**Resistance welding equipment—
Single-phase a.c. transformer
type**

First published in part as AS C356.1—1964.
AS C356.2 first published 1966.
AS C356.1—1964 and AS C356.2—1966 revised,
amalgamated and redesignated AS 2799—1985.
Second edition 1992.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 7541 7

PREFACE

This Standard was prepared by the Standards Australia Committee on Electrical Welding Plant to supersede AS 2799—1985. It incorporates substantial material from International Standard ISO 669:1981, *Rating of resistance welding equipment*, and includes a practical method of determining the rating of resistance welding equipment.

CONTENTS

| | <i>Page</i> |
|---|-------------|
| SECTION 1 SCOPE AND GENERAL | |
| 1.1 SCOPE | 3 |
| 1.2 REFERENCED DOCUMENTS | 3 |
| 1.3 DEFINITIONS | 3 |
| 1.4 SAFETY REQUIREMENTS | 6 |
| SECTION 2 TESTS | |
| 2.1 TEST CONDITIONS | 7 |
| 2.2 TYPE TESTS | 7 |
| 2.3 ROUTINE TESTS | 8 |
| SECTION 3 NAMEPLATES | |
| 3.1 GENERAL | 9 |
| 3.2 INFORMATION TO BE GIVEN ON NAMEPLATES | 9 |
| 3.3 SEAM WELDING EQUIPMENT | 9 |
| 3.4 BUTT WELDING EQUIPMENT | 9 |
| 3.5 VERIFICATION OF MARKINGS | 9 |
| APPENDICES | |
| A NOTES ON THERMAL TIME CONSTRAINTS | 10 |
| B DETERMINATION OF EQUIPMENT RATING | 12 |
| C MAXIMUM SHORT-CIRCUIT CURRENT TEST (MAXIMUM MOMENTARY INPUT CURRENT) | 16 |
| D MECHANICAL STRESS TEST | 18 |
| E IMPEDANCE RATIO TEST | 19 |
| F NO-LOAD CURRENT TEST | 19 |
| G OPEN-CIRCUIT SECONDARY VOLTAGE TEST | 20 |
| H COOLING WATER FLOW TEST | 20 |
| I WATER PRESSURE TEST | 20 |
| J HIGH VOLTAGE TEST | 21 |
| K INSULATION RESISTANCE TEST | 21 |
| L EXAMPLE OF A NAMEPLATE FOR RESISTANCE WELDING EQUIPMENT | 22 |

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS AUSTRALIA

Australian Standard

Resistance welding equipment—Single-phase a.c. transformer type

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE This Standard defines and specifies the characteristics of single-phase resistance welding equipment. It includes the information required on the equipment nameplate and specifies the test methods to be used to verify the compliance of the equipment with the requirements of this Standard.

NOTE: Appendix A gives information on thermal time constants.

It is applicable to single-phase resistance welding equipment, including all types of complete portable equipment, for use under the following conditions:

- (a) *Altitude* The altitude shall not exceed 1000 m.
- (b) *Cooling medium temperature* For water-cooled equipment, the temperature of the cooling water shall not exceed 30°C at the inlet of the equipment and, in the case of air-cooled equipment, none of the following limits shall be exceeded:
 - (i) Maximum ambient air temperature: 40°C.
 - (ii) Daily average ambient air temperature: 30°C.
 - (iii) Yearly average ambient air temperature: 20°C.
- (c) *Cooling water pressure* The pressure of the cooling water shall not be less than that which is necessary to supply the rated flow of cooling water.

This Standard does not apply to transformers sold separately or to capacitor discharge or rectifier equipment.

For a given voltage and frequency the characteristics of the equipment are calculated, constructed and tested, as a function of the following operational modes:

- (i) Intermittent operation at a duty cycle (see Clause 1.3.4) of 50%, the values of current and power being termed nominal or rated.
- (ii) Continuous operation, the values of current and power being termed continuous.

All voltages and currents shall be expressed as r.m.s. values.

1.2 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

Standards

- AS
2812 Welding, brazing and cutting of metals—Glossary of terms
3000 SAA Wiring Rules

Approval and test specifications

- AS
3100 General requirements for electrical equipment
IEC
Publication 85 Thermal evaluation and classification of electrical insulation

1.3 DEFINITIONS For the purpose of this Standard, the definitions given in AS 2812 and those below apply.

1.3.1 Continuous output current (I_{scn})—the output current corresponding to 100% duty cycle, the relationship with the nominal output current at 50% duty cycle being given by the equation:

$$I_{scn} = \frac{I_n}{\sqrt{2}}$$

1.3.2 Continuous power (P_{con})—the power corresponding to 100% duty cycle, the relationship with the nominal power at 50% duty cycle being given by the equation:

$$P_{con} = \frac{P_n}{\sqrt{2}}$$

1.3.3 Duty—a schedule of the loads on an apparatus or equipment, taking into account their respective duration and sequence.