

Australian Standard<sup>®</sup>

**Measurement of water flow in open  
channels**

**Part 2.4: General—Estimation of  
uncertainty of a flow rate measurement**



This Australian Standard® was prepared by Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 5 April 2007.  
This Standard was published on 6 August 2007.

---

The following are represented on Committee CE-024:

- Australian Industry Group
  - Australian National Committee on Irrigation and Drainage
  - Department of Environment and Water Resources
  - Institute of Instrumentation, Control and Automation Australia
  - Irrigation Association of Australia
  - National Measurement Institute
  - Plumbing Products Industry Group
  - University of New South Wales
  - University of South Australia
  - Water Services Association of Australia
- 

This Standard was issued in draft form for comment as DR 07107.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

---

### **Keeping Standards up-to-date**

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting **[www.standards.org.au](http://www.standards.org.au)**

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at **[mail@standards.org.au](mailto:mail@standards.org.au)**, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

---

Australian Standard<sup>®</sup>

## **Measurement of water flow in open channels**

### **Part 2.4: General—Estimation of uncertainty of a flow rate measurement**

Originated as AS 3778.2.4—1990.  
Third edition 2007.

#### **COPYRIGHT**

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia  
ISBN 0 7337 8308 2

## PREFACE

This Standard was prepared by the Standards Australia Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits, to supersede AS 3778.2.4—2001.

The objective of this Standard is to specify methods for measuring discharge in large rivers and estuaries by the moving-boat technique.

This Standard is identical to and reproduced from ISO 5168:2005, *Measurement of fluid flow—Procedures for the evaluation of uncertainties*.

As this Standard is reproduced from an international standard, the following applies:

- (a) Its number appears on the cover and title page while the international standard number appears only on the cover.
- (b) In the source text 'ISO 5168' should read 'AS 3778.2.4'.
- (c) A full point substitutes for a comma when referring to a decimal marker.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

## CONTENTS

	<i>Page</i>
<b>1</b>	<b>Scope .....</b> 1
<b>2</b>	<b>Normative references .....</b> 1
<b>3</b>	<b>Terms and definitions.....</b> 1
<b>4</b>	<b>Symbols and abbreviated terms .....</b> 3
<b>4.1</b>	<b>Symbols .....</b> 3
<b>4.2</b>	<b>Subscripts .....</b> 7
<b>5</b>	<b>Evaluation of the uncertainty in a measurement process.....</b> 8
<b>6</b>	<b>Type A evaluations of uncertainty .....</b> 9
<b>6.1</b>	<b>General considerations .....</b> 9
<b>6.2</b>	<b>Calculation procedure .....</b> 9
<b>7</b>	<b>Type B evaluation of uncertainties .....</b> 10
<b>7.1</b>	<b>General considerations .....</b> 10
<b>7.2</b>	<b>Calculation procedure.....</b> 10
<b>7.3</b>	<b>Rectangular probability distribution.....</b> 10
<b>7.4</b>	<b>Normal probability distribution .....</b> 11
<b>7.5</b>	<b>Triangular probability distribution .....</b> 11
<b>7.6</b>	<b>Bimodal probability distribution .....</b> 11
<b>7.7</b>	<b>Assigning a probability distribution .....</b> 11
<b>7.8</b>	<b>Asymmetric probability distributions .....</b> 11
<b>8</b>	<b>Sensitivity coefficients .....</b> 12
<b>8.1</b>	<b>General.....</b> 12
<b>8.2</b>	<b>Analytical solution.....</b> 12
<b>8.3</b>	<b>Numerical solution.....</b> 12
<b>9</b>	<b>Combination of uncertainties .....</b> 13
<b>10</b>	<b>Expression of results .....</b> 14
<b>10.1</b>	<b>Expanded uncertainty .....</b> 14
<b>10.2</b>	<b>Uncertainty budget .....</b> 15
<b>Annex A</b> (normative)	<b>Step-by-step procedure for calculating uncertainty .....</b> 17
<b>Annex B</b> (normative)	<b>Probability distributions .....</b> 20
<b>Annex C</b> (normative)	<b>Coverage factors.....</b> 22
<b>Annex D</b> (informative)	<b>Basic statistical concepts for use in Type A assessments of uncertainty .....</b> 24
<b>Annex E</b> (informative)	<b>Measurement uncertainty sources.....</b> 36
<b>Annex F</b> (informative)	<b>Correlated input variables .....</b> 38
<b>Annex G</b> (informative)	<b>Examples .....</b> 40
<b>Annex H</b> (informative)	<b>The calibration of a flow meter on a calibration rig.....</b> 58
<b>Annex I</b> (informative)	<b>Type A and Type B uncertainties in relation to contributions to uncertainty from “random” and “systematic” sources of uncertainty.....</b> 61
<b>Annex J</b> (informative)	<b>Special situations using two or more meters in parallel.....</b> 62
<b>Annex K</b> (informative)	<b>Alternative technique for uncertainty analysis.....</b> 64
<b>Bibliography</b>	<b>.....</b> 65

## INTRODUCTION

Whenever a measurement of fluid flow (discharge) is made, the value obtained is simply the best estimate that can be obtained of the flow-rate or quantity. In practice, the flow-rate or quantity could be slightly greater or less than this value, the uncertainty characterizing the range of values within which the flow-rate or quantity is expected to lie, with a specified confidence level.

GUM is the authoritative document on all aspects of terminology and evaluation of uncertainty and should be referred to in any situation where this International Standard does not provide enough depth or detail. In particular, GUM (1995), Annex F, gives guidance on evaluating uncertainty components.

---

**Australian Standard****Measurement of water flow in open channels**  
**Part 2.4: General—Estimation of uncertainty of a flow rate measurement**

---

**1 Scope**

This International Standard establishes general principles and describes procedures for evaluating the uncertainty of a fluid flow-rate or quantity.

A step-by-step procedure for calculating uncertainty is given in Annex A.

**2 Normative references**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9300, *Measurement of gas flow by means of critical flow Venturi nozzles*

*ISO Guide to the expression of uncertainty in measurement (GUM)*, 1995

*International vocabulary of basic and general terms in metrology (VIM)*, 1993

**3 Terms and definitions**

For the purposes of this document, the terms and definitions given in VIM (1993), GUM (1995) and the following apply.

**3.1  
uncertainty**

parameter, associated with the results of a measurement, that characterizes the dispersion of the values that could reasonably be attributed to the measurand

NOTE      Uncertainties are expressed as an absolute value and do not take a positive or negative sign.

**3.2  
standard uncertainty**

$u(x)$   
uncertainty of the result of a measurement expressed as a standard deviation

**3.3  
relative uncertainty**

$u^*(x)$   
standard uncertainty divided by the best estimate

NOTE 1     $u^*(x) = u(x)/x$ .

NOTE 2     $u^*(x)$  can be expressed either as a percentage or in parts per million.

NOTE 3    Relative uncertainty is sometimes referred to as dimensionless uncertainty.

NOTE 4    The best estimate is in most cases the arithmetic mean of the related uncertainty interval.