

Australian Standard[®]

Variable message signs

Part 1: Fixed signs



This Australian Standard® was prepared by Committee LG-006, Road traffic signals. It was approved on behalf of the Council of Standards Australia on 10 March 2009. This Standard was published on 10 April 2009.

The following are represented on Committee LG-006:

- ARRB Group
 - Australian Industry Group
 - AUSTROADS
 - Brisbane City Council
 - CIE Australia Inc.
 - Department for Transport, Energy and Infrastructure, South Australia
 - Hire and Rental Industry Association of Australia
 - IES: The Lighting Society
 - Lighting Council of Australia
 - Main Roads Department, Queensland
 - Roads and Traffic Authority of New South Wales
 - VicRoads
-

This Standard was issued in draft form for comment as DR 07369.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

Variable message signs

Part 1: Fixed signs

First published as AS 4852.1—2009.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7337 9120 4

PREFACE

This Standard was prepared by the Standards Australia Committee LG-006 on Road Traffic Signals.

This Standard forms Part 1 of the AS 4852 series, which covers requirements for the construction and performance of electrically powered variable message signs intended for use in road traffic management.

The objective of this Standard is to specify the requirements for the design and performance of variable message signs.

The series consists of the following Standards:

AS

- 4852 Variable message signs
- 4852.1 Part 1: Fixed signs (this Standard)
- 4852.2 Part 2: Portable signs

The use of any signs, including variable message signs, for road traffic management is subject to regulation by traffic control authorities. Guidance on and requirements relating to their use are provided in the series of Standards AS 1742, *Manual on uniform traffic control devices*.

Statements expressed in mandatory terms in notes (footnotes) to tables (figures) are deemed to be requirements of this Standard.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the Appendix to which they apply. A 'normative' Appendix is an integral part of a Standard, whereas an 'informative' Appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	4
1.2 APPLICATION	4
1.3 REFERENCED DOCUMENTS	4
1.4 DEFINITIONS	5
SECTION 2 GENERAL DESIGN AND ARRANGEMENT	
2.1 MECHANICAL REQUIREMENTS.....	8
2.2 ELECTRICAL REQUIREMENTS.....	12
2.3 COMMUNICATIONS EQUIPMENT	13
2.4 REAL-TIME CLOCK	13
2.5 MARKINGS AND LABELS.....	14
SECTION 3 DISPLAY AND OPTICAL REQUIREMENTS	
3.1 DISPLAY REQUIREMENTS	15
3.2 OPTICAL REQUIREMENTS	24
SECTION 4 OPERATION AND CONTROL	
4.1 GENERAL	26
4.2 LOCAL CONTROL	27
4.3 REMOTE CONTROL	27
4.4 PROGRAMMING	27
4.5 COMMUNICATIONS PROTOCOL	28
4.6 MONITORING, FAULT LOGGING AND REPORTING	28
4.7 FALL-BACK SYSTEM	29
4.8 SOFTWARE DEVELOPMENT	30
4.9 OPERATIONS AND MAINTENANCE MANUAL.....	30
SECTION 5 ENVIRONMENTAL REQUIREMENTS	
5.1 TEMPERATURE AND HUMIDITY	32
5.2 ENCLOSURE PROTECTION.....	32
5.3 WIND LOADING	32
5.4 ELECTROMAGNETIC COMPATIBILITY (EMC)	32
APPENDICES	
A SIGN CLEARANCES AND ACCESS.....	33
B CHARACTER FONTS.....	34
C PHOTOMETRIC TEST PROCEDURES	76
D COLORIMETRIC TEST PROCEDURES	80
E WIRELESS COMMUNICATIONS.....	81

STANDARDS AUSTRALIA

Australian Standard Variable message signs

Part 1: Fixed signs

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard covers electrically powered, on-road, variable message signs used for traffic management and/or driver information applications. Part 1 of the Standard covers 'Fixed Signs', where the display is mounted in a permanent position above or adjacent to the roadway. Part 2 of the Standard covers Portable Signs, where the display is mounted and deployed on a relocatable trailer.

While this Standard is based on systems that use the commonly available emitter, LED (Light Emitting Diodes), as the display source, the general criteria for driver observation, sign functionality and structural and operational integrity of the associated hardware are relevant for other forms of variable message signs. Relevant parts of this Standard can be applied to non-LED variable message signs. The Standard is not intended to exclude the use or development of alternative display sources.

It specifies the requirements for the design, construction, performance and certain aspects of the installation of electrically powered variable message signs, including their associated control systems.

The following types of message signs are not included within the scope of this Standard:

- (a) Information signs at bus stops, on train stations etc.
- (b) Variable message signs intended to advertise products and services to road users.
- (c) Signs that are only capable of displaying either a single message or a blank face.

1.2 APPLICATION

It is intended that variable message signs complying with this Standard be used to provide traffic-related information to motorists, cyclists and pedestrians. This includes real-time traffic information relating to incidents, roadworks and traffic times.

1.3 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

AS	
1657	Fixed platforms, walkways, stairways and ladders—Design, construction and installation
1742	Manual of uniform traffic control devices
1743	Road signs—Specifications
1744	Forms of letters and numerals for road signs (known as Standard alphabets for road signs)
2700	Colour Standards for general purposes