

Australian/New Zealand Standard™

**Stand alone maritime survivor locating  
systems (MSLS)**

**Part 2: Operating on frequencies other  
than 121.5 MHz**



## **AS/NZS 4869.2:2010**

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee RC-004, Radiocommunications Equipment—Maritime and Safety of Life. It was approved on behalf of the Council of Standards Australia on 9 December 2009 and on behalf of the Council of Standards New Zealand on 23 December 2009.

This Standard was published on 26 February 2010.

---

The following are represented on Committee RC-004:

Australian Communications and Media Authority  
Australian Industry Group  
Australian Maritime Safety Authority  
Australian Radio Communications Industry Association  
Civil Aviation Safety Authority  
Electromagnetic Technical Evaluation Committee  
Maritime NZ  
Ministry of Economic Development (New Zealand)  
Testing Interests (New Zealand)  
Yachting Australia

---

### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at [www.saiglobal.com.au](http://www.saiglobal.com.au) or Standards New Zealand web site at [www.standards.co.nz](http://www.standards.co.nz) and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

---

*This Standard was issued in draft form for comment as DR 09027.*

---

# Australian/New Zealand Standard™

## Stand alone maritime survivor locating systems (MSLS)

### Part 2: Operating on frequencies other than 121.5 MHz

First published as AS/NZS 4869.2:2010.  
Reissued incorporating Amendment No. 1 (August 2013).

#### **COPYRIGHT**

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140.

## PREFACE

This Standard was prepared by Joint Standards Australia/Standards New Zealand Committee RC-004, Radiocommunications Equipment—Maritime and Safety of Life.

*This Standard incorporates Amendment No. 1 (August 2013). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.*

The objective of this Standard is to provide the essential requirements for Maritime Survivor Locating Systems (MSLS) operating on frequencies other than 121.5 MHz. This Standard includes environmental, operational and radiofrequency requirements. These specifications are required by both the appropriate national spectrum management authority and maritime safety authority in each country.

This Standard is Part 2 of AS/NZS 4869, *Stand alone maritime survivor locating systems (MSLS)*, which consists of the following parts:

Part 1: Operating on 121.5 MHz

Part 2: Operating on frequencies other than 121.5 MHz (this Standard).

The term ‘normative’ has been used in this Standard to define the application of the appendix to which it applies. A ‘normative’ appendix is an integral part of a Standard.

## CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	4
1.2 APPLICATION .....	4
1.3 REFERENCED AND RELATED DOCUMENTS.....	5
1.4 DEFINITIONS.....	6
SECTION 2 ENVIRONMENTAL AND OPERATIONAL REQUIREMENTS	
2.1 GENERAL.....	9
2.2 OPERATIONAL REQUIREMENTS.....	10
2.3 BATTERY REQUIREMENTS .....	11
2.4 CLIMATIC AND DURABILITY REQUIREMENT .....	12
2.5 DOCUMENTATION.....	12
SECTION 3 MSLS RADIOFREQUENCY REQUIREMENTS	
3.1 GENERAL REQUIREMENTS.....	13
3.2 TYPE A MSLS TRANSMITTER REQUIREMENTS .....	14
3.3 UNIQUE IDENTIFIER .....	16
3.4 MSLS RECEIVER REQUIREMENTS FOR TYPE A AND TYPE B SYSTEMS.....	17
3.5 MSLS LOCATOR REQUIRMENTS.....	18
APPENDIX A CLIMATIC AND DURABILITY TESTS FOR MSLS TRANSMITTERS, RECEIVERS AND LOCATORS .....	19

## STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

**Australian/New Zealand Standard****Stand alone maritime survivor locating systems (MSLS)****Part 2: Operating on frequencies other than 121.5 MHz**

## SECTION 1 SCOPE AND GENERAL

**1.1 SCOPE**

This Standard provides the minimum requirements for Maritime Survivor Locating Systems (MSLSs) intended for very short-range crew retrieval applications operating on frequencies other than 121.5 MHz, commonly referred to as ‘man-overboard systems’. MSLS systems operating on 121.5 MHz are covered by AS/NZS 4869.1. The MSLS is designed to allow for self-help from the vessel or organization where there is a risk of crew falling overboard by sounding an alert from the onboard receiver.

Two basic principles of operation have been identified, as follows:

- (a) *Type A* A low power battery-operated transmitter is carried or worn by persons at risk of falling overboard. A receiver on the parent vessel continuously monitors the system’s designated frequency. If an incident occurs the transmitter involved is activated and the received signal initiates an alarm and may in some cases also be used for homing purposes to guide rescuers back to the casualty.
- (b) *Type B* Portable battery-powered radio transmitters are carried or worn by persons at risk of falling overboard. These emit a radio signal at frequent intervals which is coded to indicate the unique identity of each individual device. A receiver/decoder on the vessel is programmed to monitor these signals and to activate an alarm if the signal is not received. These systems are inherently fail safe because they activate when a signal is not detected.

The requirements in this Standard encompass the physical characteristics of the devices used in MSLS systems as they pertain to maritime use. For Type A MSLS transmitters, both the radiated power and the length of time for operation are reduced relative to conventional EPIRB type beacons, to enable the equipment to be sufficiently small and lightweight to be worn comfortably at all times when a person is operating in an open maritime environment.

MSLS may be developed and employed on certain approved frequencies. These may be frequencies covered by the Australian Communications and Media Authority’s Class licence for low interference potential devices (LIPDs) or the New Zealand Ministry of Economic Development’s General User Radio Licence (GURL) or on certain maritime frequencies such as the Digital Selective Calling (DSC) channel 70 VHF, and the radiotelephone channel 16 VHF, when such an arrangement has been authorized by the relevant regulators.

The technical requirements for equipment covered by the LIPD class licence or the GURL are contained in AS/NZS 4268.

**1.2 APPLICATION**

This Standard is intended for use by equipment designers, manufacturers and suppliers to ensure correct and reliable operation of Maritime Survivor Locating Systems operating on frequencies other than 121.5 MHz as set out in Clause 1.1.