

Australian Standard™

Railway track material

Part 12: Insulated joint assemblies

This Australian Standard was prepared by Committee CE-002, Railway Track Materials. It was approved on behalf of the Council of Standards Australia on 14 June 2002 and published on 1 August 2002.

The following are represented on Committee CE-002:

Australasian Railway Association
Australian Chamber of Commerce and Industry
Australian Industry Group
Bureau of Steel Manufactures of Australia
Rail Track Association Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

Railway track material

Part 12: Insulated joint assemblies

Originated as AS 1085.12—1987
Previous edition AS 1085.12—1999.
Third edition 2002.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 4613 6

PREFACE

This Standard was prepared by the Standards Australia Committee CE-002, Railway Track Materials, to supersede AS 1085.12—1999, *Railway permanent way material, Part 12: Insulated joint assemblies*.

The objective of this Standard is to provide manufacturers, specifiers and purchasers with performance requirements for insulated joints for use in railway track.

Changes to the previous edition are as follows:

- (a) Change of title of the AS 1085 series (previously *Railway permanent way material*).
- (b) The referenced documents list has been revised.
- (c) The most recent version of the informative Appendix 'Means of demonstrating compliance with this Standard' has been included.

Two joint grades are described to separate a joint's performance characteristics from its type of construction so that innovation is not stifled. Grade A would generally be for factory-assembled bonded joints, but if the performance requirements were satisfied, Grade A could include a high performance field joint. Also a reduced performance factory-assembled bonded joint might be classed as Grade B.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
1 SCOPE.....	4
2 PURPOSE AND CONTEXT OF USE	4
3 APPLICATION.....	4
4 REFERENCED DOCUMENTS	5
5 DEFINITIONS	5
6 METHOD OF SPECIFYING	7
7 PERFORMANCE REQUIREMENTS	7
8 MARKING.....	10

APPENDICES

A MEANS OF DEMONSTRATING COMPLIANCE WITH THIS STANDARD	11
B INFORMATION TO BE SUPPLIED BY THE PURCHASER AND THE SUPPLIER	13
C ELECTRICAL TEST.....	14
D PULL-APART TEST.....	15
E LOAD DEFLECTION TEST.....	17
F REPEATED LOAD FATIGUE TEST	19
G JOINT STRAIGHTNESS TEST	21
H HEAD HARDNESS TESTS	22

STANDARDS AUSTRALIA

Australian Standard Railway track material

Part 12: Insulated joint assemblies

1 SCOPE

This Standard specifies requirements for two grades of insulated joint assemblies. It covers insulated joints that are assembled in a factory (referred to in this Standard as ‘factory-assembled bonded insulated joints’) and joint components supplied as a kit for site assembly in track (‘field-assembled insulated joints’).

NOTES:

- 1 Insulated joints are not expansion joints.
- 2 Means of demonstrating compliance with this Standard are given in Appendix A.
- 3 Guidance on information to be provided by the purchaser and supplier is given in Appendix B.

2 PURPOSE AND CONTEXT OF USE

2.1 Function

Insulated joint assemblies join rails together in order to provide electrical isolation for signalling purposes between two lengths of rail in a railway track.

2.2 Action

Insulated joint assemblies are subject to—

- (a) electrical potential;
- (b) loads imposed by the passage of rolling stock and during maintenance;
- (c) stress generated by thermal effects; and
- (d) environmental exposure.

3 APPLICATION

Insulated joints may be specified as Grade A or Grade B in accordance with this Standard (see Appendix B).

NOTES:

- 1 The two grades specified in this Standard are intended to give the performance required for different intended uses. It is expected that Grade A would be used in main line and Grade B would be used in other applications. Grade B joints may be used in high traffic areas but a lower life would be expected.
- 2 Specimens prepared for testing field-assembled insulated joint systems are made under ‘ideal’ conditions that may not always be representative of the field environment. Factors such as poor alignment, variable surface condition, operator skill and weather conditions will mean that the test performance may not be achievable for field-assembled joints. In addition, factory-assembled joints will have head-hardened rail ends whereas field joints will not if the rails are not themselves head-hardened. Moreover, factory-assembled bonded joints are tested prior to supply and thus the properties can be guaranteed by the manufacturer. For these reasons specifiers of joints may need to select a factory-assembled joint over a field-assembled joint, dependent on actual application.