

Australian/New Zealand Standard™

**Oriented PVC (PVC-O) pipes for
pressure applications
(ISO 16422:2014, MOD)**



AS/NZS 4441:2017

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee PL-021, PVC, ABS and Polyamide Pipe Systems. It was approved on behalf of the Council of Standards Australia on 20 March 2017 and by the New Zealand Standards Approval Board on 5 April 2017. This Standard was published on 9 May 2017.

The following are represented on Committee PL-021:

Association of Accredited Certification Bodies
Australian Chamber of Commerce and Industry
Energy Networks Australia
Engineers Australia
Local Government New Zealand (LGNZ)
New Zealand Employers and Manufacturers Association (Central)
Chemistry Australia
Plastics Industry Pipe Association of Australia
Plastics New Zealand
Water New Zealand
Water Services Association of Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com or Standards New Zealand web site at www.standards.govt.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of Standards Australia or the New Zealand Standards Executive at the address shown on the back cover.

This Standard was issued in draft form for comment as DR2 AS/NZS 4441:2016.

Australian/New Zealand Standard™

Oriented PVC (PVC-O) pipes for pressure applications (ISO 16422:2014, MOD)

Originated as AS/NZS 4441(Int):1996.
Revised and redesignated as AS 4441(Int)—2003.
Revised and redesignated as AS/NZS 4441:2008.
Second edition 2017.

COPYRIGHT

© Standards Australia Limited

© The Crown in right of New Zealand, administered by the New Zealand Standards Executive

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, PO Box 1473, Wellington 6140.

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee PL-021, PVC, ABS and Polyamide Pipe Systems, to supersede AS/NZS 4441:2008.

The objective of this Standard is to specify the general aspects of pipes and joints made of oriented unplasticized poly(vinyl chloride) (PVC-O) for piping systems intended to be used underground or above-ground where not exposed to direct sunlight, for water mains and for services, for pressurized sewer systems and for irrigation systems.

This Standard is an adoption with national modifications and has been reproduced from ISO 16422:2014, *Pipes and joints made of oriented unplasticized poly(vinyl chloride) (PVC-O) for the conveyance of water under pressure—Specifications*. The modifications are additional requirements and are set out in Appendices ZZ and ZA. This revision contains the following key changes:

- (a) Table 4—Physical characteristics—Resistance to dichloromethane and alternative tests.
- (b) Annex A—Determination of pipe material classification—Procedures for classified and non-classified feedstock material.
- (c) Annex F—Determination of axial and tangential orientation factor.

Appendix ZA sets out means by which compliance with this Standard has to be demonstrated by a manufacturer.

Appendix ZB sets out the provisions for best environmental practice PVC for PVC-O pressure pipe. These provisions are in accordance with the credit criteria established by the Green Building Council of Australia in their Green Star rating program.

For best environmental practice PVC satisfying the provisions of Appendix ZB, an attestation of compliance for upstream materials such as chlorine and vinyl chloride, is necessary. Such attestations can take the form of a declaration of conformity prepared and maintained in accordance with ISO/IEC 17050, *Conformity assessment—Supplier's declaration of conformity*, Part 1: *General requirements*, and Part 2: *Supporting documentation*. Part 1 addresses the contents of the declaration of conformity and the procedures necessary to ensure ongoing compliance. Part 2 addresses the documentation required to support a declaration of conformity including the contents, traceability, availability and retention period.

Statements expressed in normative terms in notes to tables are deemed to be requirements of this Standard.

As this Standard is reproduced from an International Standard, the following applies:

- (i) In the source text 'this International Standard' should read 'this Australian/New Zealand Standard'.
- (ii) A full point substitutes for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to Australian or Australian/New Zealand Standards, as follows:

<i>Reference to International Standard</i>	<i>Australian/New Zealand Standard</i>
ISO	AS/NZS
2507 Thermoplastics pipes and fittings— Vicat softening temperature	1462 Methods of testing plastic pipes and fittings
2507-1 Part 1: General test method	1462.5 Method 5: Vicat softening temperature

The terms 'normative' and 'informative' have been used in this Standard to define the application of the annex or appendix to which they apply. A 'normative' annex or appendix is an integral part of a Standard, whereas an 'informative' annex or appendix is only for information and guidance.

CONTENTS

1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviated terms	5
	4.1 Symbols.....	5
	4.2 Abbreviations.....	6
5	Material	6
	5.1 General.....	6
	5.2 Rework material.....	6
6	Effect of materials on water quality	6
7	Material classification	6
	7.1 MRS value.....	6
	7.2 Design coefficient.....	6
	7.3 Design stress.....	7
8	Classification and selection of pipes	7
	8.1 Classification.....	7
	8.2 Calculation of wall thickness.....	8
	8.3 Determination of the allowable operating pressure, PFA, for temperatures up to 45 °C.....	8
	8.4 Derating factor related to application of the system.....	8
9	General requirements for pipes	10
	9.1 Appearance.....	10
	9.2 Opacity.....	10
10	Geometrical characteristics for pipes	10
	10.1 Measurement.....	10
	10.2 Outside diameters and wall thicknesses.....	10
	10.3 Pipes with integral sockets.....	10
	10.4 Plain ends.....	11
11	Mechanical characteristics of pipes	11
	11.1 Resistance to hydrostatic pressure.....	11
	11.2 Resistance to external blows at 0 °C.....	12
	11.3 Ring stiffness.....	12
12	Physical characteristics	12
13	Mechanical characteristics of assemblies, including joints	13
	13.1 Assemblies with non-end-load-bearing joints.....	13
	13.2 Short-term pressure test for leak tightness of assemblies.....	13
	13.3 Short-term negative pressure test for leak tightness of assemblies.....	15
	13.4 Long-term pressure test for leak tightness.....	15
	13.5 End-load-bearing joints — Pressure and bending test for leak tightness and strength.....	16
14	Elastomeric seals	16
15	Marking	16
	Annex A (normative) Establishment of the pipe material classification	17
	Annex B (informative) Minimum depth of engagement of sockets	18
	Annex C (normative) Temperature derating factor	21
	Annex D (informative) Ring stiffness of pipes	22
	Annex E (informative) Determination of the long-term test pressure by creep consideration	24
	Annex F (informative) Determination of axial and tangential orientation factor	25

INTRODUCTION

Molecular orientation of thermoplastics results in improvement of physical and mechanical properties. Orientation is carried out at temperatures well above the glass transition temperature.

Orientation of PVC-U pipe-material can be induced by different processes.

In general the following production process is common. A thick-wall tube is extruded (feedstock) and conditioned at the desired temperature. The orientation process is activated in circumferential and axial directions under controlled conditions.

After the orientation process, the pipe is cooled down quickly to ambient temperature.

The orientation of the molecules creates a laminar structure in the material of the pipe wall. This structure gives the ability to withstand brittle failure emanating from minor flaws in the material matrix or from scratches at the surface of the pipe wall. PVC-O can therefore be considered as highly resistant to notches and no testing is needed. Because of the morphology of oriented PVC-U pipe-material, there is no risk of long-line rapid crack propagation.

Improved hoop strength, allows reduced wall thickness with material and energy savings. Improved resistance to impact and fatigue also result.

The classification depends on material compound/formulation and stretch ratios used. Therefore, with the classification, these characteristics may be specified or determined.

Variations in stretch ratios should be within 10 % of the value determined on the pipes used for classification. The determination of the stretch ratios may be carried out as shown in [Annex F](#).

AUSTRALIAN/NEW ZEALAND STANDARD

**Oriented PVC (PVC-O) pipes for pressure applications
(ISO 16422:2014, MOD)****1 Scope**

This International Standard specifies the requirements of pipes and joints made of oriented unplasticized poly(vinyl chloride) (PVC-O), for piping systems intended to be used underground or above-ground where not exposed to direct sunlight, for water mains and services, pressurized sewer systems and irrigation systems.

The piping system according to this International Standard is intended for the conveyance of cold water under pressure, for drinking water and for general purposes up to and including 45 °C, and especially in those applications where special performance requirements are needed, such as impact loads and pressure fluctuations, up to pressure of 25 bars¹⁾.

Joints constructed of other materials should meet their own relevant standards in addition to the fitness-for-purpose requirements of this International Standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3:1973, *Preferred numbers — Series of preferred numbers*

ISO 161-1, *Thermoplastics pipes for the conveyance of fluids — Nominal outside diameters and nominal pressures — Part 1: Metric series*

ISO 1167-1, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 1: General method*

ISO 1167-2, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 2: Preparation of pipe test pieces*

ISO 1167-4, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 4: Preparation of assemblies*

ISO 1452-2:2009, *Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure — Unplasticized poly(vinyl chloride) (PVC-U) — Part 2: Pipes*

ISO 1452-5:2009, *Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure — Unplasticized poly(vinyl chloride) (PVC-U) — Part 5: Fitness for purpose of the system*

ISO 1628-2, *Plastics — Determination of the viscosity of polymers in dilute solution using capillary viscometers — Part 2: Poly(vinyl chloride) resins*

ISO 2505, *Thermoplastics pipes — Longitudinal reversion — Test method and parameters*

ISO 2507-1, *Thermoplastics pipes and fittings — Vicat softening temperature — Part 1: General test method*

1) 1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm²