

Australian Standard<sup>®</sup>

---

**HEARING AIDS**

**Part 0—MEASUREMENT OF  
ELECTROACOUSTICAL  
CHARACTERISTICS**

---

This Australian standard was prepared by Committee AK/11, Audiology. It was approved on behalf of the Council of the Standards Association of Australia on 25 November 1986 and published on 2 February 1987.

---

The following interests are represented on Committee AK/11:

Audiological Society of Australia  
Better Hearing Australia  
Department of Defence  
Hearing Aid Council of Australia  
National Acoustical Laboratories  
Otolaryngological Society of Australia  
State Pollution Control Commission of New South Wales  
University of Melbourne  
University of Queensland

---

***Review of Australian Standards.** To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

*Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.*

*Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.*

---

*This Standard was issued in draft form for comment as DR 85266.*

Australian Standard<sup>®</sup>

---

**HEARING AIDS**

**Part 0—MEASUREMENT OF  
ELECTROACOUSTICAL  
CHARACTERISTICS**

---

AS 1088 first published . . . . .	1971
AS 1088.0 separately published . . . . .	1987

PUBLISHED BY STANDARDS AUSTRALIA  
(STANDARDS ASSOCIATION OF AUSTRALIA)  
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 4495 3

## PREFACE

This standard was prepared by the Association's Committee on Audiology. It is identical with and has been reproduced from IEC Publication 118—0, Hearing Aids, Part 0: Measurement of Electroacoustical Characteristics. It supersedes (in part) AS 1088—1971, Methods of Measurement of the Electro-acoustic Characteristics of Air Conduction Hearing Aids.

The purpose of this standard is to specify methods which are practical and reproducible for the measurement and evaluation of the electroacoustical characteristics of air-conduction hearing aids.

For the purpose of this Australian standard, the text of the IEC standard used herein should be modified as follows:

*Cross-references:* The references to IEC standards should be replaced by references to Australian standards as follows:

*Reference to IEC standard*

IEC 68, Basic Environment Testing Procedures

IEC 118-1, Hearing Aids, Part 1: Hearing Aids with Induction Pick-up Coil Input

IEC 118-2, Hearing Aids, Part 2: Hearing Aids with Automatic Gain Control Circuits

IEC 118-7, Hearing Aids, Part 7: Measurement of Performance Characteristics of Hearing Aids for Quality Inspection for Delivery Purposes

IEC 118-8: Hearing Aids, Part 8: Methods of Measurement of Performance Characteristics of Hearing Aids Under Simulated in Situ Working Conditions

IEC 126: IEC Reference Coupler for the Measurement of Hearing Aids Using Earphones Coupled to the Ear By Means of Ear Inserts

IEC 225: Octave, Half-octave and Third-octave Band Filters Intended for the Analysis of Sound and Vibrations

IEC 711, Occluded-ear Simulator for the Measurements of Earphones Coupled to the Ear by Ear Inserts

*Appropriate Australian standard*

AS 1099, Basic Environmental Testing Procedures for Electrotechnology

AS 1088.1, Hearing Aids, Part 1—Hearing Aids with Induction Pick-up Coil Input

AS 1088.2, Hearing Aids, Part 2—Hearing Aids with Automatic Gain Control Circuits

AS 1088.7, Hearing Aids, Part 7—Measurement of Performance Characteristics of Hearing Aids for Quality Inspection for Delivery Purposes

AS 1088.8, Hearing Aids, Part 8—Methods of Measurement of Performance Characteristics of Hearing Aids Under Simulated In Situ Working Conditions

AS 1089, Reference Coupler for the Measurement of the Electroacoustic Characteristics of Hearing Aid Earphones

AS Z41, Octave, Half-octave and One third Octave Band Pass Filters Intended for the Analysis of Sound and Vibrations

AS 2928, Occluded-ear Simulator for the Measurements of Earphones Coupled to the Ear by Ear Inserts

## © Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## CONTENTS

Clause	Page
1. Scope	4
2. Object	4
3. General conditions	5
4. Explanation of terms	5
4.1 Ear simulator	5
4.2 Substitution method	5
4.3 Comparison method	5
4.4 Pressure method	5
4.5 Simulated <i>in situ</i> method	5
4.6 Reference orientation (of a hearing aid)	5
4.7 Reference point (of a hearing aid)	6
4.8 Test point	6
4.9 Supply voltage	6
4.10 Acoustic gain	6
4.11 Full-on acoustic gain (frequency response curve)	6
4.12 Maximum acoustic gain at a specified frequency	6
4.13 Saturation sound pressure level (frequency response curve)	6
4.14 Maximum saturation sound pressure level	6
4.15 Output sound pressure level for an input sound pressure level of 90 dB (OSPL <sub>90</sub> ) at a specified frequency (or frequencies)	6
4.16 Reference test frequency	6
4.17 Reference test gain control position	7
4.18 Reference test gain	7
4.19 Frequency response	7
4.20 Comprehensive frequency response curves	7
4.21 Basic frequency response curve	7
4.22 Steady state input-output graph	7
5 Test equipment	7
5.1 Acoustical requirements for the test enclosure	7
5.2 Sound field at the test point	8
5.3 Ear simulator	8
5.4 Equipment for the measurement of sound pressure level in the ear simulator	8
5.5 Equipment for automatic sweep frequency recording	9
5.6 Calibration of free-field sound pressure level	9
6 Test conditions	9
6.1 Choice of test point	9
6.2 Calibrating the sound field	10
6.3 Locating the hearing aid for tests	10
6.4 Normal operating conditions for the hearing aid	11
7 Measurements	12
7.1 Maximum saturation sound pressure level	12
7.2 Output sound pressure level frequency response for an input SPL of 90 dB	12
7.3 Full-on acoustic gain frequency response	13
7.4 Comprehensive frequency responses and basic frequency response	13
7.5 Effect of tone control position on the basic frequency response	14
7.6 Effect of gain control position on frequency response	14
7.7 Characteristics of the gain control	15
7.8 Effect on the full-on acoustic gain of variation of battery or supply voltage	15
7.9 Effect on the full-on acoustic gain of variation of internal resistance of battery or supply	15
7.10 Effect on OSPL <sub>90</sub> of variation of battery or supply voltage	16
7.11 Battery current	16
7.12 Measurement of amplitude non-linearities in hearing aids	16
7.13 Effect on amplitude non-linearities of variation of battery or supply voltage and internal impedance	19
7.14 Internal noise generated in the hearing aid	19
7.15 Characteristics of hearing aid with induction pick-up coil input	20
7.16 Characteristics of hearing aids with automatic gain control circuits	22
8. Frequency response recording chart	22
APPENDIX A — Harmonic and intermodulation distortion	23

## STANDARDS ASSOCIATION OF AUSTRALIA

**Australian Standard**

for

**HEARING AIDS**

## PART 0—MEASUREMENT OF ELECTROACOUSTICAL CHARACTERISTICS

**1. Scope**

This standard describes the measurement of physical performance characteristics of air-conduction hearing aids based on a free-field technique and measured with an ear simulator.

**2. Object**

- 2.1 The object of this standard is to describe methods of measurement for the evaluation of the electroacoustical characteristics of hearing aids.

The methods are chosen first of all to be practical and reproducible, and consequently they are based on fixed parameters chosen, to a certain extent, arbitrarily. This should be taken into consideration when comparisons are being made between test results for hearing aids of different models and manufacture, and in each case it is advisable to examine to what extent the arbitrarily chosen parameters will influence the comparison of such test results.

- 2.2 The test results obtained by the methods specified in this standard express the performance under the conditions of the test and may deviate substantially from the performance of the hearing aid under practical conditions of use.
- 2.3 It is not the purpose of this standard to restrict the variety of hearing aid performance and characteristics available, nor to inhibit in any way advances in the state of the art.
- 2.4 The most significant change in this standard is the use of an ear simulator in accordance with IEC Publication 711: Occluded-ear Simulator for the Measurement of Earphones Coupled to the Ear by Ear Inserts, rather than an acoustic coupler, IEC Publication 126: IEC Reference Coupler for the Measurement of Hearing Aids Using Earphones Coupled to the Ear by Means of Ear Inserts. The effect of this change will be to give an apparent significant increase, at some frequencies, of both gain and saturation output levels over the results obtained when measurements are made with the acoustic coupler. Results obtained by using the methods described in this standard cannot therefore be directly compared with those previously obtained using the first edition of IEC Publication 118: Recommended Methods for Measurement of the Electroacoustical Characteristics of Hearing Aids, or IEC Publication 118-7: Hearing Aids, Part 7: Measurement of Performance Characteristics of Hearing Aids for Quality Inspection for Delivery Purposes, or IEC Publication 118-8: Part 8: Methods of Measurement of Performance Characteristics of Hearing Aids under Simulated *in situ* Working Conditions. (In preparation.)