

Australian Standard[®]

**ROTATING
ELECTRICAL MACHINES
OF PARTICULAR TYPES
OR FOR PARTICULAR
APPLICATIONS**

**Part 11—Dimensions and
Performance of Small Power
Electrical Machines**

This part of the standard, prepared by Committee EL/9, Rotating Electrical Machinery, was approved on behalf of the Council of the Standards Association of Australia on 8 November 1979, and was published on 1 February 1980.

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

PREFACE

This revised edition of AS 1360, Part 11—1977 was prepared by the Association's Committee on Rotating Machines.

The revision was undertaken in response to requests from the industry to permit shaft extensions of smaller diameter for low-load applications. The opportunity was also taken to make other necessary changes.

The revision differs from the original as follows:

- (a) Shaft extensions of smaller diameter are specified for frame numbers S80 and S90 for limited torque applications where mechanical adequacy is assured (see Table 11.5.1, frame numbers S80-14 and S90-16).
- (b) Descriptions of dimensional symbols have been clarified; redefined symbols ED and ES replace previously specified EB and EC (see Fig. 11.5.1).
- (c) The application of limits of shaft extension runout has been extended to all machines (see Clause 11.5.1).
- (d) The tolerance on H for resilient-mounted frames has been considerably increased (see Table 11.6.1).

It is recognized in practice that there is some overlap between this part and Part 10 which specifies dimensions of three-phase electric motors. Motors of certain rating may be constructed to comply with either this part or Part 10; mechanical considerations may require a heavier form of construction, e.g. a larger shaft extension (see Note to Table 11.5.1), in which case reference should be made to Part 10.

In the application of this part, reference may be necessary to be following standards:

AS 1044	Limits of Electromagnetic Interference for Electrical Appliances and Equipment
AS 1110	ISO Metric Hexagon Precision Bolts and Screws
AS 1275	Metric Screw Threads for Fasteners (Based on ISO Recommendations)
AS 1359	General Requirements for Rotating Electrical Machines Part 1—Definitions Part 20—Classification of Types of Enclosure* Part 21—Classification of Methods of Cooling Part 22—Classification of Mounting Arrangements and Types of Construction Part 51—Noise Level Limits
AS 1360	Rotating Electrical Machines of Particular Types or for Particular Applications Part 10—Dimensions and Outputs of Standard Single-speed Three-phase General Purpose Motors
AS 1654	Limits and Fits for Engineering

AS C98	Flameproof Enclosure of Electrical Equipment for Explosive Atmospheres
AS C320	Classification of Insulating Materials for Electrical Machinery and Apparatus on the Basis of Thermal Stability in Service
BS 2725	Memorandum on the Measurement of Cooling Medium Temperature when Testing Electrical Machines, Transformers and Other Electrical Apparatus
BS 4235	Metric Keys and Keyways Part 1—Parallel and Taper Keys

* In course of preparation. Meanwhile reference may be made to AS 1939 Classification of Degrees of Protection Provided by Enclosures for Electrical Equipment.

First published	1977
Revised	1980

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

Page

SPECIFICATION

11.1	Scope	11-5
11.2	Definitions	11-5
11.3	Frame Nomenclature	11-6
11.4	Symbols for Dimensions and Tolerances	11-8
11.5	Shaft Extensions	11-8
11.6	Frame and Fixing Dimensions	11-10
11.7	Service Conditions	11-14
11.8	Operating Conditions	11-14
11.9	Classes of Rating	11-14
11.10	Output Ratings	11-14
11.11	Preferred Output Ratings	11-14
11.12	Voltage Ratings	11-14
11.13	Preferred Voltages, Frequency, Phases and Speeds	11-14
11.14	Motors with Multiple Ratings	11-14
11.15	Limits of Temperature Rise	11-14
11.16	Methods of Temperature Measurement to be Employed	11-15
11.17	Measurement of Temperature	11-16
11.18	Adjustments Permitted to Limits of Temperature Rise for Service Conditions Involving Non-standard Gaseous Coolant Temperatures and Altitudes	11-16
11.19	Adjustments to Temperature Rise for Test Conditions	11-17
11.20	Torque Characteristics and Locked-rotor kV.A of Induction Motor	11-17
11.21	Induction Motor Applications	11-17
11.22	Momentary Overload	11-17
11.23	Overspeed	11-18
11.24	Commutation	11-18
11.25	Noise Levels	11-18
11.26	Vibration	11-18
11.27	Ruling Plate Marking	11-18
11.28	Tests	11-19
11.29	Tolerances	11-20
11.30	Information to be Given by the Purchaser with Enquiry and Order	11-21

TABLES

11.4.1	Symbols for Mandatory Dimensions	11-7
11.4.2	Symbols for Non-mandatory Dimensions	11-8
11.5.1	Permissible Frame/Shaft Combinations	11-8
11.5.2	Dimensions of Shaft Extensions and Flats	11-9
11.6.1	Fixing Dimensions of Foot-mounted and Resilient-mounted Frames	11-11
11.6.2	Fixing Dimensions of Flange-mounted Frames	11-13
11.6.3	Fixing Dimensions of Face-flange-mounted Frames	11-13
11.15	Limit of Permissible Temperature Rise	11-15
11.20	Classification of Torque Characteristics	11-18
11.22	Momentary Overload for Motors	11-18
11.28	High Voltage Tests — Withstand Voltages	11-20
11.29	Tolerance Values	11-21

FIGURES

11.5.1	Shaft Extension with Flat	11-9
11.5.2	Shaft Extension with Keyway (Shaft Number 19 only)	11-9
11.5.3	Measurement of Shaft Extension Runout	11-10
11.5.4	Measurement of Concentricity and Perpendicularity	11-10
11.6.1	Symbols for Foot-mounted Frames	11-11
11.6.2	Symbols for Resilient-mounted Frames	11-11
11.6.3	Symbols for Flange-mounted Frames	11-12
11.6.4	Symbols for Face-flange-mounted Frames	11-12

APPENDICES

11A	Measurement of Final Temperatures of Machines: Guidance or Method of Extrapolation	11-23
11B	A Speed/Torque Curve of Cage Induction Motor to Illustrate Terms Used	11-24
11C	Application of Induction Motors	11-25

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard
for
ROTATING ELECTRICAL MACHINES OF PARTICULAR TYPES AND
FOR PARTICULAR APPLICATIONS

PART 11. DIMENSIONS AND PERFORMANCE OF SMALL POWER
ELECTRIC MACHINES

11.1 SCOPE. This Part of this standard specifies the dimensions and performance of a.c., d.c., and universal type electrical machines intended for applications for which a lighter construction than that specified in AS 1360, Part 10 is adequate and having the following characteristics:

- (a) Foot, flange, face-flange or resilient mounting.
- (b) Sleeve or rolling bearings.
- (c) Any type of enclosure.
- (d) A rated voltage up to and including 240 V d.c., 480 V single-phase a.c., or 650 V three-phase a.c.
- (e) A continuous rated output (or equivalent continuous rated output for short-time rated machines) up to and including 0.75 kW (or kV.A) for each 1000 r/min of the rated speed (or synchronous speed for a.c. machines).

NOTE: It is recognized that in practice there is some overlap between the ratings covered by this Part and those covered by Part 10: e.g. motors of certain ratings may be constructed to comply either with this Part or with Part 10 but not necessarily with both.

11.2 DEFINITIONS.* For the purpose of this Part, the following definitions apply:

11.2.1 General Definitions.

11.2.1.1 Rotating electrical machine — an electrical apparatus depending upon electromagnetic induction for its operation and having components capable of relative rotary movement and intended for converting energy.

11.2.1.2 General purpose machine — any machine designed, listed and offered in standard ratings with operating characteristics and mechanical construction suitable for use under usual service conditions without restrictions to a particular application or type of application.

11.2.1.3 Universal motor — a motor which can be operated by either direct current or single phase alternating current of normal frequencies.

11.2.1.4 Adjustable-speed motor — a motor the speed of which can be adjusted to any value in a specified range.

11.2.1.5 Multi-speed motor — a motor which can be operated at any one of two or more speeds which are

substantially constant over its normal range of loads.

11.2.2 Cooling.

11.2.2.1 Cooling — a procedure by means of which heat resulting from losses occurring in a machine is given up first to a primary coolant by increasing its temperature. The heated primary coolant may be replaced by new coolant at a lower temperature or may be cooled by a secondary coolant in some form of heat exchanger.

11.2.2.2 Open circuit cooling — a method of cooling in which the coolant is drawn from the medium surrounding the machine, passes through the machine and then returns to the surrounding medium.

11.2.2.3 Closed circuit cooling — a method of cooling in which a primary coolant is circulated in a closed circuit through the machine and, if necessary, through a heat exchanger. Heat is transferred from the primary coolant to the secondary coolant through the structural parts or in the heat exchanger.

11.2.2.4 Air-over-machine (AOM) cooling — a method of cooling where the machine is located in an air stream, the source of air movement not being an integral part of the machine.

11.2.3 Duty and Duty Cycles.

11.2.3.1 Duty — a statement of the loads, including no-load and rest and de-energized periods, to which a machine is subjected, including their duration and sequence in time.

11.2.3.2 Duty cycle — a variation of load with time in which the cycle time is too short for thermal equilibrium to be attained.

11.2.3.3 Cyclic duration factor — the ratio between the period of loading including starting and electric braking and the duration of the duty cycle, expressed per unit.

11.2.4 Loads.

11.2.4.1 Load — all the numerical values of the electrical and mechanical quantities that signify the demand to be made at a given instant on a rotating machine by an electric circuit or a mechanism.

11.2.4.2 No-load — the state of a machine rotating at normal speed under rated conditions but when no output is required of it.

* Definitions from Part 1 of AS 1359 are included here for convenience.